

PROMAR VARNISH SANDING SEALER, B26 V3

MSDS Number

BXHKC

National Stock Number

8010-01-397-3882

Product Name

PROMAR VARNISH SANDING SEALER, B26 V3

Manufacturer

SHERWIN WILLIAMS CO

Product Identification

Product ID: PROMAR VARNISH SANDING SEALER, B26 V3

MSDS Date: 03/01/1991

FSC: 8010

NIIN: 01-397-3882

MSDS Number: BXHKC

Responsible Party

SHERWIN-WILLIAMS CO

101 PROSPECT AVE N W

CLEVELAND , OH 44115-1042

US

Emergency Phone: 216-566-2917

Info Phone: 216-566-2902

Cage: 54636

Contractor

SHERWIN-WILLIAMS CO THE

CLEVELAND, OH 44115-1042

US

800-251-2486/216-566-2242

Cage: 54636

Ingredients

V.M. & P. NAPHTHA (VAPOR PRESSURE 12.0 MM HG)

CAS: 64742-48-9

Fraction By Weight: 40-60%

OSHA PEL300 PPM; STEL 400 PPM

ACGIH TLV: 300 PPM

MINERAL SPIRITS (VAPOR PRESSURE 2.0 MM HG)

CAS: 64742-47-8

Fraction By Weight: 5-25%

OSHA PEL100 PPM

ACGIH TLV: 100 PPM

VOC (THEORETICAL) 4.49-4.51 LB

RTECS: 9999999VO

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:IRRIT OF EYES,SKIN & RESPIRATORY SYSTEM. MAY CAUSE NERVOUS SYSTEM DEPRESSION. EXTREME OVEREXPOSURE MAY RESULT IN UNCONSCIOUSNESS, POSSIBLY DEATH. HEADACHE, DIZZY, NAUSEA, LOSS OF COORDINATION ARE INDICATION OF EXCESSIVE OVEREXPOSURE TO VAPORS OR SPRAY MISTS. REDNESS, ITCHING, BURNING MAY INDICATE EXCESSIVE EXPOSURE.
Effects of Overexposure:REPORTS HAVE ASSOCIATED REPEATED AND PROLONGED OVEREXPOSURE TO SOLVENTS WITH BRAIN AND NERVOUS SYSTEM DAMAGE. PROLONGED OVEREXPOSURE TO SOLVENT INGREDIENTS IN SECTION II MAY CAUSE ADVERSE EFFECTS TO THE LIVER, AND URINARY SYSTEMS.

First Aid

First Aid:INHALATION: IF AFFECTED, REMOVE FROM EXPOSURE. RESTORE BREATHING. KEEP WARM & QUIET. SKIN: WASH AFFECTED AREA THOROUGHLY WITH SOAP & WATER. REMOVE CONTAMINATED CLOTHING & WASH BEFORE REUSE. EYE: FLUSH WITH LARGE AMOUNT OF WATER FOR 15 MINUTES. GET MEDICAL ATTENTION. SWALLOWING: GET MEDICAL ATTENTION.

Fire Fighting

Flash Point Method:PMCC
Flash Point:44.0F,6.7C
Lower Limits:0.9
Upper Limits:6.0
Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL, FOAM
Fire Fighting Procedures:USE FULL PROTECT EQUIP W/SCBA. WATER MAY BE INEFFECTIVE. IF USED FOG NOZZLES PREFERRED. USE TO COOL CLOSED CNTNR/PREVENT PRESSURE, AUTOIGNITION, OR EXPLOSION.
Unusual Fire/Explosion Hazard:CLOSED CNTNR MAY EXPLODE (DUE TO BUILD UP PRESSURE) WHEN EXPOSED TO EXTREME HEAT.

Accidental Release

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. VENTILATE AND REMOVE WITH INERT ABSORBENT.

Handling

Handling and Storage Precautions:CONTENTS ARE COMBUSTIBLE. KEEP FROM HEAT/FLAME. CONSULT NFPA CODE. USE APPROVED BONDING, GROUNDING PROCEDURES. KEEP CLOSED WHEN NOT IN USE.**
Other Precautions:**TRANSFER ONLY TO APPROVED CONTAINERS WITH COMPLETE & APPROPRIATE LABELS. DO NOT TAKE INTERNALLY. KEEP OUT OF REACH OF CHILDREN.INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING/INHALING CONTENTS CAN BE HARMFUL OR FATAL.

Exposure Controls

Respiratory Protection:IF EXPOSURE CANNOT BE CONTROLLED VENTILATION, WEAR NIOSH/MSHA APPROVED ORGANIC VAPOR/PARTICULATE RESPIRATOR. WHEN SANDING/ABRADING DRIED FILM, WEAR NIOSH/MSHA APPROVED DUST/MIST RESP GENERATED FROM PRODUCT, PAINT, OR ABRASIVE.
Ventilation:LOCAL EXHAUST PREFERRED. GEN EXHAUST ACCEPTABLE IF EXPOSURE MAINTAINED
Protective Gloves:RECOMMENDED BY GLOVE SUPPLIER
Eye Protection:SAFETY GLASSES/UNPERFORATED SIDESHIELDS
Work Hygienic Practices:WASH HANDS AFTER USING
Supplemental Safety and Health
USE ONLY WITH ADEQUATE VENTILATION. AVOID BREATHING VAPOR AND SPRAY MIST. AVOID CONTACT WITH EYES & SKIN.

Chemical Properties

Boiling Pt:B.P. Text:240 TO 395F
Vapor Density:>AIR
Spec Gravity:0.82
Evaporation Rate & Reference:Percent Volatiles by Volume:72%

Stability

Stability Indicator/Materials to Avoid: YES

Hazardous Decomposition Products: BY FIRE: CARBON DIOXIDE, CARBON MONOXIDE

Disposal

Waste Disposal Methods: WASTE MAY BE HAZARDOUS AS DEFINED UNDER (RCRA) 40 CFR 261. WASTE MUST BE TESTED FOR IGNITABILITY TO DETERMINE THE APPLICABLE EPA HAZ. INCINERATE IN APPROVED FACILITY. DO NOT INCINERATE CLSD CONTAINER. DISPOSE OF IN ACCORD W/FED, STATE, & LOCAL REGS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.