

SOLID COLOR STAIN, A14

MSDS Number

BXHLD

National Stock Number

8010-01-397-3921

Product Name

SOLID COLOR STAIN, A14

Manufacturer

THE SHERWIN WILLIAMS CO

Product Identification

Product ID:SOLID COLOR STAIN, A14

MSDS Date:03/01/1991

FSC:8010

NIIN:01-397-3921

MSDS Number: BXHLD

Responsible Party

THE SHERWIN-WILLIAMS CO

101 PROSPECT AVE N W

CLEVELAND , OH 44115

US

Emergency Phone: 216-566-2917

Info Phone: 216-566-2902

Cage: DO693

Contractor

THE SHERWIN-WILLIAMS CO

CLEVELAND, OH 44115

US

216-566-2902

Cage: DO693

Ingredients

MINERAL SPIRITS (VAPOR PRESSURE 2.0 MM HG)

CAS: 64742-47-8

Fraction By Weight: 40-44%

OSHA PEL100 PPM

ACGIH TLV: 100 PPM

MINERAL SPIRITS, 140 FLASH (VAPOR PRESSURE 0.5)

CAS: 64475-85-0

RTECS: PY8240000

Fraction By Weight: 40-44%

OSHA PEL100 PPM

ACGIH TLV: 100 PPM

TITANIUM DIOXIDE

CAS: 13463-67-7

RTECS: XR2275000

Fraction By Weight: 0-18%

OSHA PEL10(5) MG/M3 DUST

ACGIH TLV: 10 MG/M3 DUST

ETHYLENE GLYCOL

CAS: 107-21-1

RTECS: KW2975000

OSHA PELC 50 PPM

ACGIH TLV: C 50 PPM

EPA Report Quantity: 1 LB

DOT Report Quantity: 1 LB

VOC

RTECS: 9999999VO

Fraction By Weight: 4.03%

Fire Fighting

Flash Point Method:PMCC

Flash Point:1029F,554C

Lower Limits:0.9

Upper Limits:6.0

Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL, FOAM

Fire Fighting Procedures:FULL PROTECTIVE EQUIP INCLUDING SCBA SHOULD BE

USED. WTR SPRAY MAY BE INEFFECTIVE.IF WTR USED, FOG NOZZLES

PREFERRED. WTR MAY BE USED TO COOL CLOSED CONTAINERS*

Unusual Fire/Explosion Hazard:*TO PREVENT PRESSURE BUILD-UP/POSSIBLE

AUTOIGN OR EXPLOS WHEN EXPOSED TO EXTREME HEAT. CLSD CNTNR MAY

EXPLODE DUE TO BUILD-UP PRESS WHEN EXPOSED TO EXTREME HEAT.

Exposure Controls

Supplemental Safety and Health

Chemical Properties

Boiling Pt:B.P. Text:300 TO 448F

Vapor Density:>AIR

Spec Gravity:0.92-1.54

Evaporation Rate & Reference:Percent Volatiles by Volume:32-65

Stability

Stability Indicator/Materials to Avoid:YES

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.