

OIL STAIN, A48V111, CLEAR BASE

MSDS Number

BXHQP

National Stock Number

8010-01-397-3839

Product Name

OIL STAIN, A48V111, CLEAR BASE

Manufacturer

THE SHERWIN WILLIAMS CO

Product Identification

Product ID: OIL STAIN, A48V111, CLEAR BASE

MSDS Date: 04/01/1991

FSC: 8010

NIIN: 01-397-3839

MSDS Number: BXHQP

Responsible Party

THE SHERWIN-WILLIAMS CO

101 PROSPECT AVE N W

CLEVELAND , OH 44115

US

Emergency Phone: 216-566-2917

Info Phone: 216-566-2902

Cage: DO693

Contractor

THE SHERWIN-WILLIAMS CO

CLEVELAND, OH 44115

US

216-566-2902

Cage: DO693

Ingredients

MINERAL SPIRITS (VAPORS PRESSURE 2.0 MM HG)

CAS: 64742-47-8

Fraction By Weight: 73-78%

OSHA PEL100 PPM

ACGIH TLV: 100 PPM

MINERAL SPIRITS, 140-FLASH (VAPOR PRESSURE 0.5 MM HG)

CAS: 64475-85-0

RTECS: PY8240000

OSHA PEL100 PPM

ACGIH TLV: 100 PPM

TOLUENE (VAPOR PRESSURE 22.0 MM HG)

CAS: 108-88-3

RTECS: XS5250000

Fraction By Weight: 3%

OSHA PEL100 PPM

ACGIH TLV: 100 PPM

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

VOC 5.51 LB/GL

Hazards

Reports of Carcinogenicity:NTP:UNKNOWN IARC:UNKNOWN OSHA:NO
Health Hazards Acute and Chronic:IRRIT OF EYES, SKIN & RESPIRATORY
SYSTEM. MAY CAUSE NERVOUS SYSTEM DEPRESSION. EXTREME OVEREXPOSURE
MAY RESULT IN UNCONSCIOUSNESS, POSSIBLY DEATH. HEADACHE, DIZZY,
NAUSEA, LOSS OF COORDINATION ARE INDICATIONS OF EXCESSIVE
OVEREXPOSURE TO VAPORS OR SPRAY MISTS. REDNESS, ITCHING, BURNING
MAY INDICATE EXCESSIVE EXPOSURE.

Effects of Overexposure:PROLONGED OVEREXPOSURE TO SOLVENT INGRED. MAY
CAUSE ADVERSE EFFECTS TO THE LIVER, URINARY SYSTEMS. REPORTS HAVE
ASSOCIATED REPEATED AND PROLONGED OVER EXPOSURE TO SOLVENTS WITH
PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE.

First Aid

First Aid:INHAL: REMOVE FROM EXPOSURE. RESTORE BREATHING, KEEP WARM &
QUIET. SKIN: WASH AFFECTED AREA THOROUGHLY WITH SOAP & WTR. REMOVE
CONTAMINATED CLOTHING & WASH BEFORE RE-USE. EYE: FLUSH W/LARGE AMTS
OF WATER FOR 15 MIN. GET MEDICAL ATTENTION. SWALLOWED:NEVER GIVE
ANYTHING BY MOUTH TO UNCONSCIOUS PERSON,DO NOT INDUCE VOMITING;
GIVE SEVERAL GLASSES OF WATER. GET MEDICAL ATTENTION.

Fire Fighting

Flash Point Method:PMCC

Flash Point:95.0F,35.0C

Lower Limits:1.0

Upper Limits:6.7

Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL, FOAM

Fire Fighting Procedures:FULL PROTECTIVE EQUIP, W/SCBA, WATER MAY BE
INEFFECTIVE. IF USED, FOG NOZZLES PREFERABLE. WATER TO COOL CLOSED
CNTNR/PREVENT PRESSURE,AUTOIGNITION, OR EXPLOSION.

Unusual Fire/Explosion Hazard:KEEP CNTNR CLSD. KEEP FRM. HEAT, ELECTR
EQUIP, SPARK, FLAME. CLSD CNTNR MAY EXPLODE W/HEAT. APPLICATION
TO HOT SURFACE REQ. SPECIAL PRECAUTION. DURING EMERGENCY*

Accidental Release

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. VENTILATE AND
REMOVE WITH INERT ABSORBENT.

Handling

Handling and Storage Precautions:CONTENTS ARE COMBUSTIBLE. KEEP FROM
HEAT/FLAME. CONSULT NFPA CODE. USE APPROVED BONDING, GROUNDING
PROCEDURES. KEEP CLOSED WHEN NOT IN USE.**

Other Precautions:**TRANSFER ONLY TO APPROVED CONTAINERS WITH COMPLETE
& APPROPRIATE LABELS. DO NOT TAKE INTERNALLY. KEEP OUT OF REACH OF
CHILDREN. INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING
INHALING THE CONTENTS MAY BE HARMFUL OR FATAL.

Exposure Controls

Respiratory Protection:IF EXPOSURE CANNOT BE CONTROLLED VENTILATION, WEAR NIOSH/MSHA APPROVED ORGANIC VAPOR/PARTICULATE
RESPIRATOR. WHEN SANDING/ABRADING DRIED FILM, WEAR NIOSH/MSHA
APPROVED DUST/MIST RESP GENERATED FROM PRODUCT, PAINT, OR

ABRASIVE.

Ventilation:LOCAL EXHAUST PREFERRED. GEN EXHAUST ACCEPTIBLE IF EXPOSURE

MAINTAINED Protective Gloves:USE GLOVES RECOMMENDED BY GLOVE SUPPLIER

Eye Protection:SAFETY GLASSES/UNPERFORATED SIDESHIELDS

Work Hygienic Practices:WASH HANDS AFTER USING

Supplemental Safety and Health

USE ONLY WITH ADEQUATE VENTILATION. AVOID BREATHING VAPOR AND SPRAY

MIST. AVOID CONTACT WITH EYES & SKINS.

Chemical Properties

Boiling Pt:B.P. Text:132 TO 388F

Vapor Density:>AIR

Spec Gravity:0.81-1.10

Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles by Volume:75-90%

Stability

Stability Indicator/Materials to Avoid:YES

Hazardous Decomposition Products:BY FIRE: CARBON DIOXIDE, CARBON MONOXIDE

Conditions to Avoid Polymerization:*OVEREXPOSURE TO DECOMPOSITON

PRODUCTS MAY CAUSE HEALTH HAZARD. SYMPTOMS MAY NOT BE IMMEDIATELY APPARENT.

Disposal

Waste Disposal Methods:WASTE MAY BE HAZARDOUS AS DEFINED BY RCRA 40 CFR

261. TEST FOR IGNITABILITY/DETERMINE EPA HAZ WASTE NUMBER.

INCINERATE IN APPROVED FACILITY. DO NOT INCINERATE CLOSED

CONTAINER. DISPOSE OF IN ACCORDANC E W/FED, STATE, LOCAL REGS

REGARDING POLLUTION.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.