

OIL STAIN, A48N103, DARK WALNUT

MSDS Number

BXHQT

National Stock Number

8010-01-397-3843

Product Name

OIL STAIN, A48N103, DARK WALNUT

Manufacturer

THE SHERWIN WILLIAMS CO

Product Identification

Product ID: OIL STAIN, A48N103, DARK WALNUT

MSDS Date: 04/01/1991

FSC: 8010

NIIN: 01-397-3843

MSDS Number: BXHQT

Responsible Party

THE SHERWIN-WILLIAMS CO

101 PROSPECT AVE N W

CLEVELAND , OH 44115

US

Emergency Phone: 216-566-2917

Info Phone: 216-566-2902

Cage: DO693

Contractor

THE SHERWIN-WILLIAMS CO

CLEVELAND, OH 44115

US

216-566-2902

Cage: DO693

Ingredients

ETHYLENE GLYCOL

CAS: 107-21-1

RTECS: KW2975000

OSHA PELC 50 PPM

ACGIH TLV: C 50 PPM

EPA Report Quantity: 1 LB

DOT Report Quantity: 1 LB

MINERAL SPIRITS (VAPOR PRESSURE 2.0 MM HG)

CAS: 64742-47-8

Fraction By Weight: 73-78%

OSHA PEL100 PPM

ACGIH TLV: 100 PPM

MINERAL SPIRITS, 140-FLASH (VAPOR PRESSURE 0.5 MM HG)

CAS: 64475-85-0

RTECS: PY8240000

OSHA PEL100 PPM

ACGIH TLV: 100 PPM

TOLUENE (VAPOR PRESSURE 22.0 MM HG)

CAS: 108-88-3

RTECS: XS5250000

Fraction By Weight: 3%

OSHA PEL100 PPM;150 PPM STEL

ACGIH TLV: 100 PPM;150 PPM STEL

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

VOC (5.42 - 5.75 LB/GAL)

RTECS: 9999999VO

Hazards

Reports of Carcinogenicity:NTP:UNKNOWN IARC:UNKNOWN OSHA:NO
Health Hazards Acute and Chronic:IRRIT OF EYES, SKIN & RESPIRATORY
SYSTEM. MAY CAUSE NERVOUS SYSTEM DEPRESSION. EXTREME OVEREXPOSURE
MAY RESULT IN UNCONSCIOUSNESS, POSSIBLY DEATH. ***
DURING EMERGENCY CONDITIONS OVE REXPOSURE TO DECOMP PROD MAY CAUSE
A HEALTH HAZ. SYMPTOMS MAY NOT BE IMMEDIATELY APPARENT. OBTAIN
MEDICAL ATTENTION.
Effects of Overexposure:HEADACHE, DIZZINESS, NAUSEA, AND LOSS OF
COORDINATION ARE INDICATIONS OF EXCESSIVE EXPOSURE TO VAPORS OR
SPRAY MISTS. REDNESS, ITCHING, BURNING SENSATION MAY INDICATE EYE
OR EXCESSIVE SKIN EXPOSURE.
Medical Cond Aggravated by Exposure:NONE GENERALLY RECOGNIZED.

First Aid

First Aid:INHAL: REMOVE FROM EXPOSURE. RESTORE BREATHING, KEEP WARM &
QUIET. SKIN: WASH AFFECTED AREA THOROUGHLY WITH SOAP & WTR. REMOVE
CONTAMINATED CLOTHING & WASH BEFORE RE-USE. EYE: FLUSH W/LARGE AMTS
OF WA TER FOR 15 MIN. GET MEDICAL ATTENTION. SWALLOWED:NEVER GIVE
ANYTHING BY MOUTH TO UNCONSCIOUS PERSON,DO NOT INDUCE VOMITING;
GIVE SEVERAL GLASSES OF WATER. GET MEDICAL ATTENTION.

Fire Fighting

Flash Point Method:PMCC
Flash Point:95.0F,35.0C
Lower Limits:1.0
Upper Limits:6.7
Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL, FOAM
Fire Fighting Procedures:FULL PROTECTIVE EQUIP, W/SCBA, WATER SPRAY MAY
BE INEFFECTIVE. IF USED, FOG NOZZLES PREFERABLE. WTR TO COOL CLOSED
CNTNR TO PREVENT PRESSURE BLDUP,AUTOIGNITION.
Unusual Fire/Explosion Hazard:KEEP CNTNR CLSD. KEEP FRM HEAT, ELECTR
EQUIP,SPARKS,FLAME. CLSD CNTNR MAY EXPLODE W/EXTREME HEAT.
APPLICATION TO HOT SURFACE REQ'R. SPCL PRECAUTION.DURING EMER

Accidental Release

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. VENTILATE AND

REMOVE WITH INERT ABSORBENT.

Handling

Handling and Storage Precautions: CONTENTS ARE FLAMMABLE. KEEP FROM HEAT/FLAME. CONSULT NFPA CODE. USE APPROVED BONDING, GROUNDING PROCEDURES. KEEP CLOSED WHEN NOT IN USE.**

Other Precautions: **TRANSFER ONLY TO APPROVED CONTAINERS WITH COMPLETE & APPROPRIATE LABELS. DO NOT TAKE INTERNALLY. KEEP OUT OF REACH OF CHILDREN. INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING INHALING THE CONTENTS MAY BE HARMFUL OR FATAL.

Exposure Controls

Respiratory Protection: IF EXPOSURE CANNOT BE CONTROLLED VENTILATION, WEAR NIOSH/MSHA APPROVED ORGANIC VAPOR/PARTICULATE RESPIRATOR. WHEN SANDING/ABRADING DRIED FILM, WEAR NIOSH/MSHA APPROVED DUST/MIST RESPIRATOR.

Ventilation: LOCAL EXHAUST PREFERRED. GEN EXHAUST ACCEPTIBLE IF EXPOSURE MAINTAINED Protective Gloves: USE GLOVES RECOMMENDED BY GLOVE SUPPLIER

Eye Protection: SAFETY GLASSES/UNPERFORATED SIDESHIELDS

Work Hygienic Practices: WASH HANDS AFTER USING

Supplemental Safety and Health

USE ONLY WITH ADEQUATE VENTILATION. AVOID BREATHING VAPOR AND SPRAY MIST. AVOID CONTACT WITH EYES & SKINS.

Chemical Properties

Boiling Pt: B.P. Text: 132 TO 388F

Vapor Density: >AIR

Spec Gravity: 0.81-1.10

Evaporation Rate & Reference: SLOWER THAN ETHER

Percent Volatiles by Volume: 75-90%

Stability

Stability Indicator/Materials to Avoid: YES

Hazardous Decomposition Products: BY FIRE: CARBON DIOXIDE, CARBON MONOXIDE

Disposal

Waste Disposal Methods: WASTE MAY BE HAZ AS DEFINED UNDER RCRA 40 CFR 261. TEST FOR IGNITABILITY/DETERMINE EPA HAZARDOUS WASTE #. INCINERATE IN APPROVED FACILITY, DO NOT INCINERATE CLOSE CONTAINER. DISPOSE IN ACCORDANCE W/FE D, STATE, LOCAL REGS REGARDING POLLUTION.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.