

LIQUID PLASTIC-CLEAR GLOSS, 90

MSDS Number

BXHSV

National Stock Number

8010-00N000575

Product Name

LIQUID PLASTIC-CLEAR GLOSS, 90

Manufacturer

FLECTO CO

Product Identification

Product ID:LIQUID PLASTIC-CLEAR GLOSS, 90 MSDS Date:06/10/1992 FSC:8010 NIIN:00N000575 MSDS Number: BXHSV

Responsible Party

FLECTO CO

1000 45TH ST

OAKLAND, CA 94608

US

Emergency Phone: 800-255-3924

Info Phone: 800-635-3286

Preparer: EDWARD M. QUESADA

Cage: GO895

Contractor

FLECTO CO INC

OAKLAND, CA 94608-3314

US

800-635-3286 Cage: 58381

Ingredients

CAS: 64742-47-8

KEROSENE (PETROLEUM), HYDROTREATED; (HYDROTREATED

RTECS: OA5504000 Fraction By Weight: 50%

OSHA PELN/K ACGIH TLV: N/K

3.93 LB/GAL; 471 G/L (COATING &

RTECS: 9999999VO OSHA PELN/K

ACGIH TLV: N/K

Hazards



LD50 LC50 Mixture: NONE SPECIFIED BY MANUFACTURER. Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic: INHALATION: RESPIRATORY TRACT IRRITANT AND CENTRAL NERVOUS SYSTEM DEPRESSANT. BURNING SENSATION IN NOSE AND THROAT, COUGH, FEELING OF DIFFICULTY BREATHING. ALSO, HEADACHE, DIZZINESS, STAGGERING GAIT, CONFUSION, UNCONSCIOUSNESS OR COMA. SKIN AND EYE CONTACT/SKIN ABSORPTION: PRIMARY IRRITATION. (EFTS OF OVEREXP)

Explanation of Carcinogenicity: NOT RELEVANT

Effects of Overexposure: HLTH HAZ: INGESTION: MAY CAUSE GASTROINTESTINAL

IRRITATION AND NAUSEA. CHRONIC: UNKNOWN AT THIS TIME.

Medical Cond Aggravated by Exposure: ANESTHESIA, RESPIRATORY TRACT

IRRITATION, DERMATITIS, NAUSEA, VOMITING.

First Aid

First Aid: EYES: FLUSH IMMEDIATELY WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES, CONSULT MD, SKIN: WASH AFFECTED AREAS WITH SOAP AND WATER, CONSULT MD IF IRRITATION PERSISTS. INHALATION: REMOVE TO FRESH A IR. INGESTION: DO NOT INDUCE VOMITING. CONSULT MD IMMEDIATELY.

Fire Fighting

Flash Point Method:SCC Flash Point: 105F,41C Lower Limits: 1.0% Upper Limits: 6.0%

Extinguishing Media: FOAM, CARBON DIOXIDE, DRY CHEMICAL.

Fire Fighting Procedures: USE NIOSH/MSHA APPROVED SCBA & FULL PROTECTIVE

EQUIPMENT . FIGHT AS VOLATILE LIQ FIRE. USE WATER TO KEEP FIRE

EXPOSED CONTAINERS COOL TO REDUCE PRESSURE.

Unusual Fire/Explosion Hazard: KEEP AWAY FROM HEAT, SPARKS AND OPEN

FLAME.

Accidental Release

Spill Release Procedures: REMOVE ALL SOURCES OF IGNITION. AVOID BREATHING VAPORS. VENTILATE AND REMOVE WITH INERT ABSORBENT. Neutralizing Agent: NONE SPECIFIED BY MANUFACTURER.

Handling

Handling and Storage Precautions: DO NOT STORE NEAR SOURCES OF EXTREME TEMPERATURE.

Other Precautions: DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN.

Exposure Controls

Respiratory Protection: NIOSH/MSHA APPROVED MASK OR RESPIRATOR FOR ORGANIC VAPORS AS NECESSARY.

Ventilation: ADEQUATE VOLUME AND PATTERN TO AVOID CONCENTRATION IN EXCESS OF TLV AND LEL.

Protective Gloves: NEOPRENE OR RUBBER.

Eve Protection: ANSI APPRVD CHEM WORKERS GOGGLES .

Other Protective Equipment: ANSI APPRVD EMERGENCY EYE BATH & DELUGE SHOWER . USE IMPERMEABLE APRONS & PROTECTIVE CLOTHING WHENEVER POSSIBLE.

Work Hygienic Practices: DO NOT STORE IN A HIGH TEMPERATURE AREA OR NEAR FIRE OR OPEN FLAMES. DO NOT TAKE INTERNALLY.

Supplemental Safety and Health NONE SPECIFIED BY MANUFACTURER.

Chemical Properties

Boiling Pt:B.P. Text:315F,157C Vapor Pres: SEE INGS Vapor Density: HVR/AIR Spec Gravity: 0.9 (H*20=1)

Evaporation Rate & Reference: SLOWER THAN ETHER

Solubility in Water: NEGLIGIBLE



Appearance and Odor: CLEAR AMBER APPEARANCE WITH A MILD ALIPHATIC ODOR.

Stability

Stability Indicator/Materials to Avoid:YES
MAY REACT WITH STRONG OXIDIZING AGENTS.
Stability Condition to Avoid:EXCESSIVE HEAT, POOR VENTILATION,
CORROSIVE ATMOSPHERES, EXCESSIVE AGING, SPARKS OR OPEN FLAME.
Hazardous Decomposition Products:NONE.

Disposal

Waste Disposal Methods: NORMAL WASTE DISPOSAL METHODS. DO NOT INCINERATE IN CLOSED CONTAINERS. NOTE: DISPOSE OF ALL WASTE IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.