

CARPET-TEX TRAFFIC-TEX

MSDS Number

BXHSZ

National Stock Number

7930-00N003746

Product Name

CARPET-TEX TRAFFIC-TEX

Manufacturer

AIRWICK INDUSTRIES INC

Product Identification

Product ID: CARPET-TEX TRAFFIC-TEX

MSDS Date: 09/01/1985

FSC: 7930

NIIN: 00N003746

MSDS Number: BXHSZ

Responsible Party

AIRWICK INDUSTRIES INC

1655 VALLEY RD

WAYNE , NJ 07474-0941

US

Emergency Phone: 201-933-8200

Info Phone: 201-633-2778

Cage: 7L847

Contractor

AIRWICK INDUSTRIES INC

941

WAYNE, NJ 07474-0941

US

201-633-2778

Cage: 7L847

Ingredients

NAPHTHA, HEAVY ALKYLATE; (PETROLEUM DISTILLATE)

CAS: 64741-65-7

Fraction By Weight: 20%

OSHA PEL300 PPM

ACGIH TLV: 300 PPM

DIPROPYLENE GLYCOL, MONOMETHYL ETHER; (DIPROPYLENE GLYCOL

CAS: 34590-94-8

RTECS: JM1575000

Fraction By Weight: 15%

OSHA PELS, 100 PPM

ACGIH TLV: S,100 PPM/150 STEL

Hazards

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE:IF INGESTED, MAY CAUSE
GASTROINTESTINAL IRRITATION WITH NAUSEA, VOMITING AND DIARRHEA.
ASPIRATION IS A CONCERN AND CAN LEAD TO CHEMICAL PNEUMONITIS AND
PULMONARY EDEMA. PROLONGED INHALATION MAY BE IRRITATING TO MUCOUS
MEMBRANES. CAUSES IRRITATION TO SKIN AND EYES. MAY CAUSE CNS
DEPRESSION, (EFFECTS OF OVEREXP)
Explanation of Carcinogenicity:NOT RELEVANT.
Effects of Overexposure:HLTH HAZ:HEADACHE, DIZZINESS AND LOSS OF
CONSCIOUSNESS.
Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

First Aid

First Aid:INGEST:GIVE WATER OR THIN SLURRY OF UP TO 40 GMS OF ACTIVATED
CHARCOAL. DO NOT INDUCE VOMITING. INHAL:SUPPORT BREATHING AS
NECESSARY. SKIN:WASH WITH SOAP AND WATER. REMOVE CONTAMINATED
CLOTHING. EYES: FLUSH WITH WATER FOR AT LEAST 15 MINUTES. CALL PHYS
IMMEDIATELY FOR ALL OF THE ABOVE.

Fire Fighting

Flash Point Method:SCC
Flash Point:>123F,>51C
Extinguishing Media:USE FOAM, CO*2, STEAM, DRY CHEMICALS.
Fire Fighting Procedures:NIOSH/MSHA APPRVD SCBA & FULL PROT EQUIP .
COOL FIRE EXPOSED CONTAINERS WITH WATER.
Unusual Fire/Explosion Hazard:VAPORS MAY BE FLAMMABLE (PETROLEUM
DISTILLATE MAY BOIL OFF)

Accidental Release

Spill Release Procedures:ELIMINATE POTENTIAL SOURCES OF IGNITION. PICK
UP WITH ABSORBENT MATERIAL.
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

Handling

Handling and Storage Precautions:DO NOT EXPOSE TO FIRE OR FLAME. STORE
AT AMBIENT TEMPERATURE. KEEP CONTAINER CLOSED WHEN NOT IN USE. DO
NOT REUSE EMPTY CONTAINER.

Exposure Controls

Respiratory Protection:NIOSH/MSHA APPROVED RESPIRATOR APPROPRIATE FOR
EXPOSURE OF CONCERN .
Ventilation:LOCAL EXHAUST:YES. MECHANICAL (GENERAL):REQUIRED.
Protective Gloves:IMPERVIOUS GLOVES .
Eye Protection:ANSI APPRVD CHEM WORKERS GOGGLES .
Other Protective Equipment:ANSI APPRVD EMERGENCY EYE WASH & DELUGE
SHOWER .
Work Hygienic Practices:NONE SPECIFIED BY MANUFACTURER.
Supplemental Safety and Health
NONE SPECIFIED BY MANUFACTURER.

Chemical Properties

Boiling Pt:B.P. Text:212F,100C
Melt/Freeze Pt:M.P/F.P Text:32.0F,0.0C
Spec Gravity:0.985 (H*20=1)
pH:9.2-10
Evaporation Rate & Reference:NOT KNOWN
Solubility in Water:DISPERSIBLE
Appearance and Odor:PALE, SLIGHTLY OPAQUE LIQUID. MILD SOLVENT ODOR.
Percent Volatiles by Volume:85%

Stability

Stability Indicator/Materials to Avoid:YES
OXIDIZING AGENTS.

Stability Condition to Avoid: HEAT OR OPEN FLAME.

Hazardous Decomposition Products: CO, CO*2 & UNIDENTIFIED ORGANICS MAY BE FORMED DURING COMBUSTION.

Disposal

Waste Disposal Methods: DISCARD ACCORDING TO LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.