

PRO-KRACK-KOTE

MSDS Number

BXHWT

National Stock Number

8030-00N058801

Product Name

PRO-KRACK-KOTE

Manufacturer

TUFF KOTE CO INC

Product Identification

Product ID:PRO-KRACK-KOTE

MSDS Date:09/29/1993

FSC:8030

NIIN:00N058801

MSDS Number: BXHWT

Responsible Party

TUFF-KOTE CO INC

210 SEMINARY AVE

WOODSTOCK , IL 60098

US

Emergency Phone: 815-338-2006

Info Phone: 815-338-2006

Cage: 15489

Contractor

TUFF-KOTE CO INC

WOODSTOCK, IL 60098-3428

US

Cage: 15489

Ingredients

INERT FILLERS AND PIGMENT; (INERTS & PIGMENTS)

Fraction By Weight:

OSHA PELN/K

ACGIH TLV: N/K

S-TRIAZINE, HEXAHYDRO-1,3,5-TRIETHYL-; (MILDEWCIDE -

CAS: 7779-27-3

RTECS: XY9275000

Fraction By Weight:

OSHA PELN/K

ACGIH TLV: N/K

SODIUM SALT OF POLYMERIC CARBOXILIC ACID; (EMULSIFIERS)

Fraction By Weight:

OSHA PELN/K
ACGIH TLV: N/K

SYNTHETIC RUBBER (EMULSIFIED)

Fraction By Weight:
OSHA PELN/K
ACGIH TLV: N/K

SODIUM HYDROXIDE (CERCLA)

CAS: 1310-73-2
RTECS: WB4900000
Fraction By Weight:
OSHA PEL2 MG/M3
ACGIH TLV: 2 MG/M3, C
EPA Report Quantity: 1000 LBS
DOT Report Quantity: 1000 LBS

Hazards

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.
Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE:MAY CAUSE EYE IRRITATION UPON CONTACT.
Explanation of Carcinogenicity:NOT RELEVANT
Effects of Overexposure:SEE HEALTH HAZARDS.
Medical Cond Aggravated by Exposure:POSSIBLE ALLERGIES.

First Aid

First Aid:INHAL:REMOVE TO FRESH AIR. SUPPORT BREATHING (GIVE O*2/ARTF RESP) . SKIN:FLUSH W/COPIOUS AMOUNTS OF WATER. CALL MD . EYES:FLUSH W/WATER FOR AT LEAST 15 MINUTES. CALL MD IMMEDIATELY. INGEST :CALL MD.

Fire Fighting

Extinguishing Media:DRIED FILM, SLOW TO IGNITE, NOT COMBUSTIBLE BEFORE DRYING. DRIED FILM - USE CO*2, WATER, ETC WHEN BEING APPLIED.
Fire Fighting Procedures:USE NIOSH/MSHA APPROVED SCBA & FULL PROTECTIVE EQUIPMENT .
Unusual Fire/Explosion Hazard:NONE.

Accidental Release

Spill Release Procedures:SCRAPE UP & PLACE IN A CONTAINER FOR DISPOSAL.
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

Handling

Handling and Storage Precautions:STORE AT ROOM TEMPERATURE - CLOSE CONTAINER AFTER EACH USE.

Exposure Controls

Respiratory Protection:NIOSH/MSHA APPROVED RESPIRATOR APPROPRIATE FOR EXPOSURE OF CONCERN . NONE NORMALLY REQUIRED.
Ventilation:GENERAL MECHANICAL VENTILATION.
Protective Gloves:IMPERVIOUS GLOVES .
Eye Protection:ANSI APPROVED CHEM WORKERS GOGGS .
Other Protective Equipment:EYE WASH FOUNTAIN & DELUGE SHOWER WHICH MEET ANSI DESIGN CRITERIA .
Work Hygienic Practices:USUAL PROCEDURES AS W/LATEX PAINT.

Supplemental Safety and Health
NONE SPECIFIED BY MANUFACTURER.

Chemical Properties

Boiling Pt: B.P. Text: 212F, 100C
Vapor Density: Spec Gravity: 1.35 (H₂O=1)
Solubility in Water: WATER EMULSION
Appearance and Odor: LIGHT COLORED, SOFT PASTE; FAINT ODOR.

Stability

Stability Indicator/Materials to Avoid: YES
Stability Condition to Avoid: NONE SPECIFIED BY MANUFACTURER.
Hazardous Decomposition Products: DRY FILM COMBUSTION.

Disposal

Waste Disposal Methods: DISPOSE TO SANITARY LANDFILL I/A/W LOCAL, STATE & FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.