

FULLER-GLO LATEX SATIN ENAMEL-BASE 3, 636-93

MSDS Number

BXHYM

National Stock Number

8010-00N058925

Product Name

FULLER-GLO LATEX SATIN ENAMEL-BASE 3, 636-93

Manufacturer

O'BRIEN CORP

Product Identification

Product ID:FULLER-GLO LATEX SATIN ENAMEL-BASE 3, 636-93

MSDS Date:03/28/1990

FSC:8010

NIIN:00N058925

MSDS Number: BXHYM

Responsible Party

O'BRIEN CORP

450 EAST GRAND AVE

SOUTH SAN FRANCISCO , CA 94080

US

Emergency Phone: 800-424-9300 (CHEMTREC)

Info Phone: 415-761-2300

Cage: FO983

Contractor

O'BRIEN CORP

SOUTH SAN FRANCISCO, CA 94080

US

(415) 761-2300

Cage: FO983

Ingredients

SILICON DIOXIDE

Fraction By Weight:

OSHA PELN/K

ACGIH TLV: N/K

0.08

CAS: 107-21-1

RTECS: KW2975000

Fraction By Weight:

OSHA PELN/K

ACGIH TLV: C 50 PPM,VAPOR

EPA Report Quantity: 1 LB

DOT Report Quantity: 1 LB

1095

CAS: 75-21-8

RTECS: KX2450000

Fraction By Weight:

OSHA PEL1 PPM; SEE 1910.1047

ACGIH TLV: 1 PPM, A2

EPA Report Quantity: 10 LBS

DOT Report Quantity: 10 LBS

TITANIUM OXIDE; (TITANIUM DIOXIDE)

CAS: 13463-67-7

RTECS: XR2275000

Fraction By Weight:

OSHA PEL15 MG/M3 TDUST

ACGIH TLV: 10 MG/M3 TDUST

CALCIUM CARBONATE; (MARBLE) (LIMESTONE)

CAS: 1317-65-3

RTECS: EV9580000

Fraction By Weight: 10-15%

OSHA PEL15 MG/M3 TDUST

ACGIH TLV: 10 MG/M3 TDUST

VOLATILE ORGANIC CONTENT 193.18 G/L

RTECS: 9999999VO

OSHA PELN/K

ACGIH TLV: N/K

ADVERSE REPRO EFTS & CHROMOSOME DMG MAY ALSO OCCUR

RTECS: 9999999ZZ

SHOW THAT INHAL EXPOS TO HIGH LEVELS (250 MG/KG) OF

RTECS: 9999999ZZ

THIS RESPONSE DID NOT OCCUR AT LOWER EXPOS LEVELS &

RTECS: 9999999ZZ

ETHYLENE

RTECS: 9999999ZZ

CHEMICAL REPRODUCTIVE HAZARDS. SEEK CONSULTATION

RTECS: 9999999ZZ

LATEST HAZARD LIST INFORMATION AND SAFE HANDLING

RTECS: 9999999ZZ

ANTICIPATED TO BE CARCINOGEN. OSHA

RTECS: 9999999ZZ

Hazards

LD50 LC50 Mixture:SEE INGREDIENTS.

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES

Health Hazards Acute and Chronic:ACUTE: EYES: PRIMARY IRRIT. INHAL: MAY CAUSE HDCH & NAUS. SKIN: POSS PRIMARY IRRIT. ING 2: CAN CAUSE IRRIT TO GI TRACT. ABDOM PAIN, DIARR, CNS DEPRESS, MALAISE, MENTAL SLUGGISHNESS, IN SEV CASES BRTHG & HEART FAILURE. ACUTE POISONING MAY DMG KIDNEYS, SEV CASES CAN RSLT IN DEATH DUE TO THIS EFT. CAN (EFTS OF OVEREXP)

Explanation of Carcinogenicity:ETHYLENE OXIDE: IARC MONOGRAPHS, SUPP, VOL 7, PG 205, 1987: GROUP 2A. NTP 7TH ANNUAL REPORT ON CARCINOGENS, (ING 13)

Effects of Overexposure:HLTH HAZ: CAUSE UPPER RESP IRRIT. HDCH, DIZZ, NAUS, VOMIT, BE IRRIT TO EYES & SKIN. ING 3 IN LIQ FORM CAN CAUSE BODILY HARM IF YOU INHALE VAP, IF IT COMES INTO CONT W/EYES/SKIN/IF INGESTED. INHAL EFTS INCL RESP IRRIT & LUNG INJURY, HDCH, NAUS, VOMIT, DIARR, SHORTNESS OF BREATH, & CYANOSIS. ING 4 CAN BE IRRIT (SUP DAT)

Medical Cond Aggravated by Exposure:REPORT SIGNS AND SYMPTOMS THAT MAY BE RELATED TO ETHYLENE OXIDE TO YOUR EMPLOYER.

First Aid

First Aid:INGEST: DRINK 1 OR 2 GLASSES OF WATER & INDUCE VOMIT BY PLACING FINGER AT BACK OF THROAT. NEVER GIVE ANYTHING BY MOUTH TO UNCON PERS. CONSULT MD/POISON CTL CENTER IMMED! INHAL: REMOVE TO FRESH AIR. RE STORE BRTHG. EYES: IMMED BEGIN FLUSHINGW/COOL WATER FOR AT LEAST 15 MIN, OCCASNL Y LIFTING LIDS TO ENSURE THORO RINSING. GET MD ATTN. SKIN: WASH THORO W/SOAP & WATER. REMOVE CONTAM CLTHG.

Fire Fighting

Flash Point:>200F,>93C

Extinguishing Media:USE MEDIA SUITABLE FOR SURROUNDING FIRE .

Fire Fighting Procedures:WEAR NIOSH/MSHA APPROVED SCBA & FULL PROTECTIVE EQUIPMENT .

Unusual Fire/Explosion Hazard:CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT.

Accidental Release

Spill Release Procedures:SOAK UP AND REMOVE WITH INERT ABSORBENT MATERIAL. PROVIDE ADEQUATE VENTILATION.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

Handling

Handling and Storage Precautions:KEEP FROM FREEZING. AVOID PROLONGED CONTACT WITH SKIN.

Other Precautions:DO NOT INGEST. KEEP OUT OF REACH OF CHILDREN.

Exposure Controls

Respiratory Protection:USE NIOSH/MSHA APPROVED MECHANICAL RESPIRATOR OR MASK TO AVOID BREATHING SPRAY MIST.

Ventilation:PROVIDE SUFF VENT IN VOL & PATTERN TO KEEP AIR CONTAM CONC BELOW APPLIC OSHA PERMISSIBLE EXPOS LEVEL/ACGIH TLV LIM.

Protective Gloves:IMPERVIOUS GLOVES .
Eye Protection:ANSI APPRVD CHEM WORK GOGGLES .
Other Protective Equipment:PROTECTIVE OVERALLS RECOMMENDED. REMOVE AND WASH CONTAMINATED CLOTHING. DISCARD CONTAMINATED SHOES.
Work Hygienic Practices:NONE SPECIFIED BY MANUFACTURER.
Supplemental Safety and Health
EFFECTS OF OVEREXPOSURE: TO UPPER RESPIRATORY TRACT & EYES. INGESTION 5 CAN BE IRRITANT TO EYES & SKIN. CHRONIC: LAB STUDIES SHOW THAT EXPOSURE OF PREGNANT ANIMALS TO ETHYLENE GLYCOL CAUSES BIRTH DEFECTS & FETAL DEATHS. ETHYLENE GLYCOL OXIDE HAS BEEN SHOWN TO CAUSE CANCER IN LAB ANIMALS & HAS BEEN ASSOCIATED WITH HIGHER INCIDENCES OF CANCERS IN HUMANS. (INGESTION 7)

Chemical Properties

Boiling Point: B.P. Text: 212°F, 100°C
Vapor Pressure: (SEE INGESTION 5)
Vapor Density: LTR/AIR
Specific Gravity: 1.19
Evaporation Rate & Reference: SLOWER THAN ETHER
Appearance and Odor: NONE SPECIFIED BY MANUFACTURER.
Percent Volatiles by Volume: 68.6

Stability

Stability Indicator/Materials to Avoid: YES
NOT APPLICABLE.
Stability Condition to Avoid: NOT APPLICABLE.
Hazardous Decomposition Products: MAY PRODUCE FUMES WHEN HEATED TO DECOMPOSITION. FUMES MAY CONTAIN CO, CO₂, AND NO₂.

Disposal

Waste Disposal Methods: DISPOSE IN ACCORDANCE WITH LOCAL, STATE, AND FEDERAL REGULATIONS. DO NOT INCINERATE IN CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.