

## **FIBER GLASS INSULATION, SUSPEND-R BOARD**

### **MSDS Number**

BXJDL

### **National Stock Number**

5970-00N059067

### **Product Name**

FIBER GLASS INSULATION, SUSPEND-R BOARD

### **Manufacturer**

SCHULLER INTERNATIONAL INC

### **Product Identification**

Product ID:FIBER GLASS INSULATION, SUSPEND-R BOARD

MSDS Date:01/01/1993

FSC:5970

NIIN:00N059067

MSDS Number: BXJDL

### **Responsible Party**

SCHULLER INTERNATIONAL INC

DENVER , CO 80127-5108

US

Emergency Phone: 800-424-9300 (CHEMTREC)

Info Phone: 303-978-4900

Cage: SCHUL

### **Contractor**

SCHULLER INTERNATIONAL, INC.

5108

DENVER, CO 80217-5108

US

303-978-2000

Cage: SCHUL

### **Ingredients**

FIBERGLASS; (FIBROUS GLASS)

CAS: 65997-17-3

Fraction By Weight: 85-98%

OSHA PEL5 MG/M3 RESP DUST

ACGIH TLV: 10 MG/M3 (

UREA EXTENDED PHENOL-FORMALDEHYDE RESIN CURED

CAS: 25104-55-6

Fraction By Weight: 2-15%

OSHA PELN/K

ACGIH TLV: N/K

KRAFT, FOIL/KRAFT, PSK, FSK, AND VARIOUS METAL BUILDING

Fraction By Weight:

OSHA PELN/K

ACGIH TLV: N/K

MAY CAUSE LENS OF EYE TO BE SCRATCHED.

RTECS: 9999999ZZ

DUSTS FROM

RTECS: 9999999ZZ

CHRONIC HLTH EFTS. TREATMENT SHOULD BE DIRECTED

RTECS: 9999999ZZ

RESP PROT. FOR EXPOS EXCEEDING 10 FIBERS PER

RTECS: 9999999ZZ

RESP W/HIGH EFFICIENCY PARTICULATE AIR (HEPA) FILTER

RTECS: 9999999ZZ

CARTRIDGES, & SURVIVAIR HALF-MASK W/#1090-00

RTECS: 9999999ZZ

KEEPING DUST AND FIBER LEVELS BELOW THE APPLICABLE

RTECS: 9999999ZZ

SHOULD BE PROVIDED AS NEC TO KEEP AIRBORNE DUST &

RTECS: 9999999ZZ

SYS SHOULD BE EVALUATED BY PROFESSIONAL INDUSTRIAL

RTECS: 9999999ZZ

BE CONDUCTED BY A PROFESSIONAL ENGINEER.

RTECS: 9999999ZZ

WASHED SEPARATELY FROM OTHER CLOTHES &

RTECS: 9999999ZZ

WASH CYCLE). THIS WILL REDUCE THE CHANCES OF FIBER

RTECS: 9999999ZZ

## **Hazards**

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:ACUTE: DUST MAY CAUSE  
IRRIT/SCRATCHINESS OF THROAT, &/ITCHING IN EYES & SKIN. CHRONIC:  
ANIMALS INJECTED W/FIBER GLASS IN LUNGS/CHEST CAVITY DEVELOPED  
TUMORS. STUDIES OF FIBER GLASS WORKERS HAVE SHOWN A SML EXCESS OF  
LUNG CANCER WHEN COMPARED TO LOC CTL GROUPS. HOWEVER, THERE IS NO  
EVIDENCE THAT THIS (EFTS OF OVEREXP)  
Explanation of Carcinogenicity:NOT RELEVANT.  
Effects of Overexposure:HLTH HAZ: EXCESS IS RELATED TO BRTHG FIBER  
GLASS. TARGET ORGANS: LUNGS, THROAT, SKIN & EYES. SYMP OF OVEREXP:  
INHAL: IRRIT OF UPPER RESP TRACT (SCRATCHY THROAT), COUGHING, &  
CONGESTION MAY OCCUR IN EX TREME EXPOS. SKIN: TEMPORARY IRRIT  
(ITCHING)/REDNESS MAY OCCUR. INGEST: MAY CAUSE TEMPORARY IRRIT TO  
GI TRACT (SUP DAT)  
Medical Cond Aggravated by Exposure:PREEXISTING CHRONIC EYE, SKIN OR  
RESPIRATORY DISEASES.

## First Aid

First Aid:INHAL: REMOVE TO FRESH AIR. DRINK WATER TO CLEAR THROAT &  
BLOW NOSE TO REMOVE FIBERS. SKIN: WASH GENTLY W/SOAP & WARM WATER  
TO REMOVE DUST & FIBERS. WASH HANDS BEFORE EATING/USING RESTROOM.  
INGEST: IR RIT OF GI TRACT MAY OCCUR & SHOULD BE TREATED  
SYMPTOMATICALLY. RINSE MOUTH W/WATER TO REMOVE FIBERS, & DRINK  
PLENTY OF WATER TO HELP REDUCE IRRIT. EYES: DO NOT RUB/SCRATCH  
EYES. DUST PARTICLES (ING 4)

## Fire Fighting

Extinguishing Media:USE MEDIA SUITABLE FOR SURROUNDING FIRE .  
Fire Fighting Procedures:WEAR NIOSH/MSHA APPROVED SCBA & FULL  
PROTECTIVE EQUIPMENT .  
Unusual Fire/Explosion Hazard:NONE.

## Accidental Release

Spill Release Procedures:PICK UP LARGE PIECES. VACUUM DUSTS. IF  
SWEEPING IS NECESSARY, USE A DUST SUPPRESSANT (SUCH AS WATER). DO  
NOT DRY SWEEP DUST ACCUMULATION. THESE PROCEDURES WILL HELP TO  
MINIMIZE POTENTIAL EXPOSURES.  
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

## Handling

Handling and Storage Precautions:USE PROTECTIVE EQUIPMENT WHEN HANDLING  
LOOSE OR UNPACKAGED MATERIAL. MATERIAL SHOULD BE KEPT DRY, AND  
PROTECTED FROM THE ELEMENTS.  
Other Precautions:WAREHOUSE STORAGE SHOULD BE IN ACCORDANCE WITH  
PACKAGE DIRECTIONS, IF ANY.

## Exposure Controls

Respiratory Protection:USE A NIOSH/MSHA APPRVD DUST/MIST RESP TO  
PROTECT AGAINST NUISANCE DUST & FIBERS (E.G. 3M 9900 & MOLDEX  
2200). OPERATIONS SUCH AS WELDING, BLOWING, TEAR OUT, & SPRAYING  
MAY GENERATE AIRBORNE FIBER CON CS REQUIRING HIGHER LEVEL OF (ING  
7)  
Ventilation:LOC EXHAUST VENT SHOULD BE PROVIDED AT AREAS OF CUTTING TO  
REMOVE AIRBORNE DUST & FIBERS. GEN DILUTION VENT (ING 11)  
Protective Gloves:LEATHER/COTTON GLOVES.  
Eye Protection:ANSI APPRVD CHEM WORKERS GOGGS .  
Other Protective Equipment:USE BARRIER CREAMS TO REDUCE SKIN CONT &  
IRRIT. WEAR LOOSE FITTING, LONG SLEEVED CLTHG TO PROT SKIN FROM  
IRRIT.  
Work Hygienic Practices:EXPOSED SKIN AREAS SHOULD BE WASHED W/SOAP &  
WARM WATER AFTER HNDLG/WORKING W/FIBER GLASS. CLTHG SHOULD BE (ING  
14)  
Supplemental Safety and Health  
APPEAR/ODOR: OR LOOSE FILL INSULATION, NO SIGNIFICANT ODOR. HAZ DECOMP  
PROD: DERIVED FROM PYROLYSIS/BURNING OF RESIN. DECOMP PROD MAY  
INCLUDE CO\*2, CO, CARBON PARTICLES, FORMALDEHYDES, & TRACES OF HYD

ROGEN CYANIDE. EFTS OF OVEREXP: (ESPECIALLY STOMACH). EYES:  
TEMPORARY IRRIT (ITCHING)/REDNESS MAY OCCUR.

## Chemical Properties

Melt/Freeze Pt:M.P/F.P Text:>1300F,>704

Spec Gravity:VARIABLE

Solubility in Water:NIL

Appearance and Odor:GOLD TO YELLOW FIBROUS GLASS BOARD/BLANKET W/W/OUT

KRAFT/OTHER FACINGS (SUP DAT

Percent Volatiles by Volume:0

## Stability

Stability Indicator/Materials to Avoid:YES

NONE SPECIFIED BY MANUFACTURER.

Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER.

Hazardous Decomposition Products:DECOMP PROD FROM MATL ARE THOSE THAT  
WOULD BE EXPECTED FROM ANY ORG (CARBON CONTAINING) MATL, & ARE  
MAINLY (SUP DAT)

## Disposal

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE W/LOCAL, STATE &  
FEDERAL REGULATIONS .

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.