

FIBER GLASS INSULATION, SOUND CONTROL BATTS

MSDS Number

BXJDP

National Stock Number

5970-00N059070

Product Name

FIBER GLASS INSULATION, SOUND CONTROL BATTS

Manufacturer

SCHULLER INTERNATIONAL INC

Product Identification

Product ID:FIBER GLASS INSULATION, SOUND CONTROL BATTS

MSDS Date:01/01/1993

FSC:5970

NIIN:00N059070

MSDS Number: BXJDP

Responsible Party

SCHULLER INTERNATIONAL INC

DENVER , CO 80127-5108

US

Emergency Phone: 800-424-9300 (CHEMTREC)

Info Phone: 303-978-4900

Cage: SCHUL

Contractor

SCHULLER INTERNATIONAL, INC.

5108

DENVER, CO 80217-5108

US

303-978-2000

Cage: SCHUL

Ingredients

FIBERGLASS; (FIBROUS GLASS)

CAS: 65997-17-3

Fraction By Weight: 85-98%

OSHA PEL5 MG/M3 RESP DUST

ACGIH TLV: 10 MG/M3 (

UREA EXTENDED PHENOL-FORMALDEHYDE RESIN CURED

CAS: 25104-55-6

Fraction By Weight: 2-15%

OSHA PELN/K

ACGIH TLV: N/K

KRAFT, FOIL/KRAFT, PSK, FSK, AND VARIOUS METAL BUILDING

Fraction By Weight:

OSHA PELN/K

ACGIH TLV: N/K

MAY CAUSE LENS OF EYE TO BE SCRATCHED.

RTECS: 9999999ZZ

DUSTS FROM

RTECS: 9999999ZZ

CHRONIC HLTH EFTS. TREATMENT SHOULD BE DIRECTED

RTECS: 9999999ZZ

RESP PROT. FOR EXPOS EXCEEDING 10 FIBERS PER

RTECS: 9999999ZZ

RESP W/HIGH EFFICIENCY PARTICULATE AIR (HEPA) FILTER

RTECS: 9999999ZZ

CARTRIDGES, & SURVIVAIR HALF-MASK W/#1090-00

RTECS: 9999999ZZ

KEEPING DUST AND FIBER LEVELS BELOW THE APPLICABLE

RTECS: 9999999ZZ

SHOULD BE PROVIDED AS NEC TO KEEP AIRBORNE DUST &

RTECS: 9999999ZZ

SYS SHOULD BE EVALUATED BY PROFESSIONAL INDUSTRIAL

RTECS: 9999999ZZ

BE CONDUCTED BY A PROFESSIONAL ENGINEER.

RTECS: 9999999ZZ

WASHED SEPARATELY FROM OTHER CLOTHES &

RTECS: 9999999ZZ

WASH CYCLE). THIS WILL REDUCE THE CHANCES OF FIBER

RTECS: 9999999ZZ

Hazards

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE: DUST MAY CAUSE
IRRIT/SCRATCHINESS OF THROAT, &/ITCHING IN EYES & SKIN. CHRONIC:
ANIMALS INJECTED W/FIBER GLASS IN LUNGS/CHEST CAVITY DEVELOPED
TUMORS. STUDIES OF FIBER GLASS WORKERS HAVE SHOWN A SML EXCESS OF
LUNG CANCER WHEN COMPARED TO LOC CTL GROUPS. HOWEVER, THERE IS NO
EVIDENCE THAT THIS (EFTS OF OVEREXP)
Explanation of Carcinogenicity:NOT RELEVANT.
Effects of Overexposure:HLTH HAZ: EXCESS IS RELATED TO BRTHG FIBER
GLASS. TARGET ORGANS: LUNGS, THROAT, SKIN & EYES. SYMP OF OVEREXP:
INHAL: IRRIT OF UPPER RESP TRACT (SCRATCHY THROAT), COUGHING, &
CONGESTION MAY OCCUR IN EX TREME EXPOS. SKIN: TEMPORARY IRRIT
(ITCHING)/REDNESS MAY OCCUR. INGEST: MAY CAUSE TEMPORARY IRRIT TO
GI TRACT (SUP DAT)
Medical Cond Aggravated by Exposure:PREEXISTING CHRONIC EYE, SKIN OR
RESPIRATORY DISEASES.

First Aid

First Aid:INHAL: REMOVE TO FRESH AIR. DRINK WATER TO CLEAR THROAT &
BLOW NOSE TO REMOVE FIBERS. SKIN: WASH GENTLY W/SOAP & WARM WATER
TO REMOVE DUST & FIBERS. WASH HANDS BEFORE EATING/USING RESTROOM.
INGEST: IR RIT OF GI TRACT MAY OCCUR & SHOULD BE TREATED
SYMPTOMATICALLY. RINSE MOUTH W/WATER TO REMOVE FIBERS, & DRINK
PLENTY OF WATER TO HELP REDUCE IRRIT. EYES: DO NOT RUB/SCRATCH
EYES. DUST PARTICLES (ING 4)

Fire Fighting

Extinguishing Media:USE MEDIA SUITABLE FOR SURROUNDING FIRE .
Fire Fighting Procedures:WEAR NIOSH/MSHA APPROVED SCBA & FULL
PROTECTIVE EQUIPMENT .
Unusual Fire/Explosion Hazard:NONE.

Accidental Release

Spill Release Procedures:PICK UP LARGE PIECES. VACUUM DUSTS. IF
SWEEPING IS NECESSARY, USE A DUST SUPPRESSANT (SUCH AS WATER). DO
NOT DRY SWEEP DUST ACCUMULATION. THESE PROCEDURES WILL HELP TO
MINIMIZE POTENTIAL EXPOSURES.
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

Handling

Handling and Storage Precautions:USE PROTECTIVE EQUIPMENT WHEN HANDLING
LOOSE OR UNPACKAGED MATERIAL. MATERIAL SHOULD BE KEPT DRY, AND
PROTECTED FROM THE ELEMENTS.
Other Precautions:WAREHOUSE STORAGE SHOULD BE IN ACCORDANCE WITH
PACKAGE DIRECTIONS, IF ANY.

Exposure Controls

Respiratory Protection:USE A NIOSH/MSHA APPRVD DUST/MIST RESP TO
PROTECT AGAINST NUISANCE DUST & FIBERS (E.G. 3M 9900 & MOLDEX
2200). OPERATIONS SUCH AS WELDING, BLOWING, TEAR OUT, & SPRAYING
MAY GENERATE AIRBORNE FIBER CON CS REQUIRING HIGHER LEVEL OF (ING
7)
Ventilation:LOC EXHAUST VENT SHOULD BE PROVIDED AT AREAS OF CUTTING TO
REMOVE AIRBORNE DUST & FIBERS. GEN DILUTION VENT (ING 11)
Protective Gloves:LEATHER/COTTON GLOVES.
Eye Protection:ANSI APPRVD CHEM WORKERS GOGGS .
Other Protective Equipment:USE BARRIER CREAMS TO REDUCE SKIN CONT &
IRRIT. WEAR LOOSE FITTING, LONG SLEEVED CLTHG TO PROT SKIN FROM
IRRIT.
Work Hygienic Practices:EXPOSED SKIN AREAS SHOULD BE WASHED W/SOAP &
WARM WATER AFTER HNDLG/WORKING W/FIBER GLASS. CLTHG SHOULD BE (ING
14)
Supplemental Safety and Health
APPEAR/ODOR: OR LOOSE FILL INSULATION, NO SIGNIFICANT ODOR. HAZ DECOMP
PROD: DERIVED FROM PYROLYSIS/BURNING OF RESIN. DECOMP PROD MAY
INCLUDE CO*2, CO, CARBON PARTICLES, FORMALDEHYDES, & TRACES OF HYD

ROGEN CYANIDE. EFTS OF OVEREXP: (ESPECIALLY STOMACH). EYES:
TEMPORARY IRRIT (ITCHING)/REDNESS MAY OCCUR.

Chemical Properties

Melt/Freeze Pt:M.P/F.P Text:>1300F,>704

Spec Gravity:VARIABLE

Solubility in Water:NIL

Appearance and Odor:GOLD TO YELLOW FIBROUS GLASS BOARD/BLANKET W/W/OUT

KRAFT/OTHER FACINGS (SUP DAT

Percent Volatiles by Volume:0

Stability

Stability Indicator/Materials to Avoid:YES

NONE SPECIFIED BY MANUFACTURER.

Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER.

Hazardous Decomposition Products:DECOMP PROD FROM MATL ARE THOSE THAT
WOULD BE EXPECTED FROM ANY ORG (CARBON CONTAINING) MATL, & ARE
MAINLY (SUP DAT)

Disposal

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE W/LOCAL, STATE &
FEDERAL REGULATIONS .

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.