FLEX GLOW RUSSET, 382

MSDS Number

BXJMP

National Stock Number

8010-00N059508

Product Name

FLEX GLOW RUSSET, 382

Manufacturer

PARKER PAINT

Product Identification

Product ID:FLEX GLOW RUSSET, 382 MSDS Date: 01/25/1989 FSC:8010 NIIN:00N059508 MSDS Number: BXJMP

Responsible Party

PARKER PAINT

TACOMA, WA 98411-0047

US

Emergency Phone: 206-473-1122

Info Phone: 206-473-1122 Preparer: J. BURNWORTH

Cage: 9H480 **Contractor**

PARKER PAINT

11047

TACOMA, WA 98409

US

253-473-1122

Cage: 9H480

Ingredients

708 @ 77F.

CAS: 1336-21-6 RTECS: BQ9625000

Fraction By Weight: 0.1%

OSHA PEL50 PPM

ACGIH TLV: 25 PPM;5 STEL EPA Report Quantity: 1000 LBS DOT Report Quantity: 1000 LBS

0.1 @ 68F.

CAS: 107-21-1

RTECS: KW2975000



Fraction By Weight: 0.6%

OSHA PELN/K

ACGIH TLV: 50 PPM, VAPOR, C EPA Report Quantity: 1 LB DOT Report Quantity: 1 LB

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE:OVEREXPOSURE MAY CAUSE HEADACHE,
NAUSEA, SKIN & EYE IRRITATION. INHAL:INHALATION OF HIGH
CONCENTRATIONS OF VAPORS MAY CAUSE HEADACHE, NAUSEA & IRRITATION OF
THE NOSE, THROAT & LUNGS. EYE:CONTACT MAY CAUSE IRRITATION OR
BURNING. SKIN CONTACT:REPEATED CONTACT MAY CAUSE IRRITATION &
DERMATITIS. SKIN(EFTS OF OVEREXP)
Explanation of Carcinogenicity:NOT RELEVANT
Effects of Overexposure:HLTH HAZ:ABSORPTION:NONE KNOWN AT THIS TIME.
INGEST:SWALLOWING CAN CAUSE GI IRRITATION, NAUSEA, VOMITING &

INGEST:SWALLOWING CAN CAUSE GI IRRITATION, NAUSEA, VOMITING & DIARRHEA. VOMITING CAN RESULT IN ASPIRATION OF MATERIAL INTO LUNGS WHICH CAN CAUSE CHEMICAL P NEUMONITIS. CHRONIC:UNPROTECTED OVEREXPOSURE TO MISTS FROM SPRAY APPLICATION MAY CAUSE LUNG DISEASE (SILICOSIS).

Medical Cond Aggravated by Exposure: NONE KNOWN AT THIS TIME.

LD50 LC50 Mixture: NONE SPECIFIED BY MANUFACTURER.

First Aid

First Aid:INHAL:REMOVE TO FRESH AIR. IF BREATHING HAS STOPPED, APPLY ARTIFICIAL RESPIRATION. CONSULT MD. EYE:WASH W/CLEAN WATER FOR AT LEAST 15 MINUTES. CONSULT MD. SKIN:WASH AFFECTED AREAS W/SOAP & WATER. REMO VE CONTAMINATED CLOTHING. CONSULT MD. INGEST:DRINK 1-2 GLASSES OF WATER TO DILUTE. CONSULT MD OR POISON CONTROL CENTER IMMEDIATELY.

Fire Fighting

Lower Limits:3.2% Upper Limits:15.2%

Extinguishing Media:FOAM, ALCOHOL FOAM, CO*2, DRY CHEMICAL.

Fire Fighting Procedures: USE NIOSH/MSHA APPROVED SCBA & FULL PROTECTIVE

EQUIPMENT.

Unusual Fire/Explosion Hazard: WATER MAY BE USED TO COOL CLOSED CONTAINERS TO PREVENT PRESSURE BUILD UP & EXPLOSION WHEN EXPOSED TO EXTREME HEAT.

Accidental Release

Spill Release Procedures: VENTILATE AREA. PREVENT SKIN & EYE CONTACT & BREATHING OF VAPOR. CONTAIN & REMOVE W/INERT ABSORBENT. Neutralizing Agent: NONE SPECIFIED BY MANUFACTURER.

Handling

Handling and Storage Precautions: DO NOT STORE ABOVE 200F. Other Precautions: DO NOT TAKE INTERNALLY. KEEP OUT OF REACH OF CHILDREN.

Exposure Controls

Respiratory Protection: NONE REQUIRED FOR BRUSH & ROLL APPLICATION. FOR SPRAY APPLICATIONS, WEAR A PROPERLY FITTED NIOSH/MSHA APPROVED (TC-23C) VAPOR/PARTICULATE RESPIRATOR UNTIL ALL VAPORS & SPRAY MISTS ARE EXHAUSTED.

Ventilation: PROVIDE SUFFICIENT VENT IN VOLUME & PATTERN TO KEEP AIR CONTAM CONC BELOW APPLIC OSHA PEL OR ACGIH TLV OCCUP EXPOS LIMS. Protective Gloves: IMPERVIOUS GLOVES.

Eye Protection: ANSI APPROVED CHEM WORKERS GOGGS .

Other Protective Equipment: EYE WASH FOUNTAIN & DELUGE SHOWER WHICH MEET ANSI DESIGN CRITERIA . COVERALLS & HOOD ARE REC DURING SPRAY



(SUPDAT)

Work Hygienic Practices: WASH HANDS BEFORE EATING OR USING THE RESTROOM. Supplemental Safety and Health OTHER PROT EQUIP: APPLICATION. PROTECTIVE CREAMS MAY BE USED FOR EASE OF CLEAN UP, NOT FOR PROTECTION.

Chemical Properties

Boiling Pt:B.P. Text:212F,100C

Vapor Pres:SEE INGS Vapor Density:LTR/AIR Spec Gravity:1.2 (H*2O=1)

Evaporation Rate & Reference: SLOWER THAN ETHER

Solubility in Water: DILUTABLE

Appearance and Odor: BROWN COLORED LIQUID W/AMMONIACAL ODOR.

Stability

Stability Indicator/Materials to Avoid:YES
NONE KNOWN AT THIS TIME.
Stability Condition to Avoid:DO NOT HEAT ABOVE 200F.
Hazardous Decomposition Products:NONE KNOWN AT THIS TIME.

Disposal

Waste Disposal Methods: DO NOT ALLOW MATERIAL TO CONTAMINATED GROUND WATER SYSTEMS. ABSORB LARGE SPILLS W/SAND, CLAY OR DIATOMACEOUS EARTH. DISPOSE I/A/W LOCAL, STATE & FEDERAL DISPOSAL REQUIREMENTS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.