

## **PRO STICK 200**

### **MSDS Number**

BXJSF

### **National Stock Number**

8040-00N059832

### **Product Name**

PRO STICK 200

### **Manufacturer**

ADHESIVE TECHNOLOGIES

### **Product Identification**

Product ID:PRO STICK 200

MSDS Date:07/22/1987

FSC:8040

NIIN:00N059832

MSDS Number: BXJSF

### **Responsible Party**

ADHESIVE TECHNOLOGIES

3 MERRILL INDUSTRIAL DR

HAMPTON , NH 03042

US

Emergency Phone: 603-926-1616

Info Phone: 603-926-1616

Cage: ADHES

### **Contractor**

ADHESIVE TECHNOLOGY CORP

KENT, WA 98031

US

206-872-2240

Cage: ADHES

### **Ingredients**

NON-HAZARDOUS INGREDIENTS

OSHA PELN/K

ACGIH TLV: N/K

### **Hazards**

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE AND CHRONIC: NONE. MOLTEN MATERIAL WILL ADHERE TO AND BURN SKIN UPON CONTACT.

Explanation of Carcinogenicity:NOT RELEVANT.

Effects of Overexposure:NONE.

Medical Cond Aggravated by Exposure:NONE.

### **First Aid**

First Aid:SKIN: MOLTEN MATERIAL WILL ADHERE TO AND BURN SKIN UPON CONTACT. IMMEDIATELY IMMERSE AFFECTED AREA IN ICE WATER. DO NOT PULL SOLIDIFIED MATERIAL FROM SKIN. SEEK MEDICAL AID. EYES: FLUSH WITH POTABLE WATER FOR AT LEAST 15 MINUTES. SEE MD INHALATION: REMOVE

TO FRESH AIR. SUPPORT BREATHING (GIVE OXYGEN OR ARTIFICIAL RESPIRATION) . INGESTION: CALL MD IMMEDIATELY .

## Fire Fighting

Flash Point:>450F,>232C

Extinguishing Media:CARBON DIOXIDE, FOAM, ETC.

Fire Fighting Procedures:WEAR NIOSH/MSHA APPROVED SCBA & FULL PROTECTIVE EQUIPMENT .

Unusual Fire/Explosion Hazard:NONE.

## Accidental Release

Spill Release Procedures:NORMAL HOUSEKEEPING AND CLEAN-UP. NO SPECIAL PROCEDURE.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

## Handling

Handling and Storage Precautions:STORE IN A COOL, DRY ATMOSPHERE.

Other Precautions:NONE.

## Exposure Controls

Respiratory Protection:NOT REQUIRED IN NORMAL CONDITIONS. SOME ODORS IN FUMES FROM MOLTEN SURFACE. USE NIOSH/MSHA APPROVED RESPIRATOR APPROPRIATE FOR EXPOSURE OF CONCERN .

Ventilation:LOCAL EXHAUST RECOMMENDED IN CONFINED AREAS. MECHANICAL (GENERAL) RECOMMENDED IN LARGE VOLUME USAGE.

Protective Gloves:IMPERVIOUS GLOVES .

Eye Protection:ANSI APPRVD CHEM WORKERS GOGGS .

Other Protective Equipment:WHERE BURNS FROM SPLASHING COULD OCCUR, COVER EXPOSED SKIN WITH LONG SLEEVE SHIRT, ETC.

Work Hygienic Practices:ALWAYS KEEP WORK AREA CLEAN AND ORGANIZED.

Supplemental Safety and Health

NONE SPECIFIED BY MANUFACTURER.

## Chemical Properties

Boiling Pt:B.P. Text:SOLID

Melt/Freeze Pt:M.P/F.P Text:185F,85C

Vapor Pres:NIL

Spec Gravity:0.98 (H\*20=1)

Solubility in Water:NIL

Appearance and Odor:OPAQUE WHITE WITH MILD ODOR; MELTS TO SEMI-LIQUID ABOVE 250F.

## Stability

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS.

Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER.

Hazardous Decomposition Products:THERMAL DECOMPOSITION OR COMBUSTION MAY PRODUCE CARBON MONOXIDE AND/OR CARBON DIOXIDE.

## Disposal

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE W/LOCAL, STATE & FEDERAL REGULATIONS .

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.