

Q-THANE EPOXY CATALYST 40T2R

MSDS Number

BXLFV

National Stock Number

8040-00F040218

Product Name

Q-THANE EPOXY CATALYST 40T2R

Manufacturer

VALSPAR CORP

Product Identification

Product ID: Q-THANE EPOXY CATALYST 40T2R

MSDS Date: 05/13/1986

FSC: 8040

NIIN: 00F040218

MSDS Number: BXLFV

Responsible Party

VALSPAR CORP

1101 THIRD ST SOUTH

MINNEAPOLIS , MN 55415-5000

US

Emergency Phone: 612-332-7371/800-228-5635

Info Phone: 612-332-7371/800-228-5635

Cage: 13374

Contractor

VALSPAR CORPORATION

MINNEAPOLIS, MN 55415

US

612-332-7371/888-345-5732

Cage: 23526

Ingredients

CYCLOHEXANONE

CAS: 180-94-1

RTECS: GW1050000

OSHA PEL200 MG/CUM

ACGIH TLV: 100 MG/CUM

ETHYL ACETATE

CAS: 141-78-6

RTECS: AH5425000

OSHA PEL1400 MG/CUM

ACGIH TLV: 1400 MG/CUM

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

2-BUTANONE (METHYL ETHYL KETONE) (MEK)

CAS: 78-93-3

RTECS: EL6475000

OSHA PEL200 PPM

ACGIH TLV: 590 MG/CUM

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

METHYLENE BIS(4-CYCLOHEXYLISOCYANATE)

CAS: 5124-30-1

RTECS: NQ9250000

Fraction By Weight: 1-3%

ACGIH TLV: 0.054 MG/CUM

Hazards

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:IRRITATION OF THE RESPIRATORY TRACT & MUCOUS MEMBRANES. EXPOSURE CAN LEAD TO ALLERGENIC SENSITIVITY. REPEATED/PROLONGED OVEREXPOSURE TO SOLVENTS CAN CAUSE PERMANENT BRAIN & NERVOUS SYSTEM DAMAGE.
Effects of Overexposure:IRRITATION, COUGHING, HEADACHE, SHORTNESS OF BREATH.
Medical Cond Aggravated by Exposure:ANY RESPIRATORY/SKIN CONDITION.

First Aid

First Aid:SKIN: WASH W/SOAP & WATER. EYES: WASH W/WATER FOR 15 MINS. INGESTION: INDUCE VOMITING. INHALATION: REMOVE TO FRESH AIR. GIVE OXYGEN IF NEEDED. OBTAIN MEDICAL ATTENTION IN ALL CASES.

Fire Fighting

Flash Point Method:OC
Flash Point:25F
Extinguishing Media:FOR CLASS B FIRES

Accidental Release

Spill Release Procedures:COVER W/ABSORBENT MATERIAL, SUCH AS SAWDUST, THEN COLLECT IN DISPOSAL CONTAINERS FOR PROPER DISPOSAL.

Handling

Handling and Storage Precautions:IAW/OSHA REGULATIONS.
Other Precautions:IAW/OSHA REGULATIONS. INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING & INHALING THE CONTENTS MAY BE HARMFUL/FATAL.

Exposure Controls

Respiratory Protection:IAW/OSHA REGULATIONS.
Ventilation:REQUIRED
Protective Gloves:IMPERVIOUS
Eye Protection:SPLASH GOGGLES
Supplemental Safety and Health

Chemical Properties

Vapor Density:>1
Spec Gravity:1.01
Solubility in Water:COMPLETE
Appearance and Odor:NORMAL FOR COATINGS PRODUCT

Percent Volatiles by Volume:40

Stability

Stability Indicator/Materials to Avoid:YES

WATER, AMINES & ALCOHOLS

Stability Condition to Avoid:HEAT, MOISTURE.

Conditions to Avoid Polymerization:HEAT, MOISTURE.

Disposal

Waste Disposal Methods:DISPOSE OF IAW/FEDERAL, STATE & LOCAL REGULATIONS. W/EPA RCRA REGULATIONS. WASTE SOLVENT COATING IS A HAZARDOUS WASTE, IGNITABLE WASTE D-001.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.