

P*L*U*S PIPE THREAD SEALANT, 51373

MSDS Number

BXXTL

National Stock Number

8030-00N061134

Product Name

P*L*U*S PIPE THREAD SEALANT, 51373

Manufacturer

FEL PRO INC CHEMICAL PRODUCTS LP

Product Identification

Product ID:P*L*U*S PIPE THREAD SEALANT, 51373

MSDS Date:07/07/1993

FSC:8030

NIIN:00N061134

MSDS Number: BXXTL

Responsible Party

FEL-PRO INC CHEMICAL PRODUCTS LP

7450 N MCCORMICK BLVD

SKOKIE , IL 60076-8205

US

Emergency Phone: 800-424-9300(CHEMTREC)

Info Phone: 303-289-5651

Preparer: CATHY GRIFFITH

Cage: JO068

Contractor

FEL-PRO INC DIV OF FELT PRODUCTS MFG CO

1103

SKOKIE, IL 60076-4046

US

847-674-7700 OR 312-761-4500

Cage: 73165

Ingredients

MICA - SILICATES (< 1% CRYSTALLINE SILICA); (SILICEOUS

CAS: 12001-26-2

RTECS: VV8760000

Fraction By Weight: 15%

OSHA PEL20 MPPCF

ACGIH TLV: 3 MG/M3 RDUST

CASTOR OIL

CAS: 68187-84-8

Fraction By Weight: >3%

OSHA PELN/K

ACGIH TLV: N/K

POLYETHYLENE; (POLYETHYLENE HOMOPOLYMERS)

CAS: 9002-88-4

RTECS: TQ3325000

Fraction By Weight: >3%

OSHA PELN/K

ACGIH TLV: N/K

DRYING OILS; (DRYING OIL POLYMER)

Fraction By Weight: >3%

OSHA PELN/K

ACGIH TLV: N/K

ETHYLENE, TETRAFLUORO-, POLYMER; (PTFE RESIN)

CAS: 116-14-3

RTECS: KX4025000

Fraction By Weight: >3%

OSHA PELN/K

ACGIH TLV: N/K

TITANIUM OXIDE; (TITANIUM DIOXIDE)

CAS: 13463-67-7

RTECS: XR2275000

Fraction By Weight: >3%

OSHA PEL15 MG/M3 TDUST

ACGIH TLV: 10 MG/M3 TDUST

Fire Fighting

Flash Point:500F,260C

Extinguishing Media:CO*2, DRY CHEMICAL, FOAM.

Fire Fighting Procedures:WEAR NIOSH/MSHA APPRVD SCBA & FULL PROT EQUIP
USE WATER TO COOL EXPOSED CNTNRS. WATER STREAM DIRECTED INTO FIRE
MAY CAUSE FROTHING W/SUBSEQUENT (SUP DAT)

Unusual Fire/Explosion Hazard:CLSD CNTNRS MAY RUPTURE/EXPLODE (DUE TO
PRESS BUILD-UP) WHEN EXPOSED TO EXTREME HEAT. IRRIT &/OR TOX
GASES/FUMES MAY BE GENERATED BY THERMAL DECOMP/COMBUSTION.

Exposure Controls

Supplemental Safety and Health

Chemical Properties

Vapor Density:HVR/AIR

Spec Gravity:0.96

Evaporation Rate & Reference:SLOWER THAN BUTYL ACETATE

Solubility in Water:NEGLIGIBLE

Appearance and Odor:OFF-WHITE PASTE WITH NO APPRECIABLE ODOR.

Stability

Stability Indicator/Materials to Avoid:YES

STRONG BASES OR OXIDANTS.

Stability Condition to Avoid:NO INFORMATION.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.