

TRIBOLUBE-3

MSDS Number

BYBYL

National Stock Number

9150-00-269-8412

Product Name

TRIBOLUBE-3

Manufacturer

AEROSPACE LUBRICANTS INC

Product Identification

Product ID:TRIBOLUBE-3

MSDS Date:09/13/1994

FSC:9150

NIIN:00-269-8412

MSDS Number: BYBYL

Responsible Party

AEROSPACE LUBRICANTS INC.

1505 DELASHMUT AVE

COLUMBUS , OH 43212-2641

US

Emergency Phone: 614-291-3045

Info Phone: 614-291-3045

Preparer: STEPHEN E. GATES

Cage: 66164

Contractor

AEROSPACE LUBRICANTS INC.

COLUMBUS, OH 43228

US

614-878-3600

Cage: 66164

Ingredients

NON-HAZARDOUS INGREDIENTS

Fraction By Weight: 100%

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE: NONE. CHRONIC: NONE.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:PROLONGED OR REPEATED CONTACT WITH THE SKIN MAY CAUSE SKIN IRRITATION.

Medical Cond Aggravated by Exposure:NO KNOWN MEDICAL CONDITION THAT MIGHT BE AGGRAVATED BY EXPOSURE.

First Aid

First Aid:INHALATION-REMOVE TO FRESH AIR, IF NECESSARY SEEK MEDICAL ATTENTION. EYES-FLUSH WITH WATER, GET MEDICAL ATTENTION. SKIN-WIPE OFF AND WASH WITH SOAP AND WATER. INGESTION-GIVE MILK OR WATER, DO NOT INDUCE VOMITING. INGESTION MAY CAUSE DIARRHEA, CONSULT

PHYSICIAN.

Fire Fighting

Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL, FOAM, WATER SPRAY, WATER FOG.

Fire Fighting Procedures:SELF-CONTAINED BREATHING APPARATUS & PROTECTIVE CLOTHING SHOULD BE WORN IN FIGHTING FIRES INVOLVING CHEMICALS. DECOMPOSITION ABOVE 290C MAY CAUSE TOXIC GASES.

Unusual Fire/Explosion Hazard:TOXIC FLUORINE GASES ARE BY PRODUCTS OF COMBUSTION.

Accidental Release

Spill Release Procedures:SCARPE UP WITH PROPER TOOLS, WIPE UP WITH ABSORBENT CLOTH OR PAPER TOWEL; APPLY NON-SKID ABSORBENT MATERIAL TO FLOOR. COLLECT WASTE MATERIALS FOR SALVAGE OR DISPOSAL.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

Handling

Handling and Storage Precautions:USE REASONABLE CARE. DO NOT STORE ABOVE 250F OR NEAR FLAMES.

Other Precautions:TOXIC VAPORS MAY EVOLVE ABOVE 550F; PROVIDE ADEQUATE VENTILATION IF USED ABOVE THIS TEMPERATURE.

Exposure Controls

Respiratory Protection:NOT REQUIRED UNLESS PRODUCT IS BEING USED AS A MIST.

Ventilation:MECHANICAL-RECOMMENDED.

Protective Gloves:PLASTIC DISPOSABLE.

Eye Protection:SAFETY GLASSES RECOMMENDED.

Other Protective Equipment:PLASTIC APRON, FABRIC LABORATORY COAT RECOMMENDED.

Work Hygienic Practices:DO NOT COMBIMATE SMOKING MATERIAL; WASH HANDS AND/OR CONTAMINATED AREA AFTER EXPOSURE.

Supplemental Safety and Health
NONE

Chemical Properties

HCC:V6

Boiling Pt:B.P. Text:>500F,>260C

Melt/Freeze Pt:M.P/F.P Text:>450F,>232C

Vapor Pres:1 MM

Spec Gravity:0.800

Solubility in Water:NEGLIGIBLE

Appearance and Odor:TAN GREASE, SLIGHT PETROLEUM ODOR.

Stability

Stability Indicator/Materials to Avoid:YES

OXIDIZING MATERIAL CAN CAUSE A REACTION.

Stability Condition to Avoid:STRONG OXIDIZERS, TEMPERATURES ABOVE 500F.

Hazardous Decomposition Products:FLUORINE PRODUCTS, SILICON DIOXIDE, CARBON DIOXIDE, TRACES OF INCOMPLETELY BURNED CARBON.

Disposal

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH CURRENT FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.