https://msdsreport.com/msds/BYGLH

RAPID SEAL

MSDS Number

BYGLH

National Stock Number

8030-00N062020

Product Name

RAPID SEAL

Manufacturer

ALCO PRODUCTS INC

Product Identification

Product ID:RAPID SEAL MSDS Date:08/31/1988 FSC:8030 NIIN:00N062020 MSDS Number: BYGLH

Responsible Party

ALCO PRODUCTS INC

13126 SATICOY ST

NORTH HOLLYWOOD , CA 91605

US

Emergency Phone: 800-424-9300(CHEMTREC)

Info Phone: 818-764-7700

Cage: 0AXK7

Contractor

ALCO PRODUCTS INC

NORTH HOLLYWOOD, CA 91605

US

818-764-7700

Cage: 0AXK7

Ingredients

SILICA, CRYSTALLINE - QUARTZ; (CRYSTALLINE QUARTZ) CAS: 14808-60-7 RTECS: VV7330000 Fraction By Weight: 2-6% OSHA PELSEE TABLE Z-3 ACGIH TLV: 0.1 MG/M3 RDUST

BENTONITE; (BENTONITE CLAY) CAS: 1302-78-9 RTECS: CT9450000 OSHA PEL5 MG/M3 (DUST) ACGIH TLV: 5 MG/M3 (DUST)

Hazards



LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER. Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:NO Health Hazards Acute and Chronic:MAY CAUSE DELAYED RESPIRATORY DISEASE IF DUST INHALED OVER A PROLONGED PERIOD OF TIME. EXCESSIVE INHALATION OF DUST MAY RESULT IN SHORTNESS OF BREATH & REDUCED PULMONARY FUNCTION. Explanation of Carcinogenicity:SILICA, CRYSTALLINE-QUARTZ:IARC MONOGRAPHS, SUPP, VOL 7, PG 341, 1987:GRP 2A. NTP 7TH ANNUAL REPORT ON CARCINS, (SUPDAT) Effects of Overexposure:SEE HEALTH HAZARDS. Medical Cond Aggravated by Exposure:INDIVIDUALS W/PULMONARY &/OR RESPIRATORY DISEASE INCLUDING BUT NOT LIMITED TO ASTHMA &

•

First Aid

First Aid:INGEST:CALL MD IMMEDIATELY . SKIN:FLUSH W/COPIOUS AMOUNTS OF WATER. CALL MD . EYES:FLUSH W/WATER FOR AT LEAST 15 MINUTES. INHAL:REMOVE TO FRESH AIR; GIVE OXYGEN OR ARTIFICIAL RESPIRATION I F NECESSARY; GET MEDICAL ATTENTION.

BRONCHITIS SHOULD BE PRECLUDED FROM EXPOSURE TO DUST.

Fire Fighting

Extinguishing Media:MEDIA SUITABLE FOR SURROUNDING FIRE . Fire Fighting Procedures:USE NIOSH/MSHA APPROVED SCBA & FULL PROTECTIVE EQUIPMENT . INORGANIC MINERAL/NON-FLAMMABLE.

Accidental Release

Spill Release Procedures:VACUUM IF POSSIBLE TO AVOID GENERATING AIRBORNE DUST. AVOID BREATHING DUST. WEAR A NIOSH/MSHA APPROVED RESPIRATOR. AVOID ADDING WATER, PRODUCT WILL BECOME SLIPPERY WHEN WET.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

Handling

Handling and Storage Precautions: AVOID BREATHING DUST. Other Precautions: SLIPPERY WHEN WET.

Exposure Controls

Respiratory Protection:USE NIOSH/MSHA APPROVED RESPIRATOR WHERE TLV LIMITS FOR CRYSTALLINE SILICA MAY BE EXCEEDED. OSHA STANDARD 1910.134 OR AWSI 200.2 - 1980 SPECIFICATION. Ventilation:LOCAL EXHAUST &/OR MECHANICAL (GENERAL) - AS APPROPRIATE. Protective Gloves:IMPERVIOUS GLOVES . Eye Protection:ANSI APPROVED CHEM WORKERS GOGGS . Other Protective Equipment:EYE WASH FOUNTAIN & DELUGE SHOWER WHICH MEET ANSI DESIGN CRITERIA . Work Hygienic Practices:USE GOOD HOUSEKEEPING PRACTICES. Supplemental Safety and Health EXPLAN OF CARCIN:1994:ANTICIPATED TO BE CARCINOGEN.

Chemical Properties

Spec Gravity:2.5 (H*2O=1) Solubility in Water:NEGLIGIBLE Appearance and Odor:PALE GREY TO BUFF POWDER OR GRANULES; ODORLESS.

Stability

Stability Indicator/Materials to Avoid:YES NONE KNOWN. Stability Condition to Avoid:NONE KNOWN. Hazardous Decomposition Products:NONE KNOWN.

Disposal

Waste Disposal Methods: FOLLOW FEDERAL, STATE & LOCAL REGULATIONS FOR SOLID WASTE.

Disclaimer (provided with this information by the compiling agencies):



https://msdsreport.com/msds/BYGLH

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.