

VC9982 CARLON ALL WEATHER QUICKSET CLEAR CEMENT QT

MSDS Number

BYHMW

National Stock Number

8040-00F001149

Product Name

VC9982 CARLON ALL WEATHER QUICKSET CLEAR CEMENT QT

Manufacturer

OATEY COMPANY

Product Identification

Product ID:VC9982 CARLON ALL WEATHER QUICKSET CLEAR CEMENT QT

MSDS Date:01/31/1991

FSC:8040

NIIN:00F001149

MSDS Number: BYHMW

Responsible Party

OATEY COMPANY

4700 W 160TH ST

CLEVELAND , OH 44135-2632

US

Emergency Phone: 303-623-5716 COLLECT

Info Phone: 216-267-7100

Preparer: GABRIELLA BITZ

Cage: EO573

Contractor

OATEY COMPANY

35906

CLEVELAND, OH 44135-2632

US

216-267-7100

Cage: EO573

Ingredients

CHLORINATED POLYVINYL CHLORIDE, PYROLYZATE, CPVC

CAS: 68648-82-8

RTECS: FO1930000

Fraction By Weight: 12-18%

TETRAHYDROFURAN

CAS: 109-99-9

RTECS: LU5950000

Fraction By Weight: 50-60%

OSHA PEL200 PPM

ACGIH TLV: 590 MG/CUM

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

ACETONE; DIMETHYL KETONE; 2-PROPANONE

CAS: 67-64-1

RTECS: AL3150000

Fraction By Weight: 10-20%

OSHA PEL2400 MG/CUM

ACGIH TLV: 750 PPM

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

2-BUTANONE (METHYL ETHYL KETONE) (MEK)

CAS: 78-93-3

RTECS: EL6475000

Fraction By Weight:

OSHA PEL200 PPM

ACGIH TLV: 590 MG/CUM

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

CYCLOHEXANONE, KETOHEXAMETHYLENE

CAS: 108-94-1

RTECS: GW1050000

Fraction By Weight: 10-16%

OSHA PEL50 PPM

ACGIH TLV: 100 MG/CUM

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

SILICON DIOXIDE, CELITE 322, AMORPHOUS SILICA GEL *95-4*

CAS: 112945-52-5

RTECS: VV7310000

Fraction By Weight: 1-2%

OSHA PEL80 MG/CUM

ACGIH TLV: 0.2 MG/CUM

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:INHALATION: IRRITATION OF MUCOUS
MEMBRANES, NOSE & THROAT. SKIN: CHRONIC CONTACT MAY LEAD TO

IRRITATION & DERMATITIS. MAY POSSIBLY BE ABSORBED. EYES:

IRRITATION. INGESTION: MAY BE ASPIRATED INTO LUNGS /CAUSE SYSTEMIC
EFFECTS.

Explanation of Carcinogenicity:NONE
Effects of Overexposure:IRRITATION, HEADACHE, DIZZINESS, NAUSEA,
NUMBNESS OF EXTREMITIES & NARCOSIS.

First Aid

First Aid:SKIN: WASH THOROUGHLY W/SOAP & WATER. EYES: REMOVE TO FRESH
AIR & IRRIGATE W/WATER FOR 15 MINS. INHALATION: REMOVE TO FRESH
AIR. GIVE CPR/OXYGEN IF NEEDED. KEEP WARM & QUIET. INGESTION: DRINK
WATER & CALL POISON CONTROL IMMEDIATELY. AVOID ALCOHOLIC
BEVERAGES. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.
OBTAIN MEDICAL ATTENTION IN ALL CASES.

Fire Fighting

Flash Point Method:PMCC
Flash Point:5-8F
Lower Limits:2
Upper Limits:12
Extinguishing Media:SMALL: USE DRY CHEMICAL, CO2, WATER/FOAM. LARGE:
EVACUATE AREA.

Accidental Release

Spill Release Procedures:VENTILATE AREA, STOP LEAK, SAFELY. TAKE UP
W/SAND, EARTH/OTHER NON-COMBUSTIBLE ABSORBING MATERIAL.

Handling

Handling and Storage Precautions:KEEP FROM HEAT, SPARKS & FLAMES. STORE
IN COOL, DRY PLACE. CONTAINERS, EVEN EMPTIES WILL RETAIN RESIDUE &
VAPORS.

Exposure Controls

Respiratory Protection:WEAR NIOSH APPROVED CANNISTER RESPIRATOR IN
ABSENCE OF ADEQUATE VENTILATION.
Ventilation:GENERAL MECHANICAL & LOCAL EXHAUST VENTILATION
Protective Gloves:RUBBER
Eye Protection:SAFETY GLASSES W/SIDE SHIELDS
Other Protective Equipment:EYE WASH, SAFETY SHOWER.
Supplemental Safety and Health

Chemical Properties

Boiling Pt:B.P. Text:151F
Vapor Pres:145
Vapor Density:2.5
Spec Gravity:0.93-0.95
Evaporation Rate & Reference:(BU AC =1): 5-8
Solubility in Water:NEGLIGIBLE
Appearance and Odor:CLEAR LIQUID W/ETHER-LIKE ODOR.

Stability

Stability Indicator/Materials to Avoid:YES
ACIDS, OXIDIZING MATERIALS, ALKALIS, CHLORINATED INORGANICS,
POTASSIUM/CALCIUM & SODIUM HYPOCHLORITE/COPPER/COPPER ALLOY
Stability Condition to Avoid:HEAT, SPARKS & OPEN FLAME.
Hazardous Decomposition Products:CO, CO2, HYDROGEN CHLORIDE, SMOKE.

Disposal

Waste Disposal Methods:DISPOSE OF IAW/FEDERAL, STATE & LOCAL
REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.

