

## **A-07 ARMOR ACRYLIC ENAMEL 11 OZ**

### **MSDS Number**

BYQPR

### **National Stock Number**

8010-00F045695

### **Product Name**

A-07 ARMOR ACRYLIC ENAMEL 11 OZ

### **Manufacturer**

MASTER CORP

### **Product Identification**

Product ID:A-07 ARMOR ACRYLIC ENAMEL 11 OZ

MSDS Date:12/09/1992

FSC:8010

NIIN:00F045695

MSDS Number: BYQPR

### **Responsible Party**

MASTER CORP

1900 EXETER ROAD

GERMANTOWN , TN 38138-1900

US

Emergency Phone: 800-255-3924

Info Phone: 901-755-5555

Cage: MASTC

### **Contractor**

MASTER CORP

381900

GERMANTOWN, TN 38138-1900

US

901-755-5555

Cage: MASTC

### **Ingredients**

ACETONE; DIMETHYL KETONE; 2-PROPANONE

CAS: 67-64-1

RTECS: AL3150000

Fraction By Weight: 18%

OSHA PEL2400 MG/CUM

ACGIH TLV: 750 PPM

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

ETHYL 3-ETHOXYPROPIONATE, PROPANOIC ACID, 3-ETHOXY-, ETHYL

CAS: 763-69-9

RTECS: UF3325000

Fraction By Weight: 4.1%

PROPANE (DIMETHYLMETHANE) \*95-4\*

CAS: 74-98-6

RTECS: TX2275000

Fraction By Weight: 14.6%

OSHA PEL1000 PPM

ACGIH TLV: SIMPLE ASPHYXIAN

ISOBUTANE, 2-METHYLPROPANE

CAS: 75-28-5

RTECS: TZ4300000

Fraction By Weight: 14.6%

OSHA PEL1800 MG/CUM

ACGIH TLV: 1000 PPM

INERT MATERIALS

Fraction By Weight: 10.9%

XYLENE, DIMETHYLBENZENE, XYLOL (IARC - GROUP 3) \*95-4\*

CAS: 1330-20-7

RTECS: ZE2100000

Fraction By Weight: 14.1%

OSHA PEL100 PPM

ACGIH TLV: 100 PPM, SKIN

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

TOLUENE (IARC CARC- GROUP 3) \*95-4\*

CAS: 108-88-3

RTECS: XS5250000

Fraction By Weight: 23.7%

OSHA PEL100 PPM

ACGIH TLV: 100 PPM

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

## Hazards

Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:INHALATION: VAPORS ARE ANESTHETIC. MAY CAUSE IRRITATION TO SKIN & RESPIRATORY TRACT. INGESTION:

HARMFUL/FATAL. REPEATED & PROLONGED OVEREXPOSURE TO SOLVENTS MAY

CAUSE PERMANENT BRAIN & NERVOUS SYSTEM DAMAGE.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:LIGHTHEADEDNESS, STAGGERING GAIT, GIDDINESS, NAUSEA, IRRITATION. DURING APPLICATION & DRYING: EYE WATERING, HEADACHE, DIZZINESS.

## First Aid

First Aid:INHALATION: REMOVE TO FRESH AIR. SKIN: WASH THOROUGHLY W/SOAP & WATER. EYES: FLUSH W/LARGE AMOUNTS OF WATER FOR 15 MINS. INGESTION: DON'T INDUCE VOMITING. OBTAIN MEDICAL ATTENTION IN ALL CASES.

## Fire Fighting

Flash Point Method:TOC  
Flash Point:Extinguishing Media:CO2/FOAM  
Fire Fighting Procedures:WEAR FULL PROTECTIVE EQUIPMENT W/SELF CONTAINED BREATHING APPARATUS. WATER MAY BE INEFFECTIVE ON FIRE BUT CAN BE USED TO COOL CONTAINERS.  
Unusual Fire/Explosion Hazard:CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT. DON'T PUNCTURE CONTAINERS. VAPORS MAY IGNITE EXPLOSIVELY.

## Accidental Release

Spill Release Procedures:REMOVE ALL IGNITION SOURCES. VENTILATE & REMOVE W/INERT ABSORBENT.

## Handling

Handling and Storage Precautions:USE ONLY W/ADEQUATE VENTILATION. KEEP FROM ALL IGNITION SOURCES. DON'T INCINERATE/BURN CONTAINER. DON'T EXPOSE TO HEAT/STORE AT TEMPS >120F.  
Other Precautions:KEEP AWAY FROM CHILDREN. DON'T DISCARD EMPTY CONTAINER IN HOME GARBAGE COMPACTOR. PREVENT BUILD-UP OF VAPORS. DON'T SMOKE. AVOID BREATHING VAPOR & CONTACT OF W/SKIN & EYES. INTENTIONAL MISUSE BY INHALING THE CONTENTS MAY BE HARMFUL/FATAL.

## Exposure Controls

Respiratory Protection:OPEN WINDOWS & DOORS/USE OTHER MEANS TO INSURE FRESH AIR ENTRY DURING APPLICATION & DRYING. IF NECESSARY, WEAR RESPIRATORY PROTECTION (NIOSH/MSHA TC 23C/LEAVE THE AREA). PROTECT AGAINST DUST GENERATED BY SANDING/ABRADING THE DRIED FILM.  
Ventilation:LOCAL EXHAUST: PREFERABLE. GENERAL EXHAUST: ACCEPTABLE IF EXPOSURE IS MAINTAINED  
Protective Gloves:SOLVENT RESISTANT  
Eye Protection:CHEMICAL SPLASH GOGGLES, FACE SHIELD  
Other Protective Equipment:SAFETY SPECTACLES W/UNPERFORATED SIDE SHIELDS  
Work Hygienic Practices:REMOVE/LAUNDER CONTAMINATED CLOTHING BEFORE REUSE. WASH HANDS AFTER USING.  
Supplemental Safety and Health

## Chemical Properties

Boiling Pt:B.P. Text:Vapor Pres:2280  
Vapor Density:>1  
Spec Gravity:Evaporation Rate & Reference:(BU ACETATE=1): Solubility in Water:INSOLUBLE  
Appearance and Odor:TYPICAL OF PAINT & LACQUER  
Percent Volatiles by Volume:85

## Stability

Stability Indicator/Materials to Avoid:YES  
Stability Condition to Avoid:HEAT, SPARKS, OPEN FLAME, TEMPS >120F & OTHER IGNITION SOURCES.  
Hazardous Decomposition Products:BY FIRE: CO2 & CO

## Disposal

Waste Disposal Methods:DON'T BURN/INCINERATE. DISPOSE OF IN ACCORDANCE W/LOCAL, STATE & FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.