

H 019-00-001 SUPERGRADE A

MSDS Number

BYQVK

National Stock Number

9150-00F046062

Product Name

H 019-00-001 SUPERGRADE A

Manufacturer

EDWARDS HIGH VACUUM INTERNATIONAL

Product Identification

Product ID:H 019-00-001 SUPERGRADE A

MSDS Date:09/02/1993

FSC:9150

NIIN:00F046062

MSDS Number: BYQVK

Responsible Party

EDWARDS HIGH VACUUM INTERNATIONAL

1 EDWARDS PK 301 BALLARDVALE STREET

WILMINGTON , MA 01887

US

Emergency Phone: (508) 658-5410

Info Phone: 508-658-5410

Cage: 21268

Contractor

EDWARDS HIGH VACUUM INTERNATIONAL

WILMINGTON, MA 01887

US

(508) 658-5410

Cage: 21268

Ingredients

ALIPHATIC HYDROCARBONS

Fraction By Weight: 100%

ACGIH TLV:

Hazards

Routes of Entry: Inhalation:NO Skin:NO Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:SKIN: GROSS OVEREXPOSURE MAY LEAD TO KERATOSIS & DERMATITIS. EYES: MAY CAUSE TRANSIENT IRRITATION OF CONJUNCTIVA. INGESTION: ASPIRATION OF LIQUID INTO LUNGS DURING VOMITING MAY CAUSE CHEMICALLY INDUCE D PNEUMONIA.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:IRRITATION.

First Aid

First Aid:SKIN/EYES: WASH W/COPIOUS AMOUNTS OF WATER FOR 10 MINS.

INHALATION: REMOVE TO FRESH AIR. INGESTION: DON'T INDUCE VOMITING.

OBTAIN MEDICAL ATTENTION IN ALL CASES.

Fire Fighting

Flash Point Method:CC

Flash Point:415.4F

Extinguishing Media:FOAM, DRY POWDER, CO2, WATER SPRAY.

Fire Fighting Procedures:WEAR BREATHING GEAR WHEN FIGHTING IN CONFINED AREAS.

Unusual Fire/Explosion Hazard:AUTOIGNITION TEMP: 471.2F. THERE IS A POSSIBILITY OF EXPLOSION IF YOU PUMP GASES CONTAINING OXYGEN OUT A CONCENTRATION >4% ABOVE THE PROPORTION CONTAINED IN AIR

Accidental Release

Spill Release Procedures:USE AN ABSORBENT. SMALL LEAKS CAN BE WIPED CLEAN.

Handling

Handling and Storage Precautions:STORE AWAY FROM HEAT. DON'T USE MINERAL OIL IN CONDITIONS WHERE THE OIL MIST & OXYGEN ENRICHED ATMOSPHERE ARE IN CONTACT W/AN IGNITION SOURCE.

Other Precautions:USE AN ALTERNATIVE PUMP FLUID UNDER THESE CONDITIONS. AVOID EXPOSURE TO OIL/MIST FUMES & VAPORS. OIL MISTS SHOULD BE KEPT TO A MINIMUM, PREFERABLY WELL BELOW 5 MG/CUM.

Exposure Controls

Respiratory Protection:DEPENDS ON CONCENTRATION OF OIL MIST IN AIR.

Ventilation:LOCAL EXHAUST: THROUGH MOST FILTER. MECHANICAL (GENERAL): EXHAUST TO ATMOSPHERE.

Protective Gloves:IMPERVIOUS POLYVINYL CHLORIDE

Eye Protection:SAFETY GLASSES

Other Protective Equipment:OVERALLS

Work Hygienic Practices:OVERALLS LAUNDERED REGULARLY.

Supplemental Safety and Health

Chemical Properties

Boiling Pt:B.P. Text:233.6F

Melt/Freeze Pt:M.P/F.P Text:5F

Vapor Pres:0.00003

Spec Gravity:0.87

pH:7

Solubility in Water:INSOLUBLE

Appearance and Odor:VISCOUS GOLDEN LIQUID W/NO ODOR.

Percent Volatiles by Volume:NONE

Stability

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS

Stability Condition to Avoid:IGNITION SOURCES, HOT SURFACES, HEAT & OTHER IGNITION SOURCES.

Hazardous Decomposition Products:CO & POSSIBLY DECOMPOSED HYDROCARBONS.

Disposal

Waste Disposal Methods:DISPOSE OF IAW/FEDERAL, STATE & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.