# Z 98 013092 A,PRO-HIDE PLUS VOC LATEX (SUPDAT)

## **MSDS Number**

**BZHRQ** 

#### **National Stock Number**

8010-00N065941

#### **Product Name**

Z 98 013092 A,PRO-HIDE PLUS VOC LATEX (SUPDAT)

#### Manufacturer

PRATT AND LAMBERT

# **Product Identification**

Product ID:Z 98 013092 A,PRO-HIDE PLUS VOC LATEX (SUPDAT)

MSDS Date: 06/24/1992

FSC:8010

NIIN:00N065941

MSDS Number: BZHRQ

# **Responsible Party**

PRATT & LAMBERT

BUFFALO, NY 14240

US

Emergency Phone: 716-873-6000

Info Phone: 716-873-6000

Cage: 77359

#### **Contractor**

PRATT & LAMBERT

BUFFALO, NY 14240

US

716-873-6000

Cage: 77359

# **Ingredients**

SILICATE, MICA; (MICA)

CAS: 12001-26-2

RTECS: VV8760000

Fraction By Weight: 5% OSHA PEL20 MPPCF; Z-3

ACGIH TLV: 3 MG/M3 RDUST

SILICA, CRYSTALLINE - QUARTZ

CAS: 14808-60-7

RTECS: VV7330000

Fraction By Weight: 5%

**OSHA PELSEE TABLE Z-3** 

ACGIH TLV: 0.1 MG/M3 RDUST



0.44 LB/GAL (53 G/L) LESS WATER &

RTECS: 99999999VO OSHA PELN/K ACGIH TLV: N/K

#### **Hazards**

LD50 LC50 Mixture: NONE SPECIFIED BY MANUFACTURER. Routes of Entry: Inhalation: YES Skin: YES Ingestion: YES Reports of Carcinogenicity: NTP: YES IARC: YES OSHA: NO

Health Hazards Acute and Chronic:ACUTE: INHAL: MAY CAUSE MILD RESPIRATORY IRRIT. EYE: LIQUID SPLASHED INTO EYE MAY CAUSE

TRANSIENT EYE IRRIT. MAY CAUSE MECHANICAL EYE IRRIT. RPTD & PRLNGD

OCCUP OVEREXP TO CRYSTALLINE SILICA MAY CAUSE SILICOSIS, A

PROGRESSIVELY DISABLING LUNG DISEASE.

Explanation of Carcinogenicity:SILICA, CRYSTALLINE-QUARTZ: IARC MONO, SUPP. VOL 7, PG 341, 1987: GROUP 2A. NTP 7TH ANNUAL REPORT ON CARCINS, (SUPDAT)

Effects of Overexposure: SEE HEALTH HAZARDS.

Medical Cond Aggravated by Exposure: PRE-EXISTING RESPIRATORY CONDITIONS MAY BE AGGRAVATED BY EXPOSURE TO CRYSTALLINE SILICA.

#### First Aid

First Aid:INGEST: CALL POIS CNTRL CTR, HOSP EMER ROOM/MD IMMED. INHAL: REMOVE TO FRESH AIR. EYE: FLUSH W/LGE AMTS OF WATER, LIFTING UPPER & LOWER LIDS OCCAS. CONTINUE FOR AT LEAST 15 MINS. GET MED ATTN. SKIN: R EMOVE CONTAMD CLTHG. WASH AFFECTED AREAW/SOAP & WATER. OBTAIN MED ATTN IF IRRIT PERSISTS. NOTE TO MD: ANY TREATMENT THAT MIGHT BE REQD FOR OVEREXP SHOULD BE DIRECTED AT CONTROL OF SYMPS &(SUPDAT)

#### Fire Fighting

Extinguishing Media: WILL NOT BURN. USE MEDIA SUITABLE FOR SURROUNDING FIRE.

Fire Fighting Procedures: WEAR NIOSH/MSHA APPROVED SCBA & FULL PROTECTIVE EQUIPMENT.

Unusual Fire/Explosion Hazard: NONE KNOWN.

#### **Accidental Release**

Spill Release Procedures: CONFINE IN SMALL AREA; USE ABSORBENT TO CLEAN UP. PLACE IN CONTAINER FOR DISPOSAL. Neutralizing Agent: NONE SPECIFIED BY MANUFACTURER.

### Handling

Handling and Storage Precautions: PROTECT FROM FREEZING.
Other Precautions: DO NOT TAKE INTERNALLY. CLOSE CONTAINER AFTER EACH USE. KEEP AWAY FROM CHILDREN. DO NOT BREATHE SANDING DUST.

#### **Exposure Controls**

Respiratory Protection:IF APPLIED BY SPRAYING, USE AN APPROPRIATE, PROPERLY FITTED NIOSH/MSHA APPROVED RESPIRATOR TO REMOVE THE SPRAY MIST. REFER TO OSHA 29CFR 1910.134 "RESPIRATORY PROTECTION". Ventilation:PROVIDE LOC EXHST VENT IN SUFF VOL & PATTERN SO AS TO MAINTAIN EXPOS Protective Gloves:IMPERVIOUS GLOVES.

Eye Protection: ANSI APPRVD CHEM WORKERS GOGGS.

Other Protective Equipment: EMERGENCY EYEWASH & DELUGE SHOWER MEETING ANSI DESIGN CRITERIA.

Work Hygienic Practices: NONE SPECIFIED BY MANUFACTURER.

Supplemental Safety and Health

TRADENAME: BLOCKFILLER WHITE. EXPLAN OF CARCIN: 1994: ANTICIPATED TO BE CARCINOGEN. FIRST AID PROC: CLINICAL CNDTNS. VENT: LIMITS WHICH MAY BE LISTED. REFER TO INDUSTRIAL VENTILATION- A MANUAL FOR REC OMMENDED PRACTICE- AMERICAN CONFERENCE OF GOVERNMENTAL INDUSTRIAL HYGIENISTS.

### **Chemical Properties**



Boiling Pt:B.P. Text:>162F,>72C

Vapor Density: HVR/AIR

Spec Gravity: 1.7

Evaporation Rate & Reference:SLOWER THAN DIETHYL ETHER Appearance and Odor:NONE SPECIFIED BY MANUFACTURER.

Percent Volatiles by Volume:50

# **Stability**

Stability Indicator/Materials to Avoid:YES NONE KNOWN.
Stability Condition to Avoid:NONE KNOWN.
Hazardous Decomposition Products:BURNING INCLG WHEN HEATED BY WELDING/CUTTING WILL PRDCE SMOKE, CARBON MONOXIDE AND CARBON DIOXIDE.

## **Disposal**

Waste Disposal Methods: DISPOSE OF IN ACCORDANCE W/LOCAL, STATE & FEDERAL LAWS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.