https://msdsreport.com/msds/BZMPR

<u>T-204, 12759</u>

MSDS Number

BZMPR

National Stock Number

7930-00N066449

Product Name

T-204, 12759

Manufacturer

ALCO PRODUCTS INC

Product Identification

Product ID:T-204, 12759 MSDS Date:11/30/1988 FSC:7930 NIIN:00N066449 MSDS Number: BZMPR

Responsible Party

ALCO PRODUCTS INC

13126 SATICOY ST

NORTH HOLLYWOOD , CA 91605

US

Emergency Phone: 714-634-5988;800-424-9300(CHEMTREC)

Info Phone: 818-764-7700

Cage: 0AXK7

Contractor

ALCO PRODUCTS INC

NORTH HOLLYWOOD, CA 91605

US

818-764-7700

Cage: 0AXK7

Ingredients

SOLVENT NAPHTHA (PETROLEUM) MEDIUM ALIPHATIC; (ALIPHATIC

CAS: 64742-88-7

Fraction By Weight: 100%

OSHA PEL300 PPM (MFR)

ACGIH TLV: 300 PPM (MFR)

Hazards

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER. Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:SKIN:CONTACT OF PRODUCT CAN CAUSE SEVERE IRRITATION AND/OR DEFATTING DUE TO THE REMOVAL OF SKINS NATURAL OILS. EYES:CONTACT OF PRODUCT CAN CAUSE SEVERE IRRITATION AND/OR DEHYDRATION OF THE EYES AND EY ELIDS. INHALATION:FUMES FROM PRODUCT CAN CAUSE NARCOTIC EFFECTS, NAUSEA, DIZZINESS, DOUBLE VISION, (EFTS OF OVEREXP) Explanation of Carcinogenicity:NOT RELEVANT Effects of Overexposure:HLTH HAZS:HDCHS & VOMITING. OTHER SYMPTOMS



INCLUDE POSSIBLE IRRIT & DEFAT OF NOSE, NASAL PASSAGES & LUNGS. INGEST:WHEN CONC SOLN OF PROD IS SWALLOWED; IT CAN CAUSE SEV IRRIT &/OR DEFAT OF MOUTH, ESOPH AGUS, STOM & INTESTINAL TRACT. OTHER SYMPS OF INGEST INCLUDE NARCOTIC EFTS, NAUS, DIZZ, DOUBLE VISION, HDCHS & VOMIT.

•

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

First Aid

First Aid:SKIN:FLUSH AREA EXPOSED FOR 15 MIN W/LUKE WARM WATER. IF DEFAT OCCURS, SKIN LOTION IS ADVISED. CONSULT MD IMMED. EYES:FLUSH AT LST 15 MIN W/COOL WATER. CONSULT MD IMMED. INHAL:REMOVE TO CLEAN ATM & AD MIN OXYG IF IT IS AVAIL. CONSULT MD IMMED. INGEST:INDUCE VOMIT; HAVE PATIENT DRINK LG AMTS OF MILK/WATER. CONSULT MD IMMED.

Fire Fighting

Flash Point:122F,50C

Extinguishing Media:SAND, DRY CHEMICAL, DRY FOAM, WATER. Fire Fighting Procedures:WEAR NIOSH/MSHA APPROVED SCBA & FULL PROTECTIVE EQUIPMENT . THIS MATERIAL READILY IGNITES IF NEAR HIGH TEMPERATURES SOURCE OR OPEN FLAME. Unusual Fire/Explosion Hazard:IF THIS MATERIAL IS EXPOSED TO A HIGH HEAT SOURCE OR OPEN FLAME THERE IS THE DANGER OF AN EXPLOSION.

Accidental Release

Spill Release Procedures:SM SPILL:FLUSH AREA W/WATER TO INDUST SEWER LINE. LG SPILL:CNTN SPILL W/DIKES OF ABSORB MATLS SUCH AS CLAY, SAND OR VERMICULITE. COLLECT MATERIAL AND DISPOSE OF MATERIAL IN A CERTIFIED CLASS ONE DISPO SAL FACILITY.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

Handling

Handling and Storage Precautions: KEEP THIS MATERIAL AWAY FROM HIGH HEAT AND OBSERVE PROEPR HOUSEKEEPING PROCEDURES. DO NOT MIX CHEMICALS UNLESS INSTRUCTED BY QUALIFIED PERSONNEL.

Other Precautions: CHEMICALS CAN BE HAZARDOUS IF NOT RESPECTED. THE USE OF PROPER EQUIPMENT AND PROCEDURES FOR HANDLING CHEMICALS ARE NOT ONLY OF BENEFIT FOR THEIR OBVIOUS USES, BUT CAN REDUCE POSSIBILITY OF SERIOUS INJ URY AND TIME LOSS ACCIDENTS.

Exposure Controls

Respiratory Protection: WHEN USING THIS MATERIAL IN CONFINED SPACE, USE OF NIOSH/MSHA APPROVED PERSONAL RESPIRATORY PROTECTION IS RECOMMENDED.

Ventilation: NONE SPECIFIED BY MANUFACTURER.

Protective Gloves: IMPERVIOUS GLOVES .

Eye Protection: ANSI APPROVED CHEM WORKERS GOGGS .

Other Protective Equipment: ANSI APPRVD EMER EYEWASH & DELUGE SHOWER . WHEN HNDLG CHEMS IN 55 GALLON DRUMS IT IS REC THAT STEEL TOED (SUP DAT)

Work Hygienic Practices: KEEP THIS MATERIAL AWAY FROM HIGH HEAT AND

OBSERVE PROPER HOUSEKEEPING PROCEDURES.

Supplemental Safety and Health

OTHER PROT EQUIP: RUBBER BOOTS AND A SPLASH APRON BE WORN.

Chemical Properties

Boiling Pt:B.P. Text:352F,178C Vapor Density:4.69 Spec Gravity:0.84 (H*2O=1) Evaporation Rate & Reference:0.5 (H*2O=1) Solubility in Water:NOT SOLUBLE Appearance and Odor:CLEAR, RED LIQUID WITH A CITRUS ODOR. Percent Volatiles by Volume:100

Stability

Stability Indicator/Materials to Avoid:YES NONE SPECIFIED BY MANUFACTURER. Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER.



Hazardous Decomposition Products: NONE SPECIFIED BY MANUFACTURER.

Disposal

Waste Disposal Methods:ALL HAZARDOUS MATERIALS MUST BE SOLIDIFIED AND DISPOSED OF IN AN EPA APPROVED CLASS ONE FACILITY. WHEN DISPOSING OF CHEMICALS, CONTACT LOCAL, STATE AND FEDERAL ENVIRONMENTAL AGENCIES TO FULLY UNDERSTA ND THE NEC REGS GOVERNING DISP OF CHEM WASTES.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.