

## **TRIBOLUBE-2**

### **MSDS Number**

BZQZY

### **National Stock Number**

9150-01-360-5638

### **Product Name**

TRIBOLUBE-2

### **Manufacturer**

AEROSPACE LUBRICANTS INC

### **Product Identification**

Product ID:TRIBOLUBE-2

MSDS Date:10/26/1993

FSC:9150

NIIN:01-360-5638

MSDS Number: BZQZY

### **Responsible Party**

AEROSPACE LUBRICANTS INC

1505 DELASHMUT AVE

COLUMBUS , OH 43212

US

Emergency Phone: 614-291-3045

Info Phone: 614-291-3045

Cage: 66164

### **Contractor**

AEROSPACE LUBRICANTS INC.

COLUMBUS, OH 43228

US

614-878-3600

Cage: 66164

### **Ingredients**

NON-HAZARDOUS INGREDIENTS

OSHA PELN/K

ACGIH TLV: N/K

### **Hazards**

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE:NONE. PROLONGED EXPOSURE CAUSES NO KNOWN ADVERSE EFFECTS. CHRONIC:NONE.

Explanation of Carcinogenicity:NOT RELEVANT

Effects of Overexposure:SEE HEALTH HAZARDS.

Medical Cond Aggravated by Exposure:NO KNOWN MEDICAL CONDITIONS THAT MIGHT BE AGGRAVATED BY EXPOSURE.

### **First Aid**

First Aid:INGESTION:CALL MD IMMEDIATELY . INHALATION:REMOVE TO FRESH AIR. SUPPORT BREATHING (GIVE O\*2/ARTF RESP) . EYES:FLUSH WITH WATER FOR AT LEAST 15 MINUTES. SKIN:WIPE OFF AND WASH WITH WATER.

## Fire Fighting

Extinguishing Media:CO\*2, DRY CHEMICAL, FOAM, WATER SPRAY.  
Fire Fighting Procedures:WEAR NIOSH/MSHA APPROVED SCBA & FULL PROTECTIVE EQUIPMENT .  
Unusual Fire/Explosion Hazard:TOXIC FLUORINE GASES.

## Accidental Release

Spill Release Procedures:USE ABSORBENT MATERIALS TO COLLECT AND CONTAIN FOR SALVAGE OR DISPOSAL.  
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

## Handling

Handling and Storage Precautions:USE REASONABLE CARE.  
Other Precautions:TOXIC VAPORS MAY EVOLVE ABOVE 550F; PROVIDE ADEQUATE VENTILATION IF USED ABOVE THIS TEMPERATURE.

## Exposure Controls

Respiratory Protection:USE NIOSH/MSHA APPROVED RESPIRATOR APPROPRIATE FOR EXPOSURE OF CONCERN . NOT REQUIRED.  
Ventilation:LOCAL EXHAUST:NOT REQUIRED. MECHANICAL (GENERAL):RECOMMENDED.  
Protective Gloves:PLASTIC DISPOSABLE.  
Eye Protection:ANSI APPROVED CHEM WORKERS GOGGS .  
Other Protective Equipment:ANSI APPROVED EMERGENCY EYE WASH AND DELUGE SHOWER . PLASTIC APRON, FABRIC LABORATORY COAT RECOMMENDED.  
Work Hygienic Practices:DO NOT CONTAMINATE SMOKING MATERIALS; WASH HANDS AFTER EXPOSURE.  
Supplemental Safety and Health  
NONE SPECIFIED BY MANUFACTURER.

## Chemical Properties

Melt/Freeze Pt:M.P/F.P Text:>550F,>288C  
Vapor Pres:Spec Gravity:1.30 (H\*2O=1)  
Solubility in Water:NIL  
Appearance and Odor:YELLOW

## Stability

Stability Indicator/Materials to Avoid:YES  
OXIDIZING MATERIALS CAN CAUSE A REACTION.  
Hazardous Decomposition Products:FLUORINE PRODUCTS, SILICON DIOXIDE, CO\*2, TRACES OF INCOMPLETELY BURNED CARBON.

## Disposal

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.