

PETROLEUM WAX BLEND

MSDS Number

BZXQK

National Stock Number

6520-00F050341

Product Name

PETROLEUM WAX BLEND

Manufacturer

BUFFALO DENTAL MFG CO INC

Product Identification

Product ID: PETROLEUM WAX BLEND

MSDS Date: 07/05/1992

FSC: 6520

NIIN: 00F050341

MSDS Number: BZXQK

Responsible Party

BUFFALO DENTAL MFG CO INC

99 LAFAYETTE DR

SYOSSET, NY 11791-3416

US

Emergency Phone: 516-496-7200

Info Phone: 516-496-7200

Cage: 09496

Contractor

BUFFALO DENTAL MFG CO INC

SYOSSET, NY 11791-3416

US

516-496-7200

Cage: 09496

Ingredients

PETROLEUM WAX BLEND

Hazards

Routes of Entry: Inhalation: YES Skin: NO Ingestion: NO

Reports of Carcinogenicity: NTP: NO IARC: NO OSHA: NO

Health Hazards Acute and Chronic: EYES: MOLTEN WAX FUMES MAY BE SLIGHTLY IRRITATING. SKIN: MOLTEN WAX WILL CAUSE BURNS ON CONTACT.

INHALATION: MAY CAUSE MILD UPPER RESPIRATORY IRRITATION.

Explanation of Carcinogenicity: NONE

Effects of Overexposure: IRRITATION, BURNS

First Aid

First Aid: EYES: FLUSH W/WATER FOR 15 MINS. SKIN: IF HOT WAX STRIKES THE SKIN, DRENCH/IMMERSE THE AREA IN WATER TO ASSIST COOLING. APPLY ICED WATER/ICE PACKS TO THE BURNED AREA. (DON'T USE ICED WATER/ICE PACKS IF THE BURNED AREA COVERS >10% OF THE BODY, MAY CAUSE SHOCK. DON'T TRY TO REMOVE WAX FROM A BURN AFTER IT HAS COOLED.

INHALATION: REMOVE TO FRESH AIR. OBTAIN MEDICAL ATTENTION IN ALL CASES.

Fire Fighting

Flash Point Method:COC
Flash Point:450F
Extinguishing Media:WATER FOG, FOAM, DRY CHEMICAL, CO2
Fire Fighting Procedures:DON'T ENTER CONFINED FIRE SPACE W/O PROPER PROTECTIVE EQUIPMENT W/A NIOSH APPROVED SELF-CONTAINED BREATHING APPARATUS. COOL FIRE EXPOSED CONTAINERS W/WATER.
Unusual Fire/Explosion Hazard:DON'T USE A DIRECT STREAM OF WATER.
PRODUCT WILL FLOAT & CAN BE REIGNITED ON SURFACE OF WATER.

Accidental Release

Spill Release Procedures:USE CAUTIOUS JUDGEMENT WHEN CLEANING UP LARGE MOLTEN LEAKS. LARGE: WEAR RESPIRATOR & PROTECTIVE CLOTHING. SHUT OFF SOURCE OF LEAK SAFELY. DIKE & CONTAIN. ALLOW WAX TO COOL & REMOVE AS SOLID. SMALL: AL LOW WAX TO COOL & REMOVE AS SOLID.

Handling

Handling and Storage Precautions:STORE IN A COOL AREA.
Other Precautions:MINIMIZE BREATHING OF VAPORS, FUMES/MIST. AVOID CONTACT W/HOT MATERIAL.

Exposure Controls

Respiratory Protection:IF EXPOSURE MAY/DOES EXCEED OEL, USE A NIOSH APPROVED RESPIRATOR TO PREVENT EXPOSURE. IAW/29 CFR 1910.134 USE EITHER AN ATMOSPHERE-SUPPLYING RESPIRATOR/AN AIR PURIFYING RESPIRATOR FOR PARTICULATES.
Protective Gloves:REQUIRED
Eye Protection:SAFETY GLASSES/GOGGLES
Other Protective Equipment:FACE SHIELD & PROTECTIVE CLOTHING TO PROTECT SKIN AGAINST HOT WAX.
Supplemental Safety and Health
THIS MSDS IS FOR WAXES, SHEETS, PRESSURE, SENSITIVE, STICKS & WIRE.

Chemical Properties

Boiling Pt:B.P. Text:600F
Vapor Pres:Spec Gravity:Solubility in Water:Appearance and Odor:VARIOUS COLORS DEPENDING ON TYPE W/CHARACTERISTIC ODOR

Stability

Stability Indicator/Materials to Avoid:YES
Hazardous Decomposition Products:CO, CO2 & UNIDENTIFIED ORGANIC COMPOUNDS MAY BE FORMED DURING COMBUSTION.

Disposal

Waste Disposal Methods:PLACE IN APPROPRIATE DISPOSAL FACILITY IN ACCORDANCE W/LOCAL, STATE & FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.