

PACTRA IMPERIAL ENAMELS, 16 NIMBUS GRAY

MSDS Number

CBHJQ

National Stock Number

8010-00N068257

Product Name

PACTRA IMPERIAL ENAMELS, 16 NIMBUS GRAY

Manufacturer

PACTRA COATINGS INC

Product Identification

Product ID:PACTRA IMPERIAL ENAMELS, 16 NIMBUS GRAY

MSDS Date:07/16/1987

FSC:8010

NIIN:00N068257

MSDS Number: CBHJQ

Responsible Party

PACTRA COATINGS INC

420 S 11TH AVE

UPLAND , CA 91786

US

Emergency Phone: 714-946-3871

Info Phone: 714-946-3871

Cage: IO302

Contractor

PACTRA INDUSTRIES

280

UPLAND, CA 91786-6828

US

714-946-3871

Cage: 33777

Ingredients

SLOWER

CAS: 67-64-1

RTECS: AL3150000

Fraction By Weight: 25-35%

OSHA PEL1000 PPM

ACGIH TLV: 750 PPM;1000 STEL

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

SLOWER

CAS: 1330-20-7

RTECS: ZE2100000

Fraction By Weight: 5-10%
OSHA PEL100 PPM
ACGIH TLV: 100 PPM;150 STEL
EPA Report Quantity: 1000 LBS
DOT Report Quantity: 1000 LBS

8030-20-7).
CAS: 8032-32-4
RTECS: OI6180000
Fraction By Weight: 5-10%
OSHA PEL300 PPM
ACGIH TLV: 300 PPM

SOLV NAPHTHA (PETRO), LIGHT AROMATIC; (HISOL 10 (AROMATIC
CAS: 64742-95-6
RTECS: WF3400000
Fraction By Weight: 5%
OSHA PEL100 PPM (MFR)
ACGIH TLV: 100 PPM (MFR)

38 @ 20C. EVAP
CAS: 64742-89-8
Fraction By Weight: 6-16%
OSHA PEL200 PPM (MFR)
ACGIH TLV: 500 PPM (MFR)

FASTER THAN ETHER. FL
CAS: 74-98-6
RTECS: TX2275000
Fraction By Weight: 30%
OSHA PEL1000 PPM
ACGIH TLV: ASPHYXIA NT

NON-HAZARDOUS INGREDIENTS
Fraction By Weight: 8-17%
OSHA PELN/K
ACGIH TLV: N/K

(TC23C OR EQUIVALENT), OR LEAVE THE AREA.
RTECS: 9999999ZZ

Hazards

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE:INHAL:EXCESSIVE INHAL OF VAPS
CAN CAUSE NASAL & RESP IRRIT, DIZZ, WEAK, FATG, NAUS, HDCH, POSS
UNCON & EVEN ASPHY. EYE CONT:CAN CAUSE SEV IRRIT, REDNESS, TEARING,
BLURRED VISION. INGEST:CAN CAUS E GI IRRIT, NAUS, VOMIT, DIARR.
SKIN CONT:CAN CAUSE IRRIT FOR SOME PERSONS. CHRONIC:RPTS HAVE ASSOC
(EFTS OF OVEREXP)
Explanation of Carcinogenicity:NOT RELEVANT
Effects of Overexposure:HLTH HAZ:RPTD & PRLNG OCCUP OVEREXP TO SOLVS
W/PERM BRAIN & NERV SYS DMG. SEV OVEREXP IN LAB ANIMALS HAS ALSO
CAUSED LIVER ABNORMS & DMG TO KIDNEYS, LUNGS & SPLEEN. INTENTIONAL
MISUSE BY DELIBERATELY CONCENTRATING & INHALING CONTENTS MAY BE
HARMFUL OR FATAL.
Medical Cond Aggravated by Exposure:CAN CAUSE ALLERGIC RESPIRATORY &/OR
SKIN REACTION.

First Aid

First Aid:INHAL:REMOVE INDIVIDUAL TO FRESH AIR. IF BRTHG IS DFCLT,
ADMIN OXYG. IF BRTHG HAS STOPPED, GIVE ARTF RESP & SEEK MED HELP.
EYES:FLUSH W/WATER FOR AT LST 15 MINS WHILE OCCAS HOLDING EYELIDS
OPEN. GET M ED ATTN. INGEST:DO NOT INDUCE VOMIT (ASPIR OF MATL INTO
LUNGS CAN CAUSE CHEM PNEUM, WHICH CAN BE FATAL). KEEP PERS WARM,
QUIET & GET MED ATTN/POIS CTL CTR. SKIN:WASH W/SOAP & WATER/VARIOUS
(SUPDAT)

Fire Fighting

Flash Point:0F,-18C
Lower Limits:1%
Extinguishing Media:"ALCOHOL" FOAM, CO*2 DRY CHEMICAL.
Fire Fighting Procedures:USE NIOSH/MSHA APPRVD SCBA & FULL PROT EQUIP .
WATER SPRAY MAY BE INEFT. WATER MAY BE USED TO COOL CLSD CNTNRS TO
PVNT PRESS BUILD-UP & POSS (SUPP DATA)
Unusual Fire/Explosion Hazard:EXTREMELY FLAMM. CLSD CNTNRS MAY EXPLODE
&/OR AUTOIGNITE WHEN EXPOS TO EXTREME HEAT. VAPS ARE HVR/AIR & MAY
TRAVEL ALONG GROUND/MAY BE MOVED BY VENT & (SUPDAT)

Accidental Release

Spill Release Procedures:ELIMINATE ALL IGNITION SOURCES. VENTILATE
AREA. ABSORB LIQUID ON PAPER, VERMICULITE, FLOOR ABSORBENT OR OTHER
ABSORBENT MATERIAL & TRANSFER TO A CLOSED CONTAINER.
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

Handling

Handling and Storage Precautions:DO NOT STORE IN AREAS ABOVE 120F, OR
IN DIRECT SUNLIGHT, OR NEAR HEAT OR OPEN FLAMES. DO NOT PUNCTURE OR
INCINERATE.
Other Precautions:STORE LG QUANTITIES IN BUILDINGS PROTECTED FOR
STORAGE OF NFPA CLASS IC FLAMMABLE LIQUIDS. AS W/ALL CHEMS, MIN
PERS CONT & BRTHG OF VAPS. WHERE SPECIAL/UNUSUAL CNDTNS EXIST, THE
EXPERT ASSISTANCE OF A N INDUSTRIAL HYGIENIST SHOULD BE SOUGHT.

Exposure Controls

Respiratory Protection:FOR CASUAL/OCCAS USE - TO AVOID BRTHG VAPS/SPRAY
MIST, OPEN WINDOWS & DOORS/USE OTHER MEANS TO ENSURE FRESH AIR
ENTRY DURING APPLICATION & DRYING. IF YOU EXPER EYE WATERING,
HDCHS/DIZZ, INCR FRESH AIR , WEAR NIOSH/MSHA RESP PROT (ING 8)
Ventilation:FOR REGULAR/CONTINUOUS USE - PROVIDE SUFFICIENT MECH (GEN)
&/OR LOC EXHST VENT TO MAINTAIN EXPOS BELOW TLV'S.
Protective Gloves:CHEM RESIST GLOVES, SUCH AS NEOPRENE.
Eye Protection:ANSI APPROVED CHEM WORKERS GOGGS .
Other Protective Equipment:EYE WASH FOUNTAIN & DELUGE SHOWER WHICH MEET
ANSI DESIGN CRITERIA .
Work Hygienic Practices:WASH HANDS BEFORE EATING OR USING WASHROOM.
Supplemental Safety and Health
MP:>1500F,>816C. FIRE FIGHT PROC:AUTOIGNIT/EXPLO WHEN EXPOS TO EXTREME

HEAT. IF WATER IS USED, FOG NOZZ ARE PREF. EXPLO HAZ:IGNITED BY PILOT LIGHTS, OTHER FLAMES, SPKS, HEATERS, SMOKING, ELEC MOTORS/O THER IGNIT SOURCES AT LOCATIONS DIST FROM MATL HNDLG POINT. FIRST AID PROC:HAND CLEANERS & WASH CLTHG BEFORE RE-USE.

Chemical Properties

Boiling Pt:B.P. Text:>133F,>56C
Melt/Freeze Pt:M.P/F.P Text:SUPP DATA
Vapor Pres:SEE INGS
Vapor Density:HVR/AIR
Spec Gravity:Evaporation Rate & Reference:SEE INGREDIENTS.
Solubility in Water:SLIGHT TO MODERATE
Appearance and Odor:TYPICAL SOLVENT PAINT.
Percent Volatiles by Volume:85-90

Stability

Stability Indicator/Materials to Avoid:YES
AVOID CONTACT W/STRONG OXIDIZING AGENTS & HEAT.
Stability Condition to Avoid:HEAT, SPARKS & OPEN FLAME.
Hazardous Decomposition Products:MAY FORM TOXIC MATERIALS, CARBON DIOXIDE/CARBON MONOXIDE, VARIOUS HYDROCARBONS, NITROGEN COMPOUNDS, ETC, WHEN BURNED.

Disposal

Waste Disposal Methods:MATERIAL COLLECTED ON ABSORBENT MATERIAL MAY BE DEPOSITED IN A POSTED TOXIC SUBSTANCE LANDFILL I/A/W LOCAL, STATE & FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.