

NAPA ND 30, 00075115

MSDS Number

CBMLX

National Stock Number

9150-00N070743

Product Name

NAPA ND 30, 00075115

Manufacturer

VALVOLINE INC

Product Identification

Product ID:NAPA ND 30, 00075115

MSDS Date:11/07/1991

FSC:9150

NIIN:00N070743

MSDS Number: CBMLX

Responsible Party

VALVOLINE INC

LEXINGTON , KY 40512

US

Emergency Phone: 800-274-5263

Info Phone: 606-264-7000

Cage: GO029

Contractor

VALVOLINE OIL CO

14000

LEXINGTON, KY 40512

US

606-357-7206 / 800-274-5263

Cage: 72527

Ingredients

SOLVENT DEWAXED RESIDUAL OIL (PETROLEUM); (PETROLEUM OIL)

CAS: 64742-62-7

Fraction By Weight: 25-40%

OSHA PELN/K

ACGIH TLV: N/K

SEVERELY HYDROTREATED HYDROCARBON OIL (ALSO CAS #72623-85-9

CAS: 72623-87-1

Fraction By Weight: 70-85%

OSHA PEL5 MG/M3 (MFR)

ACGIH TLV: 5 MG/M3 (MFR)

SHOULD BE EXCLUDED FROM AREA OF SPILL UNTIL

RTECS: 9999999ZZ

AREA OF SPILL TO PVNT SPREADING, PUMP LIQ TO SALV

RTECS: 9999999ZZ

EARTH, FLOOR ABSORBENT, OR OTHER ABSORBENT MATERIAL

RTECS: 9999999ZZ

Hazards

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:PROD IS NOT HAZ AS DEFINED BY OSHA (29 CFR 1910.1200) BASED ON TESTING OF SIMILAR PRODS &/OR COMPONENTS.
EYES:NOT EXPECTED TO CAUSE IRRIT DURING NORMAL CNDTNS OF USE.
SKIN:PRLNGD/RPTD CONT MAY BE MILD LY IRRIT TO SKIN & MAY CAUSE DERM. INGEST:NOT EXPECTED TO BE TOX. PROD HAS LAXATIVE PROPERTIES & MAY (EFTS OF OVEREXP)
Explanation of Carcinogenicity:NOT RELEVANT
Effects of Overexposure:HLTH HAZS:CAUSE NAUS, ABDOM CRAMPS & DIARR.
INHAL:NOT EXPECTED TO BE A HAZ AT NORMAL ROOM TEMP. HOWEVER, IF EXPOS EXCEED PEL/TLV OF 5 MG/M3 FOR OIL MIST, THEN INHAL OF MIST MAY RSLT IN RESP IRRIT & PO SS DISCOMFORT. CHRONIC:NONE CURRENTLY KNOWN FOR PROD. CAUTN:USED MOTOR OIL HAS BEEN SHOWN TO CAUSE SKIN CANCER (SUP DAT)
Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

First Aid

First Aid:SKIN:THORO WASHED EXPOSED AREA W/SOAP & WATER. REMOVE CONTAM CLTHG & LAUNDER BEFORE REUSE. EYES:FLUSH W/LG AMTS OF WATER, LIFTING LIDS OCCAS. GET MED ATTN, IF IRRIT PERSISTS. INGEST:DO NOT INDUCE VOMI T, KEEP PERSON WARM & QUIET, & GET MED ATTN.
INHAL:REMOVE INDIVIDUAL TO FRESH AIR. IF BRTHG IS DFCLT, ADMIN OXYG. IF BRTHG HAS STOPPED GIVE ARTF RESP. KEEP PERSON WARM, QUIET & GET MED ATTN.

Fire Fighting

Flash Point Method:COC
Flash Point:>430F,>221C
Extinguishing Media:REGULAR FOAM OR CARBON DIOXIDE OR DRY CHEMICAL.
Fire Fighting Procedures:WEAR NIOSH/MSHA APPRVD SCBA & FULL PROT EQUIP . WATER/FOAM MAY CAUSE FROTHING WHICH CAN BE VIOLENT & POSS ENDANGER LIFE OF FIREFIGHTER, ESP IF (SUPP DATA)
Unusual Fire/Explosion Hazard:NEVER USE WELDING OR CUTTING TORCH ON OR NEAR DRUM (EVEN EMPTY) BECAUSE PRODUCT (EVEN JUST RESIDUE) CAN IGNITE EXPLOSIVELY.

Accidental Release

Spill Release Procedures:SM SPILL:ABSORB LIQ ON PAPER, VERMICULITE, FLOOR ABSORB/OTHER ABSORB MATL. LG SPILL:PVNT RUN-OFF TO SEWERS, STREAMS/OTHER BODIES OF WATER. IF RUN-OFF OCCURS, NOTIFY PROPER AUTHS AS REQ, THAT SPILL HAS OCCURED. PERSONS NOT WEARING PROT EQUIP (ING 3)
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

Handling

Handling and Storage Precautions:DO NOT TRANSFER TO UNLBLED CNTNR. DO NOT USE CUTTING/WELDING TORCH ON CNTNR (EVEN EMPTY). FOR INDUST USE ONLY.
Other Precautions:BEFORE USE, REVIEW MSDS FOR MORE DETAILED INFO, INCLUDING CHRONIC HLTH EFTS. 24-HR EMER # 1-800-274-5263. CNTNRS OF MATL MAY BE HAZ WHEN EMPTIED SINCE THEY RETAIN PROD RESIDUES (VAP,

LIQ &/OR SOLID), ALL HAZ PRECS MUST BE OBSERVED.

Exposure Controls

Respiratory Protection:NOT REQ UNDER NORMAL CNDTNS OF USE. HOWEVER, IF OIL MISTS ARE GENERATED ABOVE REC PEL/TLV OF 5 MG/M3, THEN NIOSH/MSHA APPRVD RESP IS ADVISED IN ABSNECE OF PROPER ENVIRONMENTAL CONTROL. (SEE YOUR SAFETY EQUIPMENT SUPPLIER).
Ventilation:NOT REQ UNDER NORMAL CNDTNS OF USE. HOWEVER, IF UNUSUAL OPERATING CNDTNS EXIST, THEN PROVIDE SUFFICIENT MECH (SUPP DATA)
Protective Gloves:RESIST GLOVES SUCH AS NITRILE RUBBER.
Eye Protection:ANSI APPROVED CHEM WORKERS GOGGS .
Other Protective Equipment:ANSI APPROVED EMERGENCY EYE WASH AND DELUGE SHOWER . NORMAL WORK CLOTHING COVERING ARMS AND LEGS.
Work Hygienic Practices:NONE SPECIFIED BY MANUFACTURER.
Supplemental Safety and Health
FIRE FIGHT PROC:SPRAYED INTO CNTNRS OF HOT, BURNING LIQ. DENSE SMK MAY BE GENERATED WHILE BURNING. EFTS OF OVEREXP:IN CERTAIN LAB ANIMALS CONTINUALLY EXPOSED TO USED MOTOR OIL BY RPTD APPLICATNS. AVOID PRLNGD/RPTD CONT TO SKIN. VENT:(GEN &/OR LOC EXHST) VENT TO MAINTAIN EXPOS BELOW PEL/TLV(S).

Chemical Properties

Boiling Pt:B.P. Text:575F,302C
Vapor Density:HVR/AIR
Spec Gravity:0.889 @ 60F
Evaporation Rate & Reference:SLOWER THAN ETHER
Appearance and Odor:LIGHT AMBER LIQUID IN HOMOG SOLUTION FORM.

Stability

Stability Indicator/Materials to Avoid:YES
AVOID CONTACT WITH:STRONG OXIDIZING AGENTS.
Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER.
Hazardous Decomposition Products:NONE SPECIFIED BY MANUFACTURER.

Disposal

Waste Disposal Methods:SMALL AND LARGE SPILLS:DISPOSE OF IN ACCORDANCE WITH ALL LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.