

EXTERIOR WOOD FINISH-BROWN OAK

MSDS Number

CBNHL

National Stock Number

8010-00N071189

Product Name

EXTERIOR WOOD FINISH-BROWN OAK

Manufacturer

WATCO DENNIS CORP

Product Identification

Product ID:EXTERIOR WOOD FINISH-BROWN OAK

MSDS Date:11/01/1986

FSC:8010

NIIN:00N071189

MSDS Number: CBNHL

Responsible Party

WATCO-DENNIS CORP

19610 RANCHO WAY

RANCHO DOMINGUEZ , CA 90220

US

Emergency Phone: 213-635-2778

Info Phone: 213-635-2778

Cage: 51611

Contractor

WATCO-DENNIS CORP/SANTA MONICA, CA 90404

Cage: 51611

Ingredients

KEROSENE (PETROLEUM), HYDROCARBON; (MINERAL SPIRITS)

CAS: 64742-47-8

RTECS: OA5504000

Fraction By Weight: 42-44%

OSHA PEL500 PPM (MFR)

ACGIH TLV: 100 PPM (MFR)

DISTANNOXANE, HEXABUTYL-; (BIS (TRI-N-BUTYLTIN) OXIDE)

CAS: 56-35-9

RTECS: JN8750000

Fraction By Weight: 0.5-0.6%

OSHA PELS, 0.1 MG/M3 (SN)

ACGIH TLV: S, 0.1 MG/M3 (SN)

Hazards

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE:SKIN:MAY BE ABSORBED THROUGH SKIN AND MAY CAUSE SKIN IRRITATION. EYE:IRRITATING TO EYES, POSSIBLE REDNESS & BLURRED VISION. INHALATION:MAY CAUSE DIZZINESS, LIGHTHEADEDNESS & HEADACHES. INGESTION :MAY CAUSE GASTROINTESTINAL IRRITATION,NAUSEA & VOMITING. CHRONIC:"STUDIES OF GROUPS OF WORKERS HAVE (EFTS OF OVEREXP)
Explanation of Carcinogenicity:NOT RELEVANT.
Effects of Overexposure:HLTH HAZ:SHOWN THAT CHRONIC MIXED EXPOSURE TO SOLVENTS INCLUDING MINERAL SPIRITS CAN CAUSE PERSISTENT NEUROBEHAVIORAL SYMPTOMS SUCH AS FATIGUE, IRRITABILITY, SLEEP DISTURBANCES, AND DIFFICULTIES IN CO NCENTRATION AND MEMORY".
Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

First Aid

First Aid:SKIN:WASH AFFECTED AREAS WITH SOAP & WATER. EYE:FLUSH WITH WATER FOR AT LEAST 15 MINUTES, GET MEDICAL ATTENTION. INHAL:REMOVE INDIVIDUAL TO FRESH AIR. IF BRTHG IS DFCLT, ADMIN OXYG. IF BRTHG HAS STOPP ED, GIVE ARTF RESP & GET MED ATTN IMMED. INGEST:DO NOT INDUCE VOMITING. GIVE 4 CUPS OF WATER OR OTHER LIQUIDS. GET MED ATTN IMMEDIATELY.

Fire Fighting

Flash Point Method:TCC
Flash Point:104F,40C
Lower Limits:1.0%
Upper Limits:6.7%
Extinguishing Media:CO*2, DRY CHEMICAL, FOAM, WATER SPRAY.
Fire Fighting Procedures:USE NIOSH/MSHA APPROVED SCBA & FULL PROTECTIVE EQUIPMENT . DO NOT ENTER ANY ENCLOSED OR CONFINED SPACE WITHOUT PROTECTIVE EQUIPMENT.
Unusual Fire/Explosion Hazard:WATER SOAK OILY CLOTHS AFTER USE TO AVOID SPONTANEOUS COMBUSTION.

Accidental Release

Spill Release Procedures:ELIMINATE ALL SOURCES OF IGNITION IN VICINITY OF SPILL OR RELEASED VAPOR. CLEAN UP SPILLS AS SOON AS POSSIBLE WITH ABSORBENT CLAY, DIATOMACEOUS EARTH OR OTHER SUITABLE MATL. (IF USING CLOTHS, WATER SO AK, BEFORE DISPOSAL).
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

Handling

Handling and Storage Precautions:DO NOT STORE INSIDE THE HOME. KEEP AWAY FROM HEAT OR OPEN FLAME. KEEP OUT OF REACH OF CHILDREN. USE ONLY IN WELL-VENTILATED AREAS.
Other Precautions:KEEP CONTAINER CLOSED WHEN NOT IN USE. WATER SOAK OILY CLOTHS AFTER USE TO AVOID SPONTANEOUS COMBUSTION AND PLACE CLOTHS OUTSIDE OF BUILDINGS AND AWAY FROM COMBUSTIBLE MATERIALS.

Exposure Controls

Respiratory Protection:NIOSH/MSHA APPROVED RESPIRATOR FOR ORGANIC VAPOR OR MIST IF PPM REQUIRES.
Ventilation:ADEQUATE FOR PPM. LOCAL EXHAUST - IF REQUIRED BY PPM.
Protective Gloves:NEOPRENE GLOVES.
Eye Protection:ANSI APPRVD CHEM WORKERS GOGGLES .
Other Protective Equipment:ANSI APPRVD EMERGENCY EYE WASH & DELUGE SHOWER .
Work Hygienic Practices:AFTER USE, WASH HANDS THOROUGHLY WITH SOAP & WATER. LAUNDER CONTAMINATED CLOTHING BEFORE REUSE.
Supplemental Safety and Health
SPEC GRAV (H*20=1) (BY PRODUCT):0.88-0.95.

Chemical Properties

Boiling Pt:B.P. Text:>302F,>150C
Vapor Pres:4 @ 77F
Vapor Density:4.8
Spec Gravity:SUPDAT

Evaporation Rate & Reference:0.20 (BU AC =1)

Solubility in Water:NIL

Appearance and Odor:AMBER LIQUID.

Percent Volatiles by Volume:47-49

Stability

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS.

Stability Condition to Avoid:OPEN FLAMES, HOT SURFACES OR ANY IGNITION SOURCE.

Hazardous Decomposition Products:NORMAL AND INCOMPLETE COMBUSTION CAN PRODUCE TOXIC FUMES.

Disposal

Waste Disposal Methods:THIS PRODUCT IS HAZARDOUS TO AQUATIC LIFE AND ANIMALS. OBEY ALL RELEVANT FEDERAL, STATE AND LOCAL LAWS. DO NOT CONTAMINATE ANY LAKES, STREAMS, PONDS, UNDERGROUND WATER SUPPLY, FOOD OR FEED.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.