ACCUMIX UHS CLEANER 13825-1 TO 13829-1

MSDS Number

CBVBK

National Stock Number

7930-01-386-1014

Product Name

ACCUMIX UHS CLEANER 13825-1 TO 13829-1

Manufacturer

S C JONSON WAX

Product Identification

Product ID:ACCUMIX UHS CLEANER 13825-1 TO 13829-1

MSDS Date:04/21/1993

FSC:7930

NIIN:01-386-1014 MSDS Number: CBVBK

Responsible Party

S.C. JONSON WAX

1525 HOWE ST

RACINE, WI 53403-2237

US

Emergency Phone: 800-228-5635

Info Phone: 414-631-2777

Preparer: TERRY A. MAYERS

Cage: NO353

Contractor

SC JOHNSON AND SON INC

RACINE, WI 53403-2236

US

800-725-6737

Cage: 32204

Ingredients

WATER

CAS: 7732-18-5 RTECS: ZC0110000

Fraction By Weight: 25-40%

AMMONIUM HYDROXIDE (CERCLA)

CAS: 1336-21-6 RTECS: BQ9625000

Fraction By Weight: 2-6%

OSHA PEL25 PPM/STEL 35

ACGIH TLV: 25 PPM/STEL 35

EPA Report Quantity: 1000 LBS



DOT Report Quantity: 1000 LBS

MONOETHANOLAMINE

CAS: 141-43-5

RTECS: KJ5775000

Fraction By Weight: 20-25% OSHA PEL3 PPM/STEL 6 ACGIH TLV: 3 PPM/STEL 6

DIPROPYLENE GLYCOL METHYL ETHER (SARA 313)

CAS: 34590-94-8 RTECS: JM1575000

Fraction By Weight: 10-15%

OSHA PEL100PPM/STEL 150 SKIN ACGIH TLV: 100PPM/STEL 150 SKIN

POLYACRYLIC ACID

CAS: 9003-01-4 RTECS: AT4680000

Fraction By Weight: 3-8%

GLYCOL ETHER, MONOETHANOLAMINE 3.25 LB/GL

RTECS: 9999999VO

Fraction By Weight: NA

OSHA PELNOT RELEVANT

ACGIH TLV: NOT RELEVANT

ALKOXYLATED LINEAR ALCOHOLS

CAS: 52232-09-4

Fraction By Weight: 3-8%

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Effects of Overexposure: DIRECT CONTACT OF PRODUCT VAPOR W/EYES CAN CAUSE SEVERE IRRITATION. DIRECT CONTACT OF PRODUCT W/SKIN CAN CAUSE IRRITATION. PRODUCT MISTS/FOG MAY CAUSE SEVERE IRRITATION TO NOSE/THROAT/LUNGS. IF INHALE D/TAKEN INTERNALLY MAY CAUSE CORROSIVE DAMAGE TO MOUTH/THROAT/STOMACH.

Medical Cond Aggravated by Exposure:PERSONS W/PREEXISTING SKIN

DISORDERS MAY BE MORE SUSCEPTIBLE TO IRRITATING EFFECTS.

First Aid

First Aid:INGEST: DUE TO EXTREME PH, CONSIDER THE POSSIBILITY OF CORROSIVE DAMAGE TO MOUTH/THROAT/STOMACH IN TREATMENT. DRINK LOTS WATER/MILK. GET MED AID. FLUSH EYES W/WATER 15-20 MIN. IF IRRITATION PERSISTS G ET MEDICAL AID. WASH SKIN W/PLENTY OF WATER. IF IRRITATION PERSISTS GET MEDICAL AID. IF MISTS/FOGS/VAPORS CAUSE



DISCOMFORT MOVE TO FRESH AIR. VENTILATE AREA IF DISCOMFORT PERSISTS GET MEDICAL AID.

Fire Fighting

Flash Point:>180F,>82C Lower Limits:NOT EST. Upper Limits:NOT EST.

Extinguishing Media: FOAM, CO2, DRY CHEMICAL, WATER FOG.

Fire Fighting Procedures: NORMAL FIRE FIGHTING PROCEDURES MAY BE USED.

Unusual Fire/Explosion Hazard: NO SPECIAL HAZARDS KNOWN.

Accidental Release

Spill Release Procedures: DIKE LARGE SPILLS. ABSORB W/OIL-DRI OR SIMILAR INERT MATERIAL. SWEEP OR SCRAPE UP & CONTAINERIZE. DO NOT LET SPILLED/LEAKING MATERIAL ENTER WATERCOURSE.

Handling

Handling and Storage Precautions: WASH THOROUGHLY AFTER HANDLING. KEEP FROM FREEZING. KEEP OUT OF REACH OF CHILDREN. FOR INDUSTRIAL USE ONLY.

Other Precautions: WARNING: COROSIVE: HARMFUL OR FATAL IF SWALLOWED. UNDILUTED PRODUCT MAY CAUSE CHEMICAL BURNS. EYE IRRITANT. DO NOT GET IN EYES OR BREATH VAPORS. MIX ONLY WITH WATER.

Exposure Controls

Respiratory Protection:IF MISTS/VAPORS NOT ADEQUATELY CONTROLLED BY LOCAL VENTILATION, USE APPROPRIATE RESPIRATORY PROTECTION TO PREVENT OVEREXPOSURE

Ventilation: GENERAL ROOM VENTILATION ADEQUATE. SUBSTANTIAL AMTS OF MISTS/VAPORS CAN BE CONTROLLED W/LOCAL EXHAUST OR RESP PROTECTION Protective Gloves: NEOPRENE FOR UNDILUTED PRODUCT. Eye Protection: CHEMICAL WORKER SPLASH PROOF GOGGLES.

Work Hygienic Practices: USE GOOD PERSONAL HYGIENE PRACTICES. WASH CONTAMINATED CLOTHES/EQUIPMENT BEFORE REUSE.

Supplemental Safety and Health

NK .

Chemical Properties

Boiling Pt:B.P. Text:NOT EST.
Melt/Freeze Pt:M.P/F.P Text:NOT EST.
Vapor Pres:NOT EST.
Vapor Density:NOT EST.
Spec Gravity:1.02
pH:>12.0

Evaporation Rate & Reference: NOT EST.

Solubility in Water: COMPLETE

Appearance and Odor: BLUE GREEN LIQUID, AMMONIA ODOR

Percent Volatiles by Volume: NE

Stability

Stability Indicator/Materials to Avoid:YES STRONG ACIDS (MURIATIC), STRONG OXIDIZING MATERIALS (LIQUID CHLORINE)

Disposal

Waste Disposal Methods: WASTE FROM NORMAL USE: MAY BE SEWERED TO PUBLIC OWNED TREATMENT WORKS IN COMPLIANCE WITH APPLIC FEDERAL/STATE/LOCAL/PRETREATMENT REQ. UNDILUTED PRODUCT IS REGULATED UNDER THE RESOURCE CONSERVATION AND RECOVERY ACT AS CORROSIVE WASTE (40 CFR 261.22)

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their



https://msdsreport.com/msds/CBVBK

particular situation.