

MIL-L-3150C(AMMENDMENT 2)

MSDS Number

CCBYW

National Stock Number

9150-00-231-2356

Product Name

MIL-L-3150C(AMMENDMENT 2)

Manufacturer

VELSICOL CHEMICAL CORP

Product Identification

Product ID:MIL-L-3150C(AMMENDMENT 2)
MSDS Date:12/01/1995
FSC:9150
NIIN:00-231-2356
MSDS Number: CCBYW

Responsible Party

VELSICOL CHEMICAL CORP 10400 W HIGGINS SUITE 600 ROSEMONT , IL 60018-3713

US

Emergency Phone: 708-298-9000

Info Phone: 708-298-9000 708-298-9014(FAX)

Preparer: N.R.NETZEL

Cage: VELSI

Contractor

VELSICOL CHEMICAL CORPORATION

ROSEMONT, IL 60018

US

847-298-9000 Cage: VELSI

Ingredients

HYDROTREATED NAPTHENIC OIL

Hazards

LD50 LC50 Mixture:TLV FOR OIL MIST IS 5MG/M3 Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EYES:MISTS FROM EXCESSIVE HEATING MAY CAUSE IRRITATION.SKIN:LOW DERMAL TOXICITY.MISTS FROM EXCESSIVE HEATING MAY CAUSE IRRITATION.INGEST:LOW ORAL TOXICITY.MAY CAUSE GI TRACT IRRITATION.INHAL:MISTS FRO M EXCESSIVE HEATING MAY CAUSE RESPIRATORY IRRITATION.

RESPIRATORY IRRITATION.

Explanation of Carcinogenicity: NONE OF THE INGREDIENTS IN THIS PRODUCT IS LISTED BY NTP, IARC OR OSHA AS A CARCINOGEN.

Effects of Overexposure: INGEST: VOMITING, NAUSEA.

Medical Cond Aggravated by Exposure: NONE SPECIFIED BY MANUFACTURER.

First Aid

First Aid:SKIN:REMOVE CONTAMINATED CLOTHING; WASH WITH SOAP AND



WATER.EYES:FLUSH WITH WATER FOR 15 MINUTES.CALL PHYSICIAN IF IRRITATION DEVELOPS.INHAL:REMOVE TO FRESH AIR.GIVE OXYGEN OR ARTIFICIAL RESPIRATION IF NEEDED.INGEST: DO NOT INDUCE VOMITING.GET PROMPT QUALIFIED MEDICAL ATTENTION.NOTE TO PHYSICIAN:TREAT SYMPTOMATICALLY.

Fire Fighting

Flash Point Method:COC Flash Point:400F,204C

Extinguishing Media: WATER FOG, DRY CHEMICAL, CARBON DIOXIDE, FOAM. AVOID SPREADING BURNING LIQUID WITH WATER STREAM.

Fire Fighting Procedures: WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A FULL FACED SELF CONTAINED BREATHING APPARATUS. COOL FIRE EXPOSED CONTAINERS WITH WATER SPRAY.

Unusual Fire/Explosion Hazard: COMBUSTION OR HEAT OF FIRE MAY PRODUCE HAZARDOUS DECOMPOSITION PRODUCTS AND VAPORS.HEAT OF FIRE MAY CAUSE CONTAINERS TO BURST.

Accidental Release

Spill Release Procedures: SOAK UP WITH NON-COMBUSTIBLE INERT ADSORBANT(EG.CLAY); PLACE COLLECTED MATERIAL IN AN APPROPRIATE CONTAINER FOR DISPOSAL; CLEAN SPILL AREA TO REMOVE SLIPPERINESS.

Handling

Handling and Storage Precautions: STORE IN A COOL, DRY PLACE WITH ADEQUATE VENTILATION. KEEP AWAY FROM HEAT, OPEN FLAMES AND STRONG OXIDANTS. KEEP CONTAINERS TIGHTLY CLOSED.

Other Precautions: AVOID EYE AND SKIN CONTACT. DO NOT BREATHE VAPORS.

Exposure Controls

Respiratory Protection: NONE NORMALLY REQUIRED. NIOSH/MSHA-APPROVED RESPIRATOR OR SCBA AS APPROPIATE FOR EXPOSURE OF CONCERN.

Ventilation: USE GENERAL DILUTION VENTILATION.

Protective Gloves: IMPERMEABLE GLOVES. Eye Protection: CHEMICAL SPLASH GOGGLES

Other Protective Equipment: PROTECTIVE CLOTHING, AS NEEDED. PROVIDE A

LOCAL EYE WASH STATION AND SAFETY SHOWER.

Work Hygienic Practices: WASH HANDS. SEPERATE WORK CLOTHES FROM STREET CLOTHES.LAUNDER WORK CLOTHES BEFORE REUSE.KEEP FOOD OUT OF THE WORK

Supplemental Safety and Health

NONE

Chemical Properties

HCC:V6

Vapor Pres: 0.01@300F Vapor Density:>1 Spec Gravity: 0.93

Evaporation Rate & Reference: Solubility in Water: NEGLIGIBLE

Appearance and Odor: CLEAR LIQUID; SLIGHT ODOR.

Stability

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS. Stability Condition to Avoid: HIGH HEAT. Hazardous Decomposition Products: UNIDENTIFIED TOXIC FUMES.

Disposal

Waste Disposal Methods: CONTACT YOUR LOCAL ENVIRONMENTAL OFFICER. DISPOSE OF IN ACCORDANCE WITH ALL FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this



