

ALL-PROTECT

MSDS Number

CCCMK

National Stock Number

6850-00F050555

Product Name

ALL-PROTECT

Manufacturer

CFR CORP

Product Identification

Product ID:ALL-PROTECT

MSDS Date:07/31/1995

FSC:6850

NIIN:00F050555

MSDS Number: CCCMK

Responsible Party

CFR CORPORATION

601 LAKEVIEW POINT STE B

NEW BRIGHTON , MN 55112-5000

US

Emergency Phone: 612-631-0369/800-228-5635 EXT 163

Info Phone: 612-631-0369/800-228-5635 EXT 163

Cage: CRDEF

Contractor

CFR CORPORATION

NEW BRIGHTON, MN 55112-5000

US

612-631-0369/800-228-5635 EXT 163

Cage: CRDEF

Ingredients

ISOPARAFFINIC HYDROCARBONS (NAPHTHA PETROLEUM),

CAS: 64742-48-9

Fraction By Weight: >90%

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EYE & MUCOUS MEMBRANE IRRITATION.

SKIN: IRRITATION. PROLONGED INHALATION MAY CAUSE IRRITATION TO NOSE, THROAT & RESPIRATORY TRACT. MAY BE HARMFUL IF SWALLOWED.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:IRRITATION, LETHARGY, DIARRHEA, NAUSEA

Medical Cond Aggravated by Exposure:PRE-EXISTING EYE, SKIN, RESPIRATORY DISORDERS & HEARING CONDITIONS.

First Aid

First Aid:EYES/SKIN: FLUSH W/COOL RUNNING WATER FOR 15 MINS. INGESTION: DON'T INDUCE VOMITING. INHALATION: MOVE TO FRESH AIR. OBTAIN MEDICAL ATTENTION IN ALL CASES.

Fire Fighting

Flash Point:115F

Lower Limits:0.7

Upper Limits:7

Extinguishing Media:FOAM, CO2, DRY CHEMICAL

Fire Fighting Procedures:USE NIOSH/MSHA APPROVED SELF CONTAINED BREATHING APPARATUS IN AREAS WHERE THIS MATERIAL IS INVOLVED IN A FIRE. COOL CONTAINERS W/WATER SPRAY.

Unusual Fire/Explosion Hazard:PREVENT CONTAINER RUPTURE.

Accidental Release

Spill Release Procedures:SOAK UP PRODUCT W/AN ABSORBENT MATERIAL & PLACE IN NON-LEAKING CONTAINER FOR PROPER DISPOSAL.

Handling

Handling and Storage Precautions:KEEP FROM FREEZING, STORE IN A COOL PLACE. KEEP CLOSED WHEN STORED. KEEP FROM HEAT, FLAMES, SPARKS & OTHER IGNITION SOURCES.

Other Precautions:DON'T REUSE EMPTY CONTAINER, USE IAW/LABEL DIRECTIONS. KEEP LOCKED SUFFICIENT TO MAKE INACCESSIBLE TO CHILDREN/PERSONS UNFAMILIAR W/ITS PROPER USE. DON'T CONTAMINATE WATER, FOOD/FEED BY STORAGE/DISPOS AL.

Exposure Controls

Respiratory Protection:NONE REQUIRED WHEN USED AS SPECIFIED.

Ventilation:LOCAL EXHAUST/MECHANICAL (GENERAL)

Protective Gloves:RUBBER/NEOPRENE

Eye Protection:CHEMICAL GOGGLES

Other Protective Equipment:NONE REQUIRED WHEN USED AS SPECIFIED.

Work Hygienic Practices:REMOVE/LAUNDER CONTAMINATED CLOTHING BEFORE REUSE. WASH HANDS AFTER USING.

Supplemental Safety and Health

Chemical Properties

Boiling Pt:B.P. Text:320-350F

Vapor Pres:2

Vapor Density:>1

Spec Gravity:0.755

Evaporation Rate & Reference:(BUTYL ACETATE=1): 0.3

Solubility in Water:Appearance and Odor:CLEAR COLORLESS LIQUID

Stability

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZERS

Stability Condition to Avoid:FREEZING, HEAT, FLAMES, SPARKS & OTHER IGNITION SOURCES

Hazardous Decomposition Products:OXIDES OF CARBON & UNIDENTIFIED ORGANIC COMPOUNDS

Disposal

Waste Disposal Methods:TREAT/DISPOSE OF IN ACCORDANCE W/LOCAL, STATE & FEDERAL REGULATIONS/IAW/REGULATIONS UNDER THE RCRA.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.