

V-9355S LOW VOC **PRIMERS,THINNERS,BASEMAKERS,CLEAR,ACTIVATOR**

MSDS Number

CCCXL

National Stock Number

8010-00F050750

Product Name

V-9355S LOW VOC PRIMERS,THINNERS,BASEMAKERS,CLEAR,ACTIVATOR

Manufacturer

DUPONT E I DE NEMOURS AND CO INC AUTOMOTIVE PRODS D

Product Identification

Product ID:V-9355S LOW VOC PRIMERS,THINNERS,BASEMAKERS,CLEAR,ACTIVATOR

MSDS Date:01/01/1995

FSC:8010

NIIN:00F050750

MSDS Number: CCCXL

Responsible Party

DUPONT E I DE NEMOURS & CO INC AUTOMOTIVE PRODS D

BRANDYWINE BLDG 3332 1007 MARKET ST

WILMINGTON , DE 19898-5000

US

Emergency Phone: 800-441-3637/800-441-7515

Info Phone: 800-441-7515/800-441-3637

Preparer: T R LOUER

Cage: 23027

Contractor

TETRA MFG CORP (CAGE CANCELLED)

WESTBURY, NY 11590

US

NONE

Cage: 23027

Ingredients

ACETONE; DIMETHYL KETONE; 2-PROPANONE

CAS: 67-64-1

RTECS: AL3150000

Fraction By Weight: 58%

OSHA PEL2400 MG/CUM

ACGIH TLV: 750 PPM

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

OXO-HEXYL ACETATE *96-2*

CAS: 88230-35-7

ISOPROPANOL (ISOPROPYL ALCOHOL), 2-PROPANOL, DIMETHYL

CAS: 67-63-0

RTECS: NT8050000

OSHA PEL400 PPM

ACGIH TLV: 400 PPM

AMYL ACETATE

CAS: 628-63-7

RTECS: AJ1925000

OSHA PEL100 PPM

ACGIH TLV: 100 PPM

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

TOLUENE (IARC CARC- GROUP 3) *96-3*

CAS: 108-88-3

RTECS: XS5250000

Fraction By Weight: 13%

OSHA PEL100 PPM

ACGIH TLV: 100 PPM

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

LIGHT ALIPHATIC NAPHTHA, VM & P NAPHTHA, LACOLENE

CAS: 64742-89-8

OSHA PEL300 PPM

ACGIH TLV: 300 PPM

6.6 LBS/GAL

RTECS: 9999999VO

Hazards

Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:INHALATION: MAY CAUSE NOSE & THROAT IRRITATION. EXPOSURE TO ISOCYANATES MAY CAUSE RESPIRATORY SENSITIZATION & MAY CAUSE A DECREASE IN LUNG FUNCTION WHICH MAY BE PERMANENT. EYES: IRRITATION/BURNING. SK IN: IRRITATION & DERMATITIS. REPEATED/PROLONGED OVEREXPOSURE TO SOLVENTS MAY CAUSE PERMANENT BRAIN & CNS DAMAGE.
Explanation of Carcinogenicity:NONE
Effects of Overexposure:GI DISTRESS, IRRITATION, EYE WATERING, HEADACHES, NAUSEA, DIZZINESS, LOSS OF COORDINATION, BURNING, DISCOMFORT.

First Aid

First Aid:INHALATION: REMOVE TO FRESH AIR. EYES: FLUSH W/PLENTY OF

WATER FOR 15 MINS. SKIN: WASH W/SOAP & WATER. OBTAIN MEDICAL ATTENTION IN ALL CASES.

Fire Fighting

Flash Point Method:CC
Flash Point:Lower Limits:0.2
Upper Limits:36.5
Extinguishing Media:WATER SPRAY, FOAM, CO2, DRY CHEMICAL.
Fire Fighting Procedures:USE FULL PROTECTIVE EQUIPMENT & SCBA. WATER FROM FOG NOZZLES MAY BE USED TO COOL CLOSED CONTAINERS.
Unusual Fire/Explosion Hazard:WHEN HEATED ABOVE THE FLASHPOINT, EMITS FLAMMABLE VAPORS, WHEN MIXED W/AIR CAN BURN/BE EXPLOSIVE. FINE MISTS/SPRAYS MAY BE FLAMMABLE AT TEMPS < THE FLASHPOINT.

Accidental Release

Spill Release Procedures:DON'T BREATHE VAPORS. DON'T GET IN EYES/ON SKIN. WEAR A POSITIVE PRESSURE SUPPLIED AIR VAPOR/PARTICULATE RESPIRATOR(NIOSH/MSHA TC-19C)& PROTECTIVE MATERIAL. REMOVE SOURCES OF IGNITION. ABSORB W/INERT MATERIAL. VENTILATE AREA. (SEE SUPP)
Neutralizing Agent:DECONTAMINATION SOLUTIONS: 20% SURFACTANT (TERGITOL TMN 10), 80% WATER.

Handling

Handling and Storage Precautions:KEEP AWAY FROM HEAT, SPARKS & FLAME. CLOSE CONTAINER AFTER EACH USE. GROUND CONTAINERS WHEN POURING. DON'T STORE >120F. OBSERVE LABEL PRECAUTIONS.
Other Precautions:DON'T SAND, FLAME CUT, BRAZE/WELD DRY COATING W/O A NIOSH/MSHA APPROVED RESPIRATOR/APPROPRIATE VENTILATION. DON'T BREATHE VAPORS. DON'T PERMIT ANYONE W/O PROTECTION IN THE PAINTING AREA.

Exposure Controls

Respiratory Protection:WEAR A POSITIVE PRESSURE SUPPLIED AIR RESPIRATOR(NIOSH/MSHA TC-19C)during application. INDIVIDUALS W/A HISTORY OF LUNG/BREATHING PROBLEMS/REACTION TO ISOCYANATES SHOULDN'T USE/BE EXPOSED TO PRODUCT.
Ventilation:SUFFICIENT IN VOLUME & PATTERN TO KEEP CONTAMINANTS BELOW APPLICABLE OSHA LIMITS.
Protective Gloves:NEOPRENE
Eye Protection:SPLASH GUARDS/SIDE SHIELDS
Other Protective Equipment:COVERALLS.
Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING & BEFORE EATING/SMOKING.
Supplemental Safety and Health
VOLATILE VOLUME: 6.4-100%. SPILLS: POUR LIQUID DECONTAMINATE SOLUTION OVER THE AREA & ALLOW TO SIT 10 MINS, MINIMUM. THIS PROCEDURE CAN GENERATE PRESSURE. DON'T CLOSE CONTAINER. AFTER 48 HOURS, CLOSE CONTAINER & DISPOSE OF MATERIAL.

Chemical Properties

Boiling Pt:B.P. Text:129-1652F
Vapor Density:>1
Evaporation Rate & Reference:LESS THAN ETHER
Solubility in Water:MISCIBLE
Percent Volatiles by Volume:(SUPP)

Stability

Stability Indicator/Materials to Avoid:YES
NONE REASONABLY FORSEEABLE.
Stability Condition to Avoid:HEAT, SPARKS, FLAME, TEMPS >120F.
Hazardous Decomposition Products:CO, CO2, SMOKE.

Disposal

Waste Disposal Methods:INCINERATE/DISPOSE OF IAW/FEDERAL, STATE & LOCAL REGULATIONS. DON'T ALLOW MATERIAL TO CONTAMINATE GROUND WATER SYSTEMS. DON'T INCINERATE IN CLOSED CONTAINERS. FLAMMABLE LIQUID UN1263.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.