

AZROCK HEAVY DUTY FLOOR FINISH STRIPPER

MSDS Number

CCFFX

National Stock Number

7930-00F051440

Product Name

AZROCK HEAVY DUTY FLOOR FINISH STRIPPER

Manufacturer

AZROCK INDUSTRIES INC

Product Identification

Product ID:AZROCK HEAVY DUTY FLOOR FINISH STRIPPER

MSDS Date:08/10/1992

FSC:7930

NIIN:00F051440

MSDS Number: CCFFX

Responsible Party

AZROCK INDUSTRIES INC

10999 IH 10 W

SAN ANTONIO , TX 78269-6060

US

Emergency Phone: 210-558-6400

Info Phone: 210-558-6400

Cage: 22112

Contractor

AZROCK INDUSTRIES INC

SAN ANTONIO, TX 78269-6060

US

800-228-5635; 512-558-6400

Cage: 22112

Ingredients

TETRASODIUM SALT OF ETHYLENEDIAMINETETRAACETIC ACID, SODIUM

CAS: 64-02-8

RTECS: AH5075000

Fraction By Weight: 1-5%

2-AMINOETHANOL, ETHANOLAMINE, MONOETHANOLAMINE

CAS: 141-43-5

RTECS: KJ5775000

Fraction By Weight: 2-6%

OSHA PEL3 PPM

ACGIH TLV: 7.5 MG/CUM

DIPROPYLENE GLYCOL METHYL ETHER, DOWANOL DPM, DIPROPYLENE

CAS: 34590-94-8
RTECS: JM1575000
Fraction By Weight: 2-6%
OSHA PEL100 PPM SKIN
ACGIH TLV: 100 PPM

WATER
CAS: 7732-18-5
RTECS: ZC0110000

MATERIAL 90.4 G/L
RTECS: 9999999VO

Hazards

Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EYES: CAN CAUSE SEVERE IRRITATION & DAMAGE. SKIN: MAY CAUSE IRRITATION.
Explanation of Carcinogenicity:NONE
Effects of Overexposure:IRRITATION, REDNESS, DRYNESS.

First Aid

First Aid:EYES: FLUSH W/WATER FOR 15 MINS. SKIN: REMOVE W/SOAP & WATER.
INHALATION: REMOVE TO FRESH AIR & VENTILATE AREA. INGESTION: DRINK
LARGE AMOUNTS OF WATER/MILK. OBTAIN MEDICAL ATTENTION IN ALL CASES.

Fire Fighting

Extinguishing Media:CO2, DRY POWDER, WATER.
Fire Fighting Procedures:USUAL FIRE FIGHTING PROCEDURES MAY BE USED.
Unusual Fire/Explosion Hazard:NONE

Accidental Release

Spill Release Procedures:ABSORB LARGE QUANTITIES W/OIL-DRI/SIMILAR
INERT MATERIAL. SMALL QUANTITIES MAY BE FLUSHED TO THE SEWER
W/LARGE QUANTITIES OF WATER. DILUTE TO A PH OF LESS THAN 10.

Handling

Handling and Storage Precautions:KEEP FROM FREEZING.
Other Precautions:KEEP OUT OF REACH OF CHILDREN.

Exposure Controls

Ventilation:NORMAL ROOM IS ADEQUATE.
Protective Gloves:RUBBER/POLY VINYL CHLORIDE/IMPERVIOUS
Eye Protection:CHEMICAL WORKERS SPLASH PROOF GOGGLES
Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING.
Supplemental Safety and Health

Chemical Properties

Boiling Pt:B.P. Text:>200F
Vapor Pres:20
Vapor Density:AS WATER
Spec Gravity:1.04
Solubility in Water:INFINITE
Appearance and Odor:LIGHT COLORED LIQUID W/A FAINT FRAGRANCE

Stability

Stability Indicator/Materials to Avoid:YES
STRONG ACIDS, MURIATIC ACID, STRONG OXIDIZING AGENTS, LIQUID CHLORINE.
Stability Condition to Avoid:FREEZING.

Hazardous Decomposition Products:OXIDES OF CARBON & NITROGEN.

Disposal

Waste Disposal Methods:DISPOSE OF AT A PERMITTED WASTE FACILITY
IAW/FEDERAL, STATE & LOCAL REGULATIONS. CORROSIVE LIQUID UN1760.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.