

## **TY21516, TY6497 C P GREEN TOUCHUP PAINT (AEROSOL)**

### **MSDS Number**

CDBXQ

### **National Stock Number**

8010-00F052682

### **Product Name**

TY21516, TY6497 C P GREEN TOUCHUP PAINT (AEROSOL)

### **Manufacturer**

DEERE AND CO

### **Product Identification**

Product ID:TY21516, TY6497 C P GREEN TOUCHUP PAINT (AEROSOL)

MSDS Date:02/15/1989

FSC:8010

NIIN:00F052682

MSDS Number: CDBXQ

### **Responsible Party**

DEERE & CO

JOHN DEERE RD

MOLINE , IL 61265

US

Emergency Phone: 800-822-8262/309-765-8000

Info Phone: 800-822-8262/309-765-8000

Preparer: T M SNYDER

Cage: 4X159

### **Contractor**

DEERE AND CO

MOLINE, IL 61265

US

309-765-8000

Cage: 75160

### **Ingredients**

LIGHT ALIPHATIC NAPHTHA, VM & P NAPHTHA, LACOLENE \* 96-4 \*

CAS: 64742-89-8

Fraction By Weight:

OSHA PEL300 PPM

ACGIH TLV: 300 PPM

STODDARD SOLVENT (PETROLEUM DISTILLATE), MINERAL SPIRITS

CAS: 8052-41-3

RTECS: WJ8925000

Fraction By Weight:

OSHA PEL100 PPM

ACGIH TLV: 100 PPM

XYLENE, DIMETHYLBENZENE, XYLOL (IARC - GROUP 3) \*96-4\*

CAS: 1330-20-7

RTECS: ZE2100000

Fraction By Weight:

OSHA PEL100 PPM

ACGIH TLV: 100 PPM, SKIN

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

SOLVENT NAPHTHA, PETROLEUM, LIGHT AROMATIC, HIGH FLASH

CAS: 64742-95-6

RTECS: WF3400000

Fraction By Weight:

OSHA PEL25 PPM

ACGIH TLV: 25 PPM

BUTANOL, N-BUTYL ALCOHOL, PROPYL CARBINOL, BUTYL ALCOHOL

CAS: 71-36-3

RTECS: EO1400000

Fraction By Weight:

OSHA PEL50 PPM

ACGIH TLV: 50 PPM

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

ETHANOL (ETHYL ALCOHOL), TECSOL, ALCOHOL, SYNASOL \*96-4\*

CAS: 64-17-5

RTECS: KQ6300000

Fraction By Weight:

OSHA PEL1000 PPM

ACGIH TLV: 1000 PPM

C.I. PIGMENT YELLOW 97 \*96-4\*

CAS: 12225-18-2

Fraction By Weight:

TITANIUM DIOXIDE, TITANIUM OXIDE (SUSPECTED ANIMAL

CAS: 13463-67-7

RTECS: XR2275000

Fraction By Weight:

OSHA PEL15 MG/CUM

ACGIH TLV: 10 MG/CUM (DUST)

PHTHALOCYANINE GREEN PIGMENT

CAS: 14302-13-7

RTECS: GL7500000

Fraction By Weight:

OSHA PEL1 PPM

ACGIH TLV: 1 PPM

COMPLEX INORGANIC BLUE PIGMENT, FERRIC FERROCYANIDE PIGMENT

CAS: 14038-43-8

RTECS: LJ8200000

Fraction By Weight:

OSHA PEL15 MG/CUM

ACGIH TLV: 10 MG/CUM

PROPANE (DIMETHYLMETHANE) \*96-4\*

CAS: 74-98-6

RTECS: TX2275000

OSHA PEL1000 PPM

ACGIH TLV: SIMPLE ASPHYXIAN

ISOBUTANE, 2-METHYLPROPANE

CAS: 75-28-5

RTECS: TZ4300000

OSHA PEL1000 MG/CUM

ACGIH TLV: 1000 PPM

ACETONE; DIMETHYL KETONE; 2-PROPANONE \*96-4\*

CAS: 67-64-1

RTECS: AL3150000

Fraction By Weight:

OSHA PEL750 PPM

ACGIH TLV: 750 PPM

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

V M & P NAPHTHA, LIGROINE, MINERAL SPIRITS \*96-4\*

CAS: 8032-32-4

RTECS: OI6180000

Fraction By Weight:

OSHA PEL300 PPM

ACGIH TLV: 300 PPM

## Hazards

Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:INHALATION: ANESTHETIC, IRRITATION OF THE RESPIRATORY TRACT/CNS DEPRESSION. SKIN/EYES: IRRITATION. PROLONGED/REPEATED OVEREXPOSURE TO SOLVENTS MAY CAUSE CNS, KIDNEY & LIVER DAMAGE.  
Explanation of Carcinogenicity:NONE  
Effects of Overexposure:IRRITATION, HEADACHE, DIZZINESS, STAGGERING GAIT, CONFUSION, UNCONSCIOUSNESS, COMA.  
Medical Cond Aggravated by Exposure:PRE-EXISTING SKIN, EYE, RESPIRATORY CONDITIONS & CNS DISORDERS.

## First Aid

First Aid:INHALATION: REMOVE TO FRESH AIR. RESTORE BREATHING, KEEP WARM & QUIET. EYES: FLUSH W/WATER FOR 15 MINS. SKIN: WASH W/SOAP & WATER ONLY. INGESTION: DON'T INDUCE VOMITING. OBTAIN MEDICAL ATTENTION IN ALL CASES.

## Fire Fighting

Flash Point:20F (PROPELLANT)  
Lower Limits:0.9  
Upper Limits:2.6  
Extinguishing Media:CO2, DRY CHEMICAL, FOAM.  
Fire Fighting Procedures:WATER MAY BE INEFFECTIVE. WATER MAY BE USED TO KEEP FIRE EXPOSED CHEMICALS COOL.  
Unusual Fire/Explosion Hazard:CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT. DON'T APPLY TO HOT SURFACES.

## Accidental Release

Spill Release Procedures:REMOVE IGNITION SOURCES; AVOID BREATHING VAPORS, VENTILATE AREA; CLEAN UP W/INERT ABSORBENT & NON-SPARKING TOOLS.

## Handling

Handling and Storage Precautions:DON'T STORE >120F. DON'T EXPOSE TO DIRECT SUNLIGHT/OTHER HEAT SOURCE. DON'T PUNCTURE/INCINERATE. DON'T FLAME CUT, BRAZE/WELD PARTS COATED W/PAINT.  
Other Precautions:CONTAINERS SHOULD BE GROUNDED WHEN POURING. DON'T TAKE INTERNALLY. KEEP AWAY FROM CHILDREN. KEEP CONTAINERS TIGHTLY CLOSED. ISOLATE FROM HEAT, ELECTRICAL EQUIPMENT, SPARKS & OPEN FLAME.

## Exposure Controls

Respiratory Protection:USE NIOSH APPROVED RESPIRATOR.  
Ventilation:LOCAL EXHAUST TO KEEP TLV/PEL BELOW ACCEPTABLE LEVELS.  
Protective Gloves:RECOMMENDED  
Eye Protection:RECOMMENDED  
Supplemental Safety and Health  
BOILING POINT: 0F FOR PROPELLANT.

## Chemical Properties

Boiling Pt:B.P. Text:(SEE SUPP)  
Vapor Density:>1  
Evaporation Rate & Reference:(ETHER = 1): Appearance and Odor:GREEN SOLVENT  
Percent Volatiles by Volume:82

## Stability

Stability Indicator/Materials to Avoid:YES  
STRONG OXIDIZING AGENTS.  
Stability Condition to Avoid:HEAT, SPARKS, OPEN FLAME, HOT SURFACES/OTHER SOURCES OF IGNITION.  
Hazardous Decomposition Products:CO2, CO, OTHER UNIDENTIFIED ORGANIC COMPOUNDS.

## Disposal

Waste Disposal Methods:DISPOSE OF IAW/FEDERAL, STATE & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.