

M 33-34 HYDRAULIC JACK OIL

MSDS Number

CDCZD

National Stock Number

9150-00F041885

Product Name

M 33-34 HYDRAULIC JACK OIL

Manufacturer

RADIATOR SPECIALTY CO

Product Identification

Product ID:M 33-34 HYDRAULIC JACK OIL MSDS Date: 08/01/1994 FSC:9150 NIIN:00F041885 MSDS Number: CDCZD

Responsible Party

RADIATOR SPECIALTY CO

1900 WILKINSON BLVD

CHARLOTTE , NC 28208-4689

US

Emergency Phone: 800-438-6947/704-377-6555

Info Phone: 704-377-6555/800-438-6947

Preparer: I LIEBMAN

Cage: 77628 **Contractor**

RADIATOR SPECIALTY COMPANY

34689

US

CHARLOTTE, NC 28208

704-377-6555/303-623-5716

Cage: 77628

Ingredients

MINERAL OIL; PETROLATUM-LIQUID; WHITE MINERAL OIL, PARAFFIN

CAS: 8012-95-1 RTECS: PY8030000

Fraction By Weight: >90%

OSHA PEL5 MG/CUM ACGIH TLV: 5 MG/CUM

Hazards

Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic: EYES: MILD IRRITANT. SKIN: SLIGHTLY

IRRITATING ON PROLONGED EXPOSURE. Explanation of Carcinogenicity: NONE Effects of Overexposure: IRRITATION



First Aid

First Aid:EYES: FLUSH W/WATER FOR 15 MINS. SKIN: WASH W/SOAP & WATER. INHALATION: MOVE TO FRESH AIR. INGESTION: DON'T INDUCE VOMITING. OBTAIN MEDICAL ATTENTION IN ALL CASES.

Fire Fighting

Flash Point Method:COC Flash Point:390F

Extinguishing Media: FOAM, CO2, DRY CHEMICAL

Fire Fighting Procedures: WEAR SELF CONTAINED, POSITIVE PRESSURE

BREATHING APPARATUS & PROTECTIVE CLOTHES.

Accidental Release

Spill Release Procedures: WIPE UP W/RAGS. REMOVE IGNITION SOURCES, VENTILATE AREA. CONFINE LEAK & TRANSFER TO WASTE DRUM.

Handling

Handling and Storage Precautions:STORE IN COOL PLACE AWAY FROM OXIDIZING AGENTS. KEEP AWAY FROM CHILDREN.
Other Precautions:WEARING CONTACT LENSES IS INADVISABLE.

Exposure Controls

Ventilation: USE W/ADEQUATE GENERAL VENTILATION.

Protective Gloves: RUBBER Eye Protection: GOGGLES

Work Hygienic Practices: REMOVE/LAUNDER CONTAMINATED CLOTHING BEFORE

REUSE.

Supplemental Safety and Health

Chemical Properties

Boiling Pt:B.P. Text:690F

Spec Gravity:0.86

pH:7

Solubility in Water:INSOLUBLE

Appearance and Odor:LIGHT AMBER LIQUID W/PETROLEUM ODOR

Percent Volatiles by Volume:

Stability

Stability Indicator/Materials to Avoid:YES OXIDIZING AGENTS Stability Condition to Avoid:IGNITION SOURCES

 $\label{thm:local_products} \mbox{Hazardous Decomposition Products:BY FIRE: NORMAL PRODUCTS OF}$

COMBUSTION, CO2, CO, SMOKE

Disposal

Waste Disposal Methods: DISPOSE OF IN ACCORDANCE W/LOCAL, STATE & FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.