

M P CERAMIC TILE ADHESIVE

MSDS Number

CDQXZ

National Stock Number

8040-00F053030

Product Name

M P CERAMIC TILE ADHESIVE

Manufacturer

DAP INC

Product Identification

Product ID:M P CERAMIC TILE ADHESIVE

MSDS Date:05/25/1994

FSC:8040

NIIN:00F053030

MSDS Number: CDQXZ

Responsible Party

DAP INC

5300 HUBERVILLE RD

DAYTON , OH 45401-0277

US

Emergency Phone: 513-667-4461/800-543-3840

Info Phone: 513-667-4461/800-543-3840

Cage: 90300

Contractor

DAP INC.

277

DAYTON, OH 45401-0277

US

513-253-7154/800-543-3840

Cage: 90300

Ingredients

HYDROCARBON RESIN

WATER

CAS: 7732-18-5

RTECS: ZC0110000

CLAY (KAOLIN), ALUMINUM SILICATE *96-4*

CAS: 1332-58-7

RTECS: GF1670500

ACGIH TLV: 10 MG/CUM TOTAL DUST

110-120 GM/L LESS WATER LESS

RTECS: 9999999VO

MEDIUM ALIPHATIC NAPHTHA (AROMATIC 100), PARAFFIN-NAPTHANES

CAS: 64742-88-7

Fraction By Weight: 1-3%

OSHA PEL500 PPM

ACGIH TLV: 100 PPM

ETHYLENE GLYCOL, GLYCOL *96-4*

CAS: 107-21-1

RTECS: KW2975000

Fraction By Weight: 1-3%

OSHA PEL50 PPM

ACGIH TLV: C 127 MG/CUM

EPA Report Quantity: 1 LB

DOT Report Quantity: 1 LB

STYRENE BUTADIENE RUBBER COPOLYMER LATEX

Hazards

Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:MAY IRRITATE EYES/SKIN/NOSE &
RESPIRATORY TRACT. HARMFUL IF INHALED. FATAL IF SWALLOWED.
INGESTION: ETHYLENE GLYCOL-CAUSES GI IRRITATION; DEATH.
OVEREXPOSURE MAY CAUSE RESPIRATORY/CARDIAC FAILURE; KID NEY & LIVER
DAMAGE. REPEATED/PROLONGED OVEREXPOSURE TO SOLVENTS MAY CAUSE
PERMANENT BRAIN & NERVOUS SYSTEM DAMAGE.
Explanation of Carcinogenicity:NONE
Effects of Overexposure:IRRITATION, NAUSEA, VOMITING, DIARRHEA

First Aid

First Aid:EYES: FLOOD W/LARGE QUANTITIES OF WATER FOR 15 MINS. SKIN:
WASH W/SOAP & WATER. INHALATION: REMOVE TO FRESH AIR. INGESTION:
DON'T INDUCE VOMITING. OBTAIN MEDICAL ATTENTION IN ALL CASES.

Fire Fighting

Flash Point:>200F
Extinguishing Media:FOAM, CO2, DRY CHEMICAL
Fire Fighting Procedures:USE WATER SPRAY TO COOL EXPOSED SURFACES.

Accidental Release

Spill Release Procedures:USE ABSORBENT MATERIAL/SCRAPE UP DRIED
MATERIAL & PLACE INTO CONTAINERS.

Handling

Handling and Storage Precautions:STORE AWAY FROM CAUSTICS & OXIDIZERS.
KEEP CONTAINERS TIGHTLY CLOSED WHEN NOT IN USE & FROM EXCESSIVE
HEAT & FREEZING.
Other Precautions:KEEP OUT OF REACH OF CHILDREN. VAPORS ARE >AIR & WILL
COLLECT IN LOW AREAS; BASEMENTS, SUMPS. CHECK ALL LOW AREAS BEFORE
ENTERING.

Exposure Controls

Respiratory Protection:NOT REQUIRED UNDER NORMAL USAGE & W/ADEQUATE VENTILATION.
Ventilation:SUFFICIENT MECHANICAL (LOCAL/GENERAL EXHAUST) TO MAINTAIN EXPOSURE Protective Gloves:RECOMMENDED
Eye Protection:SAFETY GLASSES W/SIDE SHIELDS
Other Protective Equipment:NOT REQUIRED.
Work Hygienic Practices:REMOVE/LAUNDER CONTAMINATED CLOTHING BEFORE REUSE.
Supplemental Safety and Health

Chemical Properties

Boiling Pt:B.P. Text:212F
Vapor Pres:17.5
Vapor Density:>1
Spec Gravity:1.53
Evaporation Rate & Reference:(N-BUTYL ACETATE=1): Appearance and Odor:SMOOTH BUFF COLORED PASTE W/A MILD SOLVENT ODOR
Percent Volatiles by Volume:45-50

Stability

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZERS & CAUSTICS
Stability Condition to Avoid:EXCESSIVE HEAT, FREEZING
Hazardous Decomposition Products:NORMAL COMBUSTION PRODUCTS; CARBON OXIDES, NITROGEN OXIDES

Disposal

Waste Disposal Methods:LIQUIDS CAN'T BE DISPOSED OF IN A LANDFILL.
DON'T REUSE EMPTY CONTAINERS. DISPOSE OF IN ACCORDANCE W/LOCAL, STATE & FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.