

H S GLOSS GRAY BAC-707

MSDS Number

CDRGC

National Stock Number

8010-00F053379

Product Name

H S GLOSS GRAY BAC-707

Manufacturer

DEXTER CORP PACKAGING PRODUCTS DIV

Product Identification

Product ID:H S GLOSS GRAY BAC-707

MSDS Date:01/09/1996

FSC:8010

NIIN:00F053379

Kit Part:Y

MSDS Number: CDRGC

Responsible Party

DEXTER CORP PACKAGING PRODUCTS DIV

1 EAST WATER ST

WAUKEGAN , IL 60085-5614

US

Emergency Phone: 847-623-4200

Info Phone: 847-623-4200

Cage: 91342

Contractor

DEXTER CORP THE PACKAGING PRODUCTS DIV

WAUKEGAN, IL 60085-5614

US

847-623-4200

Cage: 91342

Ingredients

ARSENIC, ARSENICALS (HUMAN & ANIMAL CARCINOGEN BY IARC,

CAS: 7440-38-2

RTECS: CG0525000

Fraction By Weight: 0.0002%

OSHA PEL0.5 MG/CUM

ACGIH TLV: 0.2 MG/CUM

EPA Report Quantity: 1 LB

DOT Report Quantity: 1 LB

LEAD (IARC CARC GROUP 2B) *96-4*

CAS: 7439-92-1

RTECS: OF7525000

Fraction By Weight: 0.00007%

ACGIH TLV: 0.15 MG/CUM

EPA Report Quantity: 1 LB

DOT Report Quantity: 1 LB

CRYSTALLINE-QUARTZ SILICA, SILICA DUST (SUSPECTED HUMAN

CAS: 14808-60-7

RTECS: VV7330000

Fraction By Weight:

OSHA PEL10 MG/CUM %RESP SIO2

ACGIH TLV: 0.1 MG/CUM RESP DUST

2-HEPTANONE, METHYL N-AMYL KETONE *96-4*

CAS: 110-43-0

RTECS: MJ5075000

Fraction By Weight:

OSHA PEL465 MG/CUM

ACGIH TLV: 233 MG/CUM

PROPYLENE GLYCOL METHYL ETHER (1-METHOXY-2-PROPANOL)

CAS: 107-98-2

RTECS: UB7700000

Fraction By Weight:

ACGIH TLV: 100 PPM

XYLENE, DIMETHYLBENZENE, XYLOL (IARC - GROUP 3) *96-4*

CAS: 1330-20-7

RTECS: ZE2100000

Fraction By Weight:

OSHA PEL100 PPM

ACGIH TLV: 100 PPM, SKIN

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

1,2,4-TRIMETHYLBENZENE *96-4*

CAS: 95-63-6

RTECS: DC3325000

Fraction By Weight:

ACGIH TLV: 25 PPM

METHYL ETHYL KETONE, 2-BUTANONE *97-1*

CAS: 78-93-3

RTECS: EL6475000

Fraction By Weight:

OSHA PEL200 PPM

ACGIH TLV: 590 MG/CUM

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

BENZENE (SUSPECTED HUMAN CARC BY ACGIH, IARC, ANIMAL

CAS: 71-43-2

RTECS: CY1400000

Fraction By Weight: 0.00059%

ACGIH TLV: 0.3 MG/CUM (A2) IC

EPA Report Quantity: 10 LBS

DOT Report Quantity: 10 LBS

XYLENE, DIMETHYLBENZENE, XYLOL (IARC - GROUP 3) *96-4*

CAS: 1330-20-7

RTECS: ZE2100000

OSHA PEL100 PPM

ACGIH TLV: 100 PPM, SKIN

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES
Health Hazards Acute and Chronic:INHALATION: IRRITATION TO THE
RESPIRATORY TRACT. SKIN/EYES: IRRITATION. PRODUCT MAY BE ABSORBED
THRU THE EYES, SKIN, INHALATION & INGESTION.
Explanation of Carcinogenicity:SEE INGREDIENTS.
Effects of Overexposure:IRRITATION, HEADACHE, DIZZINESS, DROWSINESS.

First Aid

First Aid:EYES: FLUSH W/WATER FOR 15 MINS. SKIN: WASH W/SOAP & WATER.
INGESTION: DRINK WATER. OBTAIN MEDICAL ATTENTION IN ALL CASES.

Fire Fighting

Flash Point Method:SCC
Flash Point:23F
Lower Limits:1.1
Extinguishing Media:WATER FOG, FOAM, DRY CHEMICAL/CO2.

Accidental Release

Spill Release Procedures:REMOVE IGNITION SOURCES. VENTILATE AREA.
REMOVE W/INERT ABSORBANT & NON-SPARKING TOOLS.

Handling

Handling and Storage Precautions:CONTAINERS SHOULD BE GROUNDED WHEN
POURING. AVOID FREE FALL OF LIQUID IN EXCESS OF A FEW INCHES. THE
DRUM SHOULD BE INDUSTRIALLY CLEANED.
Other Precautions:MAKE SURE DRUM IS COMPLETELY EMPTY BEFORE ATTEMPTING
TO WELD/BRAZE. DON'T FLAME CUT, BRAZE/WELD W/O NIOSH APPROVED
RESPIRATOR/APPROPRIATE VENTILATION. AVOID BREATHING VAPORS. DON'T

TAKE INTERNALLY.

Exposure Controls

Respiratory Protection:WHERE GENERAL DILUTION/LOCAL EXHAUST VENTILATION FAILS TO ADEQUATELY DILUTE THE TWA/PEL, USE NIOSH/MSHA APPROVED AIR LINE TYPE RESPIRATORS/HOODS FOR ENCLOSED & CONFINED AREAS. AIR PURIFYING RESPIRATOR S MAY BE USED FOR OTHER AREAS.

Ventilation:GENERAL DILUTION/LOCAL EXHAUST VENTILATION.

Protective Gloves:CHEMICAL RESISTANT

Eye Protection:REQUIRED

Work Hygienic Practices:REMOVE/LAUNDER CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health

Chemical Properties

Boiling Pt:B.P. Text:168-999F

Vapor Density:> 1

VOC Grams/Liter:3.2

Stability

Stability Indicator/Materials to Avoid:YES

Hazardous Decomposition Products:WELDING: CO, OXIDES OF NITROGEN.

Disposal

Waste Disposal Methods:DISPOSE OF IAW/FEDERAL, STATE & LOCAL REGULATIONS. PAINT, UN1263.

Other Information

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.