

## **U-24 LATEX**

### **MSDS Number**

CDVLP

### **National Stock Number**

5610-00-618-0258

### **Product Name**

U-24 LATEX

### **Manufacturer**

WESTPAC PRODUCTS CO INC

### **Product Identification**

Product ID:U-24 LATEX  
MSDS Date:04/18/1997  
FSC:5610  
NIIN:00-618-0258  
Kit Part:Y  
MSDS Number: CDVLP

### **Responsible Party**

WESTPAC PRODUCTS CO INC  
106 HEGENBERGER LOOP  
OAKLAND , CA 94621-1326  
US  
Cage: 4Z694

### **Contractor**

WESTPAC PRODUCTS CO INC  
OAKLAND, CA 94621-1326  
US  
Cage: 4Z694

### **Ingredients**

ACRYLIC POLYMER  
CAS: 25068-63-7  
Fraction By Weight: 36.0%

DEFOAMER  
Fraction By Weight: 0.5%

WATER  
CAS: 7732-18-5  
RTECS: ZC0110000  
Fraction By Weight: 63.06%

FORMALDEHYDE (SARA 302/313) (CERCLA)  
CAS: 50-00-0  
RTECS: LP8925000

Fraction By Weight: 0.05%

EPA Report Quantity: 100 LBS

DOT Report Quantity: 100 LBS

## Hazards

LD50 LC50 Mixture: ORAL RAT LD50 >50G/KG

Routes of Entry: Inhalation: YES Skin: YES Ingestion: NO

Reports of Carcinogenicity: NTP: NO IARC: NO OSHA: NO

Health Hazards Acute and Chronic: INHAL: HEADACHE, NAUSEA, NOSE/THROAT/LUNG IRRITATION. SKIN: IRRITATION. EYE: IRRITATION.

## First Aid

First Aid: INHAL: MOVE TO FRESH AIR. EYE: FLUSH W/LARGE AMOUNTS WATER FOR >15 MINUTES, CALL DR. SKIN: WASH W/SOAP & WATER

## Fire Fighting

Flash Point: NONCOMBUSTIBLE

Lower Limits: NA

Upper Limits: NA

Extinguishing Media: NA

Fire Fighting Procedures: NA

Unusual Fire/Explosion Hazard: MAY SPLATTER >212F POLYMER FILMS WILL BURN.

## Accidental Release

Spill Release Procedures: EVAC AREA, FLOOR MAY BE SLIPPERY. DIKE/CONTAIN W/INERT MATERIAL, TRANSFER TO CONTAINER FOR RECOVERY/DISPOSAL, KEEP AWAY FROM BODIES OF WATER.

Neutralizing Agent: FERRIC CHLORIDE & LIME.

## Handling

Handling and Storage Precautions: STORE BETWEEN 34 & 140F, DONT FREEZE, MAINTAIN ADEQUATE VENTWHERE PRODUCT HEATED/CURED.

## Exposure Controls

Respiratory Protection: NONE REQUIRED IF GOOD VENT. IF NOT, USE MSHA/NIOSH APPROVED EQUIPMENT.

Ventilation: LOCAL EXHAUST AT POINT OF CONTAMINATION, MECHANICAL VENT AT POINT OF CONTAMINATION RELEASE.

Protective Gloves: IMPERVIOUS.

Eye Protection: CHEMICAL SPLASH GOGGLES.

Other Protective Equipment: ADEQUATE SKIN PROTECTION.

Supplemental Safety and Health  
NK

## Chemical Properties

Boiling Pt: B.P. Text: 212F, 100C

Vapor Pres: 17 @ 68F

Vapor Density: Spec Gravity: 1-1.2

pH: 9.5-10

Viscosity: 100CPS

Evaporation Rate & Reference: Solubility in Water: DILUTABLE

Appearance and Odor: MILKY WHITE LIQUID, MILD ACRYLIC ODOR

Percent Volatiles by Volume: 52-54

## Stability

Stability Indicator/Materials to Avoid: YES

NK

Stability Condition to Avoid: TEMPS >350F

## Disposal

Waste Disposal Methods: FLUSH CLEAR SUPERNANT LIQUID TO CHEM SEWER. LANDFILL/INCINERATE SOLIDS ACCORDING TO LOCAL/STATE/FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.