

## **U-1003 BLACK**

### **MSDS Number**

CFFPL

### **National Stock Number**

8010-00F053615

### **Product Name**

U-1003 BLACK

### **Manufacturer**

STERLING LACQUER MFG CO

### **Product Identification**

Product ID:U-1003 BLACK

MSDS Date:02/16/1996

FSC:8010

NIIN:00F053615

MSDS Number: CFFPL

### **Responsible Party**

STERLING LACQUER MFG CO

3150 BRANNON AVE

ST LOUIS , MO 63139-1422

US

Emergency Phone: 314-776-4450

Info Phone: 314-776-4450

Preparer: P D MOORE

Cage: 60003

### **Contractor**

STERLING LACQUER MFG CO

ST. LOUIS, MO 63139-1422

US

314-776-4450

Cage: 60003

### **Ingredients**

PROPYLENEGLYCOL MONOMETHYL ETHER ACETATE,

CAS: 108-65-6

RTECS: AI8925000

Fraction By Weight: 25-30%

XYLENE, DIMETHYLBENZENE, XYLOL (IARC - GROUP 3) \*97-1\*

CAS: 1330-20-7

RTECS: ZE2100000

Fraction By Weight: 5-

OSHA PEL100 PPM

ACGIH TLV: 100 PPM, SKIN

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

METHYL ETHYL KETONE, 2-BUTANONE \*97-1\*

CAS: 78-93-3

RTECS: EL6475000

Fraction By Weight: 12%

OSHA PEL200 PPM

ACGIH TLV: 590 MG/CUM

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

ACETIC ACID, ETHYL ESTER, ETHYL ACETATE \*97-1\*

CAS: 141-78-6

RTECS: AH5425000

Fraction By Weight: 10%

OSHA PEL1400 MG/CUM

ACGIH TLV: 1400 MG/CUM

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

## Hazards

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:INHALATION: MAY CAUSE IRRITATION TO THE RESPIRATORY TRACT; NOSE, THROAT, LUNGS & CAUSE NARCOSIS. EYES: IRRITATING, MAY INJURE TISSUE IF NOT PROPERLY REMOVED. SKIN: SLIGHT IRRITANT. INGESTION: MODERATE LY TOXIC.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:IRRITATION, NAUSEA, VOMITING, DIARRHEA, NARCOSIS

Medical Cond Aggravated by Exposure:RESPIRATORY PROBLEMS.

## First Aid

First Aid:EYES: FLUSH W/WATER FOR 15 MINS. SKIN: WASH W/SOAP & WATER.

INHALATION: MOVE TO FRESH AIR. INGESTION: DON'T INDUCE VOMITING.

OBTAIN MEDICAL ATTENTION IN ALL CASES.

## Fire Fighting

Flash Point Method:TCC

Flash Point:21F

Lower Limits:1.1

Upper Limits:13.1

Extinguishing Media:FOAM, CO2, DRY CHEMICAL

Fire Fighting Procedures:WEAR SELF CONTAINED BREATHING APPARATUS W/A FULL FACEPIECE OPERATED IN PRESSURE-DEMAND WHEN FIGHTING FIRES. USE WATER FOG NOZZLES TO COOL CLOSED CONTAINERS.

Unusual Fire/Explosion Hazard:DON'T USE WATER. FLAMMABLE LIQUID CAN RELEASE VAPORS THAT FORM MIXTURES AT TEMP AT/ABOVE FLASHPOINT. ELIMINATE/ISOLATE IGNITION SOURCES. MAY PRODUCE TOXIC GASES

## Accidental Release

Spill Release Procedures:WEAR RESPIRATOR, ABSORB W/VERMICULITE/OTHER ABSORBENT MATERIAL. ELIMINATE ALL IGNITION SOURCES. STOP LEAK AT SOURCE & PREVENT SPREADING.

## Handling

Handling and Storage Precautions:STORE IN DRY AREA. KEEP CONTAINERS CLOSED. PROTECT FROM PHYSICAL DAMAGE. EMPTIED CONTAINERS RETAIN PRODUCT RESIDUES. STORE Other Precautions:STORE LARGE QUANTITIES IN BUILDINGS DESIGNED TO COMPLY W/OSHA 1910.106. KEEP CLOSURE TIGHT & CONTAINER UPRIGHT. DON'T STORE NEAR HEAT/SPARKS/FLAME. DON'T GET IN EYES. KEEP AWAY FROM CHILDREN. AVOID SK IN CONTACT. DON'T TAKE INTERNALLY.

## Exposure Controls

Respiratory Protection:IF TLV IS EXCEEDED, A NIOSH/MSHA JOINTLY APPROVED AIR SUPPLY RESPIRATOR IS ADVISED IN ABSENCE OF PROPER ENVIRONMENTAL CONTROL.  
Ventilation:SUFFICIENT MECHANICAL (GENERAL/LOCAL EXHAUST) VENTILATION TO MAINTAIN EXPOSURE BELOW TLVS.  
Protective Gloves:SOLVENT RESISTANT  
Eye Protection:CHEMICAL SPLASH GOGGLES/SAFETY GLASSES  
Other Protective Equipment:SOLVENT IMPERVIOUS CLOTHING & BOOTS.  
Work Hygienic Practices:REMOVE/LAUNDER CONTAMINATED CLOTHING BEFORE REUSE. WASH W/SOAP & WATER AFTER USE, BEFORE EATING/SMOKING.  
Supplemental Safety and Health

## Chemical Properties

Boiling Pt:B.P. Text:167-302F  
Vapor Density:> 1  
Spec Gravity:1.1  
VOC Grams/Liter:4.56  
Evaporation Rate & Reference:SLOWER THAN ETHER  
Solubility in Water:Appearance and Odor:BLACK LIQUID W/SOLVENT ODOR

## Stability

Stability Indicator/Materials to Avoid:YES  
STRONG OXIDIZING AGENTS  
Stability Condition to Avoid:EXCESSIVE HEAT, SPARKS, FLAME, TEMPS  
AT/ABOVE 21F & OTHER IGNITION SOURCES  
Hazardous Decomposition Products:BY BURNING: CO2, CO

## Disposal

Waste Disposal Methods:DESTROY BY LIQUID INCINERATION. CONTAMINATED ABSORBENT MAY BE DEPOSITED IN A LANDFILL IAW/LOCAL, STATE & FEDERAL REGULATIONS.

## Other Information

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.