
LPS TAPMATIC DUAL ACTION PLUS 2 CUTTING FLUID 40260

MSDS Number

CGJQZ

National Stock Number

7930-00F040934

Product Name

LPS TAPMATIC DUAL ACTION PLUS 2 CUTTING FLUID 40260

Manufacturer

LPS LABORATORIES

Product Identification

Product ID:LPS TAPMATIC DUAL ACTION PLUS 2 CUTTING FLUID 40260

MSDS Date:06/28/1992

FSC:7930

NIIN:00F040934

MSDS Number: CGJQZ

Responsible Party

LPS LABORATORIES

4647 HUGH HOWELL ROAD

TUCKER , GA 30084-5052

US

Emergency Phone: 404-934-7800/202-887-1255

Info Phone: 404-934-7800/202-887-1255

Preparer: JOHN ROUDEBUSH

Cage: 66724

Contractor

LPS LABORATORIES, INC.

TUCKER, GA 30085-5052

US

404-934-7800

Cage: 66724

Ingredients

NON HAZARDOUS PROPRIETARY BLEND

Fraction By Weight: 20-30%

HEAVY ALIPHATIC NAPHTHA *95-2*

CAS: 64742-96-7

Fraction By Weight: 70-80%

OSHA PEL500 PPM

Hazards

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:INHALATION: ANESTHETIC EFFECTS. EYES:
IRRITATION. INGESTION: LOW ORDER OF ORAL TOXICITY, HOWEVER MINUTE
AMOUNT ASPIRATED INTO LUNGS MAY CAUSE SEVERE PULMONARY INJURY.

Explanation of Carcinogenicity:NONE

Effects of Overexposure: HEADACHE, DIZZINESS, NAUSEA, DRYING, IRRITATION.
Medical Cond Aggravated by Exposure: NONE FROM NORMAL EXPOSURE.

First Aid

First Aid: INHALATION: REMOVE TO FRESH AIR. EYES: FLUSH W/PLENTHY OF WATER. SKIN: WASH W/ SOAP & WATER. APPLY MEDICATED CREAM. INGESTION: DON'T INDUCE VOMITING. OBTAIN MEDICAL ATTENTION IN ALL CASES.

Fire Fighting

Flash Point Method: SCC
Flash Point: 165F
Lower Limits: 1
Upper Limits: 6
Extinguishing Media: FOAM, DRY CHEMICAL, CO2
Fire Fighting Procedures: DON'T USE WATER. TREAT AS COMBUSTIBLE PETROLEUM DISTILLATES.
Unusual Fire/Explosion Hazard: NEVER USE WELDING/CUTTING TORCH ON/NEAR DRUM (EVEN EMPTY).

Accidental Release

Spill Release Procedures: VENTILATE AREA. REMOVE IGNITION SOURCES. REMOVE LEAKING CONTAINER & TRANSFER REMAINING PRODUCT TO ANOTHER VESSEL. PREVENT FROM GOING INTO SEWERS/WATER SOURCES BY DIKING/IMPOUNDING. USE SAFETY EQUIPMENT, MOP/SOAK UP W/ ABSORBENT MATERIAL.

Handling

Handling and Storage Precautions: STORE 32F. STORE AWAY FROM IGNITION SOURCES.
Other Precautions: AVOID BREATHING VAPORS.

Exposure Controls

Respiratory Protection: NONE REQUIRED IF GOOD VENTILATION IS MAINTAINED. ENCLOSED AREAS: USE NIOSH APPROVED ORGANIC VAPOR CARTRIDGE RESPIRATOR/SCBA.
Ventilation: LOCAL EXHAUST IS ADEQUATE. MECHANICAL VENTILATION WHEN SPRAYING IN ENCLOSED AREAS. MINIMIZE VAPOR CONCENTRATIONS.
Protective Gloves: SOLVENT RESISTANT
Eye Protection: FACE SHIELD/GOGGLES
Other Protective Equipment: NONE
Work Hygienic Practices: REMOVE/LAUNDRER CONTAMINATED CLOTHING BEFORE REUSE. WASH THOROUGHLY AFTER HANDLING.
Supplemental Safety and Health

Chemical Properties

Boiling Pt: B.P. Text: 350F
Vapor Pres: 2
Vapor Density: 4.7
Spec Gravity: 0.817
Evaporation Rate & Reference: (N-BU AC = 1): 0.07
Solubility in Water: INSOLUBLE
Appearance and Odor: CLEAR, THIN LIQUID W/MILD, FATTY ODOR.
Percent Volatiles by Volume: 70

Stability

Stability Indicator/Materials to Avoid: YES
STRONG OXIDIZING AGENTS.
Stability Condition to Avoid: SPARKS, OPEN FLAMES & OTHER IGNITION SOURCES.
Hazardous Decomposition Products: CO

Disposal

Waste Disposal Methods: DISPOSE OF IAW/FEDERAL, STATE & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department

of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.