

P-120, THORNEL PITCH & THERMALGRAPH BASED ON (SUPDAT)

MSDS Number

CHBMR

National Stock Number

9390-00N085365

Product Name

P-120, THORNEL PITCH & THERMALGRAPH BASED ON (SUPDAT)

Manufacturer

AMOCO PERFORMANCE PRODUCTS INC

Product Identification

Product ID:P-120, THORNEL PITCH & THERMALGRAPH BASED ON (SUPDAT)

MSDS Date:06/16/1997

FSC:9390

NIIN:00N085365

MSDS Number: CHBMR

Responsible Party

AMOCO PERFORMANCE PRODUCTS INC

200 EAST RANDOLPH DRIVE

CHICAGO , IL 60601

US

Emergency Phone: 800-424-9300(CHEMTREC)

Info Phone: 312-856-3340;800-222-2448

Cage: 15958

Contractor

AMOCO OIL CO

CHICAGO, IL 60601-6401

US

800 447-8735

Cage: 15958

Ingredients

CARBON; (CARBON FIBER, PITCH BASED)

CAS: 7440-44-0

RTECS: FF5250100

Fraction By Weight: 100%

OSHA PEL15 MG/M3 TDUST

ACGIH TLV: 2 MG/M3 TDUST

ARE USED/HNDLD SHOULD BE PROPERLY PROTECTED AGAINST

RTECS: 9999999ZZ

INVOLVING CHRONIC APPLICATION OF PITCH

RTECS: 9999999ZZ

WEAK LOC TUMORIGENIC RESPONSE. BENZENE EXTRACT OF

RTECS: 9999999ZZ

GENETIC EFTS.

RTECS: 9999999ZZ

MEETS CRITERIA FOR BEING TOX, CORR,

RTECS: 9999999ZZ

SUBPART C). THIS MATL COULD ALSO BECOME HAZ WASTE IF

RTECS: 9999999ZZ

IF IT IS HAZ WASTE, REGS IN 40 CFR 262-266, 268, 270

RTECS: 9999999ZZ

FIBERS. NIOSH REC EXPOS LIM OF 3 FIBERS/CC FOR

RTECS: 9999999ZZ

RECS EXPOS GUIDELINE OF 3 FIBERS/CC UP TO 10

RTECS: 9999999ZZ

CONSERVATIVE APPROACH & INCLS ALL FIBER DIAMETERS IN

RTECS: 9999999ZZ

OUR MFG OPERATIONS HAVE BEEN LOW-TYPICALLY 0.01-0.02

RTECS: 9999999ZZ

CHOPPING OPERATIONS.

RTECS: 9999999ZZ

Hazards

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:THIS PROD HAS BEEN EVAL & DOES NOT REQ ANY HAZ WARNING ON LBL UNDER OSHA CRITERIA. HNDLG &/OR PROCESSING OF THIS MATL MAY GENERATE AIRBORNE FIBERS & PARTICLES WHICH CAN CAUSE MECH IRRIT OF EYES, SKIN, NOSE & THROAT. EYE/SKIN CONT:NO SIGNIFICANT HLTH HAZS IDENTIFIED. PARTICLES/FIBERS MAY CAUSE SLIGHT (EFTS OF OVEREXP)

Explanation of Carcinogenicity:NOT RELEVANT

Effects of Overexposure:HLTH HAZ:DISCOMFORT SIMILAR TO GETTING DUST IN EYE/RUBBING SAND AGAINST SKIN. INHAL:NO SIGNIFICANT IRRIT EXPECTED OTHER THAN POSS MECH IRRIT. INGEST:NO SIGNIFICANT HLTH HAZS IDENTIFIED. TOX INFO:DENSE DUST GENERATED BY HNDLG &/OR PROCESSING OF THIS MATL MAY BE IRRIT TO EYES, SKIN, NOSE & THROAT. STUDIES

(ING 3)
Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

First Aid

First Aid:EYES:FLUSH W/PLENTY OF WATER FOR AT LEAST 15 MINUTES. GET MEDICAL ATTENTION IF IRRITATION PERSISTS. SKIN:WASH EXPOSED SKIN W/SOAP & WATER. INHAL:REMOVE TO UNCONTAMINATED AREA. GET MEDICAL ATTENTION. I NGEST:IF LARGE AMOUNT IS SWALLOWED, GETMEDICAL ATTENTION.

Fire Fighting

Extinguishing Media:AGENTS APPROVED FOR CLASS A HAZARDS (E.G., FOAM, STEAM) OR WATER FOG.

Fire Fighting Procedures:USE NIOSH APPROVED SCBA & FULL PROTECTIVE EQUIPMENT .

Unusual Fire/Explosion Hazard:FIBER, DUST & FIBROUS PARTICLES ARE ELECTRICALLY CONDUCTIVE & CAN CAUSE SHORTING IN ELEC EQUIP. EXPLO SHORTING OF HIGH VOLTAGE SYSTEMS IS POSS. CARBON (SUPDAT)

Accidental Release

Spill Release Procedures:CONTAIN & REMOVE BY MECHANICAL MEANS. VACUUM OR SWEEP OUT; AVOID PRODUCING DUST.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

Handling

Handling and Storage Precautions:MINIMIZE DUST GENERATION & ACCUMULATION. NO SPECIAL STORAGE REQUIREMENTS.

Other Precautions:NONE SPECIFIED BY MANUFACTURER.

Exposure Controls

Respiratory Protection:IF VENT IS INADEQ, USE NIOSH APPRVD RESP THAT WILL PROT AGAINST DUST/MIST. CURRENTLY NO HLTH STDS EXIST FOR EMPLOYEE EXPOS TO CARBON FIBERS. IN 1977, NIOSH PROPOSED THAT THEIR REC STD FOR FIBROUS GLAS S BE APPLIED TO OTHER MAN-MADE (ING 9)

Ventilation:NO SPECIAL CONTROLS NECESSARY. LOCAL EXHAUST VENTILATION MAY BE NECESSARY FOR SOME OPERATIONS.

Protective Gloves:IMPERVIOUS GLOVES .

Eye Protection:ANSI APPROVED CHEM WORKERS GOGGS .

Other Protective Equipment:ANSI APPRVD EYE WASH FOUNTAIN & DELUGE SHOWER. LONG SLEEVE-GARMENTS W/TIGHT-FITTING CUFFS & USE OF BARRIER(SUPDAT)

Work Hygienic Practices:NONE SPECIFIED BY MANUFACTURER.

Supplemental Safety and Health

MFR'S TRADE NAME/PART NO:HIGH & ULTRA-HIGH MODULUS FIBER. OTHER PROT EQUIP:CREAMS/TALCUM PROVIDE ADDNL PROT TO SKIN. EXPLO HAZ:FIBERS ARE ELECTRONICALLY CONDUCTIVE & MAY CAUSE SHORT CIRCUITS WHICH RSL T IN DMG TO/MALFUNCTIONING ELEC EQUIP. ALL FORMS OF ELEC EQUIP, ENCLOSURES & CIRCUITS IN/NEAR AREAS WHERE FIBERS (ING 2)

Chemical Properties

Melt/Freeze Pt:M.P/F.P Text:6512F,3600C

Solubility in Water:NEGLIGIBLE; Appearance and Odor:BLACK CARBON FIBER, FABRIC OR CLOTH.

Stability

Stability Indicator/Materials to Avoid:YES
NONE IDENTIFIED.

Stability Condition to Avoid:AVOID GENERATING DUST.

Hazardous Decomposition Products:NONE IDENTIFIED.

Disposal

Waste Disposal Methods:DISP MUST BE I/A/W APPLIC FED, STATE/LOC REGS. DO NOT INCIN. BURIAL AT PERMITTED LANDFILL IS REC. RCRA:THIS UNUSED MATL, WHEN DISCARDED/DISP OF, IS NOT SPECIFICALLY LISTED AS HAZ WASTE IN FED REGS; HO WEVER, IT COULD BE CONSIDERED HAZ IF IT(ING 6)

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.