
T BASE F63TX NON-LEAD CUSTOM COLORS, POLANE (SUP DAT)

MSDS Number

CHGMT

National Stock Number

8010-00N087167

Product Name

T BASE F63TX NON-LEAD CUSTOM COLORS, POLANE (SUP DAT)

Manufacturer

SHERWIN WILLIAMS CO

Product Identification

Product ID:T BASE F63TX NON-LEAD CUSTOM COLORS, POLANE (SUP DAT)

MSDS Date:11/01/1995

FSC:8010

NIIN:00N087167

MSDS Number: CHGMT

Responsible Party

SHERWIN-WILLIAMS CO

101 PROSPECT AVE NW

CLEVELAND , OH 44115

US

Emergency Phone: 216-566-2917

Info Phone: 216-566-2902

Cage: 54636

Contractor

SHERWIN-WILLIAMS CO THE

CLEVELAND, OH 44115-1042

US

800-251-2486/216-566-2242

Cage: 54636

Ingredients

22.0

CAS: 108-88-3

RTECS: XS5250000

Fraction By Weight: 3-8%

OSHA PEL200 PPM

ACGIH TLV: 50 PPM, S

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

5.9

CAS: 1330-20-7

RTECS: ZE2100000

Fraction By Weight: 2-4%

OSHA PEL100 PPM
ACGIH TLV: 100 PPM/150 STEL
EPA Report Quantity: 1000 LBS
DOT Report Quantity: 1000 LBS

METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA 313) (CERCLA)

CAS: 78-93-3
RTECS: EL6475000
Fraction By Weight: 4-23%
OSHA PEL200 PPM
ACGIH TLV: 200 PPM/300 STEL
EPA Report Quantity: 5000 LBS
DOT Report Quantity: 5000 LBS

2.0

CAS: 108-94-1
RTECS: GW1050000
Fraction By Weight: 10-30%
OSHA PEL50 PPM, S
ACGIH TLV: 25 PPM, S
EPA Report Quantity: 5000 LBS
DOT Report Quantity: 5000 LBS

10.0

CAS: 123-86-4
RTECS: AF7350000
Fraction By Weight: 5-26%
OSHA PEL150 PPM
ACGIH TLV: 150 PPM/200 STEL
EPA Report Quantity: 5000 LBS
DOT Report Quantity: 5000 LBS

TALC (POWDER), CONTAINING NO ASBESTOS FIBERS; (TALC)

CAS: 14807-96-6
RTECS: WW2710000
Fraction By Weight: 6-12%
OSHA PEL20 MPPCF
ACGIH TLV: 2 MG/M3 RDUST

TITANIUM OXIDE; (TITANIUM DIOXIDE)

CAS: 13463-67-7
RTECS: XR2275000

Fraction By Weight: 0-30%
OSHA PEL15 MG/M3 TDUST
ACGIH TLV: 10 MG/M3 TDUST

4.4-5.4

RTECS: 9999999VO
OSHA PELN/K
ACGIH TLV: N/K

PRESSURE IN, AND POSSIBLE BURSTING OF
RTECS: 9999999ZZ

SYMPS INCL ABDOM DISCOMFORT/PAIN, CONSTIP,
RTECS: 9999999ZZ

IRRITABILITY, WEAK, MUSC & JOINT PAINS, HDCH &
RTECS: 9999999ZZ

STUDIES HAVE ASSOC EXPOS TO CHROMIUM VI CMPDS
RTECS: 9999999ZZ

LEAD CHROMATE (CHROME YELLOW, MOLYBDATE ORANGE)
RTECS: 9999999ZZ

MAY CAUSE ADVERSE EFTS TO LIVER, URINARY,
RTECS: 9999999ZZ

ISOCYANATES WILL EXPER INCRD ALLERGIC RXN ON RPTD
RTECS: 9999999ZZ

OTHER SOLVS. RATS EXPOSED TO TITANIUM DIOXIDE DUST
RTECS: 9999999ZZ

EXPOS LEVELS ARE NOT ATTAINABLE IN WORKPLACE. RPTS
RTECS: 9999999ZZ

& NERV SYS DMG. TOLUENE & LEAD APPEAR ON THE NAVY
RTECS: 9999999ZZ

APPROP HEALTH PROFESSIONALS CONCERNING LATEST

RTECS: 9999999ZZ

(HOUSEHOLD AMMONIA). AFTER 10 MIN, COLLECT IN

RTECS: 9999999ZZ

WASH SPILL AREA WITH SOAP AND WATER.

RTECS: 9999999ZZ

INCIN IN APPRVD FACILITY. DO NOT INCIN

RTECS: 9999999ZZ

CONSULT NFPA CODE. USE APPRVD BONDING &

RTECS: 9999999ZZ

ONLY TO APPRVD CONTRS W/COMPLETE & APPROP LABELING.

RTECS: 9999999ZZ

CHILDREN. INT MISUSE BY DELIB CONC & INHALING

RTECS: 9999999ZZ

Hazards

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE: IRRIT OF EYES, SKIN & RESP SYS. MAY CAUSE NERV SYS DEPRESS. EXTREME OVEREXP MAY RSLT IN UNCON & POSS DEATH. CERTAIN COLORS CONTAIN LEAD. ACUTE OCCUP OVEREXP TO LEAD IS UNCOMMON, BUT RSLTS IN SY MPS SIMILAR TO CHRONIC OVEREXP DESCRIBED BELOW. SIGNS & SYMPS OF OVEREXP: HDCH, DIZZ, NAUS & LOSS OF (EFTS OF OVEREXP)

Explanation of Carcinogenicity:NOT RELEVANT.

Effects of Overexposure:HLTH HAZ: COORD ARE INDICATIONS OF EXCESS EXPOS TO VAPS/SPRAY MISTS. REDNESS & ITCH/BURNING SENSATION MAY INDICATE EYE/EXCESS SKIN EXPOS. CHRONIC: CERTAIN COLORS CONTAIN LEAD &/OR CHROMATE. CHRONIC OV EREXP TO LEAD MAY RSLT IN DMG TO BLOOD-FORMING, NERV, URINARY & REPRO SYS (INCL EMBRYOTOX EFTS). (ING 10)

Medical Cond Aggravated by Exposure:MAY CAUSE ALLERGIC RESPIRATORY AND/OR SKIN REACTION IN SUSCEPTIBLE PERSONS OR SENSITIZATION. THIS EFFECT MAY BE DELAYED SEVERAL HOURS AFTER EXPOSURE.

First Aid

First Aid:INHALATION: IF ANY BREATHING PROBLEMS OCCUR DURING USE, LEAVE AREA AND GET FRESH AIR. IF PROBLEMS REMAIN OR OCCUR LATER, IMMEDIATELY GET MEDICAL ATTENTION. SKIN: WASH AFFECTED AREA THOROUGHLY WITH SOA P AND WATER. REMOVE CONTAMINATED CLOTHING AND LAUNDER BEFORE REUSE. EYES: FLUSH WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES. GET MEDICAL ATTENTION. INGESTION: GET MEDICAL ATTENTION.

Fire Fighting

Flash Point:41.0F,5.0C

Lower Limits:0.7%

Upper Limits:13.3%

Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL, FOAM.

Fire Fighting Procedures:WEAR NIOSH APPRVD SCBA & FULL PROT EQUIP .
WATER SPRAY MAY BE INEFFECTIVE. IF WATER IS USED, FOG NOZZ ARE
PREF. WATER MAY BE USED TO COOL CLSD (SUP DAT)
Unusual Fire/Explosion Hazard:KEEP CONTRS TIGHTLY CLSD. ISOLATE FROM
HEAT, ELEC EQUIP, SPKS, & OPEN FLAMES. CLSD CONTRS MAY EXPLODE WHEN
EXPOSED TO EXTREME HEAT. APPLICATION TO HOT (SUP DAT)

Accidental Release

Spill Release Procedures:REMOVE ALL SOURCES OF IGNIT. VENT AREA. FOR
COLORS & REDUCERS: REMOVE W/INERT ABSORB. FOR CATALYSTS: ALL PERS
IN AREA SHOULD BE PROTECTED AS DIRECTED. COVER SPILL W/ABSORB MATL.
DEACTIVATE SPILLED MAT L W/10% AMMONIUM HYDROXIDE SOLN (ING 20)
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

Handling

Handling and Storage Precautions:NO PERS W/CHRONIC (LONG-TERM)
LUNG/BRTHG PROBLEMS/IF THEY EVER HAD RXN TO ISOCYANATES, SHOULD USE
THESE PRODS/BE IN AREA WHERE THEY ARE BEING USED.
Other Precautions:KEEP AWAY FROM HEAT, SPKS & OPEN FLAME. DURING USE &
UNTIL ALL VAPS ARE GONE: KEEP AREA VENTD; DO NOT SMOKE; EXTING ALL
FLAMES, PILOT LIGHTS & HEATERS; TURN OFF STOVES, ELEC TOOLS &
APPLIANCES, & ANY OTHER SOURCES OF IGNIT. (ING 23)

Exposure Controls

Respiratory Protection:WHERE OVERSPRAY IS PRESENT, USE POS PRESS
AIR-SUPP RESP (TC-19C NIOSH APPRVD). IF NOT AVAIL, USE PROPERLY
FITTED NIOSH APPRVD ORG VAP PARTICULATE RESP. FOLLOW RESP MFR'S
DIRECTIONS FOR USE. CONT NEHC FOR MORE SPECIFIC INFO .
Ventilation:LOC EXHST PREF. GEN EXHST ACCEPTABLE IF EXPOS IS MAINT
BELOW APPLIC EXPOS LIMS. REFER TO OSHA STDS 1910.94/107/108.
Protective Gloves:IMPERVIOUS GLOVES .
Eye Protection:ANSI APPRVD CHEM WORKERS GOGGLES .
Other Protective Equipment:EMERGENCY EYEWASH AND DELUGE SHOWER MEETING
ANSI DESIGN CRITERIA .
Work Hygienic Practices:AVOID BRTHG VAP & SPRAY MIST. AVOID CONT W/SKIN
& EYES. WASH HANDS AFTER USING.
Supplemental Safety and Health
TRADE NAME/PART #: B/T POLYURETHANE ENAMEL SYSTEMS. FIRE FIGHT PROC:
CONTRS TO PVNT PRESS BUILD-UP & POSS AUTOIGNIT/EXPLO WHEN EXPOSED
TO EXTREME HEAT. EXPLO HAZ: SURFS REQUIRES SPECIAL PREC. DURING E
MER CNDTNS OVEREXP TO DECOMP PRODS MAY CAUSE HLTH HAZ. SYMPS MAY
NOT BE IMMED APPARENT. OBTAIN MED ATTN.

Chemical Properties

Boiling Pt:B.P. Text:>174F,>79C
Vapor Pres:SEE INGS
Vapor Density:HVR/AIR
Spec Gravity:0.85-1.40
Evaporation Rate & Reference:SLOWER THAN ETHER
Appearance and Odor:NONE SPECIFIED BY MANUFACTURER
Percent Volatiles by Volume:30-100

Stability

Stability Indicator/Materials to Avoid:YES
CONTAM OF CATALYST W/WATER. ALCOHOLS. AMINES & OTHER COMPOUNDS WHICH
REACT W/ISOCYANATES, MAY RSLT IN DANGEROUS (ING 9)
Stability Condition to Avoid:NONE KNOWN.
Hazardous Decomposition Products:BY FIRE: CARBON DIOXIDE & MONOXIDE,
OXIDES OF METALS IN INGS SECTION. OXIDES OF NITROGEN, POSS OF
HYDROGEN CYANIDE.

Disposal

Waste Disposal Methods:WASTE MAY BE HAZ AS DEFINED UNDER RCRA 40 CFR
261. WASTE MUST BE TESTED FOR IGNITABILITY TO DETERMINE APPLIC EPA
HAZ WASTE NUMBERS. WASTE FROM PRODS CONTAINING LEAD,
CHROMIUM/METHYL ETHYL KETONE MUST ALSO BE TESTED FOR
EXTRACTABILITY. (ING22)

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.