

192401 44 ACRI-FLAT WHITE BASES & COLORS

MSDS Number

CJZNY

National Stock Number

-

Product Name

192401 44 ACRI-FLAT WHITE BASES & COLORS

Manufacturer

WELLBORN PAINT MFG CO

Product Identification

Product ID:192401 44 ACRI-FLAT WHITE BASES & COLORS

MSDS Date:09/01/1998

FSC:NIIN:Submitter:F BT

Status Code:A

MSDS Number: CJZNY

Responsible Party

WELLBORN PAINT MFG CO

215 ROSSMOOR RD SW

ALBUQUERQUE , NM 87105

US

Emergency Phone: 505-877-5050

Info Phone: 505-877-5050

Cage: 60378

Contractor

WELLBORN PAINT MFG CO

ALBUQUERQUE, NM 87105

US

505-877-5050

Cage: 60378

Ingredients

NON-HAZARDOUS INGREDIENT

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Health Hazards Acute and Chronic:INHALATION: IRRITATION IN THE UPPER & LOWER RESPIRATORY TRACTS. EYES/SKIN: MAY CAUSE IRRITATION.

INGESTION: GASTROINTESTINAL IRRITANT.

Effects of Overexposure:IRRITATION, NAUSEA, HEADACHES, DIZZINESS, REDNESS, TEARING, VOMITING, DIARRHEA

Medical Cond Aggravated by Exposure:HEADACHES, DIZZINESS, NAUSEA

First Aid

First Aid:INHALATION: MOVE TO FRESH AIR. APPLY CPR. EYES/SKIN: THOROUGHLY WASH W/CLEAN WATER. INGESTION: IF CONSCIOUS, GIVE 2 GLASSES OF WATER TO DRINK. OBTAIN MEDICAL ATTENTION IN ALL CASES.

Fire Fighting

Flash Point:NONE

Lower Limits:NONE

Upper Limits:NONE

Extinguishing Media: ONLY DRIED FILM WILL BURN. FOAM, CO₂,
CHEMICAL/WATER FOG
Fire Fighting Procedures: WEAR APPROPRIATE FIRE FIGHTING PROTECTION
W/SELF CONTAINED BREATHING IN CONFINED AREAS.
Unusual Fire/Explosion Hazard: UNOPENED CONTAINERS MAY BURST OPEN &
SPATTER. KEEP CONTAINERS COOL W/WATER SPRAY/REMOVE FROM AREA.

Accidental Release

Spill Release Procedures: KEEP OUT OF OPEN BODIES OF WATER, STORM DRAINS
& SEWERS. DIKE & ABSORB W/INERT MATERIAL & PUT INTO CONTAINERS FOR
RECOVERY/DISPOSAL.

Handling

Handling and Storage Precautions: KEEP CONTAINERS CLOSED WHEN NOT IN
USE. ROTATE STOCK, USE OLD MATERIALS FIRST.
Other Precautions: DON'T TAKE INTERNALLY. AVOID PROLONGED
CONTACT/INHALATION. KEEP OUT OF REACH OF CHILDREN.

Exposure Controls

Respiratory Protection: WEAR RESPIRATORY PROTECTION UNLESS VENTILATION
KEEP AIRBORNE CONTAMINATES BELOW EXPOSURE TLV/WHEN SPRAY APPLYING
THIS PRODUCT, SANDING/ABRADING THE DRIED FILM/AT ANYTIME THERE IS
EXPOSURE TO MIST, SPRAY, DUST/SMOKE FROM THE PRODUCT. MUST BE AN
AIR SUPPLIED MASK/HOOD/A NIOSH APPROVED RESPIRATOR IAW/29 CFR
1910.134 W/AN ORGANIC VAPOR & DUST CARTRIDGE.
Ventilation: USE LOCAL EXHAUST TO REDUCE AIRBORNE MATERIALS BELOW
TLV/USE PERSONAL RESPIRATORY PROTECTION AS INDICATED. MECHANICAL
EXHAUST MUST BE EXPLOSION PROOF.
Protective Gloves: IMPERMEABLE SOLVENT RESISTANT
Eye Protection: CHEMICAL GOGGLES/FACESHIELD
Other Protective Equipment: CAP & IMPERMEABLE APRON.
Work Hygienic Practices: REMOVE/LAUNDER CONTAMINATED CLOTHING & SHOES
BEFORE REUSE.
Supplemental Safety and Health

Chemical Properties

Boiling Pt: =100.C, 212.F
Vapor Pres: 17.5
Vapor Density: >1
Evaporation Rate & Reference: SLOWER-BUTYL ACETATE
Solubility in Water: MISCIBLE
Appearance and Odor: OPAQUE LIQUID W/MILD ODOR

Stability

Stability Indicator/Materials to Avoid: YES
WATER, STRONG ACIDS/ALKALIS
Hazardous Decomposition Products: BURNING FILM WILL EMIT STRONG ACRID
FUMES.

Disposal

Waste Disposal Methods: INCINERATE/LANDFILL/DISPOSE OF IN ACCORDANCE
W/LOCAL, STATE & FEDERAL REGULATIONS.

Other Information

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.