

"EASTMAN" ETHYL ACETATE, 99%

MSDS Number

CKDMG

National Stock Number

6810-00-245-6694

Product Name

"EASTMAN" ETHYL ACETATE, 99%

Manufacturer

EASTMAN CHEMICAL PRODUCTS INC

Product Identification

Product ID:"EASTMAN" ETHYL ACETATE, 99%

MSDS Date:04/20/1990

FSC:6810

NIIN:00-245-6694

Status Code:A

MSDS Number: CKDMG

Responsible Party

EASTMAN CHEMICAL PRODUCTS, INC.

KINGSPORT , TN 37662

US

Emergency Phone: 615-229-6094

Info Phone: 615-229-6094

Cage: TO540

Contractor

PHOENIX INDUSTRIES INC

RICHMOND, VA 23222

US

264-5535

Cage: 0YED2

Ingredients

ETHYL ACETATE

CAS: 141-78-6

RTECS: AH5425000

OSHA PEL1400 MG/M3;400 PPM

ACGIH TLV: 1440 MG/M3;400 PPM

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

ETHANOL

CAS: 64-17-5

RTECS: KQ6300000

OSHA PEL1900 MG/M3;1000 PPM

ACGIH TLV: 1880 MG/M3;1000 PPM

Hazards

LD50 LC50 Mixture:ORAL LD-50 RAT 5.60 G/KG
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE: INHALATION: HIGH VAPOR CONCENTRATIONS MAY CAUSE DROWSINESS AND IRRITATION. EYES: LOW HAZARD FOR USUAL INDUSTRIAL HANDLING. HOWEVER, ANY MATERIAL THAT CONTACTS THE EYE MAY BE IRRITATING OR MAY CAUSE MECHANICAL INJURY. SKIN: PROLONGED OR REPEATED CONTACT MAY CAUSE DRYING, CRACKING, OR IRRITATION. INGESTION: EXPECTED TO BE A LOW INGESTION HAZARD.
Explanation of Carcinogenicity:CARCINOGENICITY CLASSIFICATION (COMPONENTS PRESENT AT 0.1% OR MORE): NONE LISTED.
Effects of Overexposure:ACUTE: INHALATION: HIGH VAPOR CONCENTRATIONS MAY CAUSE DROWSINESS AND IRRITATION. EYES: LOW HAZARD FOR USUAL INDUSTRIAL HANDLING. HOWEVER, ANY MATERIAL THAT CONTACTS THE EYE MAY BE IRRITATING OR MAY CAUSE MECHANICAL INJURY. SKIN: PROLONGED OR REPEATED CONTACT MAY CAUSE DRYING, CRACKING, OR IRRITATION. INGESTION: EXPECTED TO BE A LOW INGESTION HAZARD.
Medical Cond Aggravated by Exposure:NO DATA PROVIDED BY RESPONSIBLE PARTY.

First Aid

First Aid:INHALATION: IN CASE OF IRRITATION BY VAPOR, REMOVE FROM EXPOSURE, TREAT SYMPTOMATICALLY, AND GET MEDICAL ATTENTION, IF SYMPTOMS PERSIST. EYES: ANY MATERIAL THAT CONTACTS THE EYE SHOULD BE WASHED OUT IMMEDIATELY AND MEDICAL ATTENTION OBTAINED IF SYMPTOMS PERSIST. SKIN: WASH WITH SOAP AND PLENTY OF WATER. INGESTION: CALL A PHYSICIAN OR POISON CONTROL CENTER IMMEDIATELY. INDUCE VOMITING AS DIRECTED BY MEDICAL PERSONNEL. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.

Fire Fighting

Flash Point Method:TCC
Flash Point:=-4.4C, 24.F
Autoignition Temp: =485.C, 905.F
Lower Limits:2.02% AT 38C
Upper Limits:10.7% AT 38C
Extinguishing Media:MEANS OF EXTINCTION: WATER SPRAY, DRY CHEMICAL, CARBON DIOXIDE, OR "ALCOHOL" FOAM.
Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS AND PROTECTIVE CLOTHING TO PREVENT CONTACT WITH SKIN AND EYES. USE WATER SPRAY TO KEEP FIRE-EXPOSED CONTAINERS COOL. WATER MAY BE INEFFECTIVE IN FIGHTING THE FIRE.
Unusual Fire/Explosion Hazard:MATERIAL IS FLAMMABLE. VAPORS MAY TRAVEL CONSIDERABLE DISTANCE TO A SOURCE OF IGNITION AND FLASH BACK. KEEP AWAY FROM HEAT, SPARKS, AND FLAME. KEEP CONTAINER CLOSED. USE WITH ADEQUATE VENTILATION.

Accidental Release

Spill Release Procedures:ELIMINATE ALL IGNITION SOURCES. WEAR A SELF-CONTAINED BREATHING APPARATUS AND APPROPRIATE PERSONAL PROTECTIVE EQUIPMENT. FOR LARGE SPILLS, USE WATER SPRAY TO DISPERSE VAPORS AND DILUTE SPILL TO A NONFLAMMABLE MIXTURE. PREVENT RUNOFF FROM ENTERING DRAINS, SEWERS, OR STREAMS.
Neutralizing Agent:NO DATA PROVIDED BY RESPONSIBLE PARTY.

Handling

Handling and Storage Precautions:KEEP FROM CONTACT WITH OXIDIZING MATERIALS. COMPLY WITH ALL NATIONAL, STATE OR PROVINCIAL & LOCAL CODES PERTAINING TO THE STORAGE, HANDLING, DISPENSING & DISPOSAL OF FLAMMABLE LIQUIDS.
Other Precautions:SINCE EMPTIED CONTAINERS RETAIN PRODUCT RESIDUE, FOLLOW LABEL WARNINGS EVEN AFTER CONTAINER IS EMPTIED. RESIDUAL VAPORS MAY EXPLODE ON IGNITION; DO NOT CUT, DRILL, GRIND OR WELD ON OR NEAR THIS CONTAINER.

Exposure Controls

Respiratory Protection:AN APPROVED RESPIRATOR MUST BE WORN IF EXPOSURE IS LIKELY TO EXCEED RECOMMENDED EXPOSURE LIMITS. RESPIRATOR TYPE: ORGANIC VAPOR.

Ventilation:GOOD GENERAL VENTILATION (TYPICALLY 10 AIR CHANGES PER HOUR) SHOULD BE USED. VENTILATION RATES SHOULD BE MATCHED TO CONDITIONS.

Protective Gloves:IMPERMEABLE GLOVES ARE RECOMMENDED.

Eye Protection:SAFETY GLASSES WITH SIDE SHIELDS (OR GOGGLES) ARE RECOMMENDED.

Other Protective Equipment:LOCAL EXHAUST VENTILATION OR AN ENCLOSED HANDLING SYSTEM MAY BE NEEDED TO CONTROL AIRBORNE LEVELS BELOW RECOMMENDED EXPOSURE LIMITS. RECOMMENDED DECONTAMINATION FACILITIES:EYE BATH & WASHING FACILITIES.

Work Hygienic Practices:NO DATA PROVIDED BY RESPONSIBLE PARTY.

Supplemental Safety and Health

PREVENTIVE MEASURES: AVOID BREATHING VAPOR AT CONCENTRATIONS GREATER THAN THE EXPOSURE LIMITS. AVOID PROLONGED OR REPEATED CONTACT WITH SKIN. KEEP CONTAINER CLOSED. USE WITH ADEQUATE VENTILATION.

Chemical Properties

HCC:F2

Boiling Pt:=-77.8C, 172.F

Melt/Freeze Pt:=-82.6C, -117.F

Vapor Pres:AT 20C(68F): 86 MMHG

Vapor Density:3.04 AIR=1

Spec Gravity:(WATER=1) AT 20C: 0.90Z

pH:NOT AVAILABLE

Viscosity:AT 20C (68F): 0.4519

Evaporation Rate & Reference:(N-BUTYL ACETATE =1): 4.1

Solubility in Water:MODERATE

Appearance and Odor:COLORLESS LIQUID. ODOR: SWEET, ESTER.

Stability

Stability Indicator/Materials to Avoid:YES

MATERIAL CAN REACT VIOLENTLY WITH: OXIDIZERS.

Stability Condition to Avoid:NO DATA PROVIDED BY RESPONSIBLE PARTY.

Hazardous Decomposition Products:HAZARDOUS COMBUSTION PRODUCTS: CARBON MONOXIDE, CARBON DIOXIDE.

Conditions to Avoid Polymerization:WILL NOT OCCUR.

Disposal

Waste Disposal Methods:(OBSERVE ALL LAWS CONCERNING HEALTH AND ENVIRONMENT.): INCINERATION.

Toxicology

Toxicological Information:TOXICITY DATA: ORAL LD-50 (RAT) = 5.6 G/KG; INHALATION LC50 (RAT) >8,000 PPM; DERMAL LD50 (RABBIT) > 20 ML/KG; SKIN IRRITATION (RABBIT) = SLIGHT; EYE IRRITATION (RABBIT) = SLIGHT; SKIN SENSITIZATION (HUMAN) = NONE. SUBCHRONIC TOXICITY DATA: GUINEA PIGS EXPOSED TO 2000 PPM ETHYL ACETATE FOR 4H/DAY, 6 DAYS/WK SHOWED NO EVIDENCE OF HARM AFTER 65 EXPOSURES. MICE WERE NARCOTIZED BUT RECOVERED FROM 3-4 HR EXPOSURE TO 5000 PPM.CATS EXPOSED TO 9200 PPM DEMONSTRATED SALIVATION & COUGHING & EXPOSURE TO 17,000 PPM WAS LETHAL. DEATHS ATTRIBUTED TO PULMONARY EDEMA, HEMMORHAGE, HYPEREMIA.

Other Information

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.

Ecology

Ecological:PRODUCT HAS THE FOLLOWING PROPERTIES: HIGH BIOCHEMICAL OXYGEN DEMAND& A POTENTIAL TO CAUSE OXYGEN DEPLETION IN AQUEOUS SYSTEMS, A LOW POTENTIAL TO AFFECT AQUATIC ORGANISMS, READY BIODEGRADABILITY TO U NACCLIMATED MICROORGAMISMS AND A LOW POTENTIAL TO BIOCONCENTRATE. WHEN DILUTED WITH WATER, THIS MATERIAL RELEASED DIRECTLY OR INDIRECTLY INTO THE ENVIRONMENT IS NOT EXPECTED TO HAVE A SIGNIFIGANT IMPA CT. OXYGEN DEMAND DATA: COD: 1.54 G OXYGEN/G; BOD-5: 1.24 G OXYGEN/G. ACUTE AQUATIC EFFECTS: 96 H LC50-DAPHNID: 2500 MG/L; 48 H LC50-GOLDEN ORFA: 270 MG/L.

Transport

Transport Information:US DOT CLASSIFICATION: FLAMMABLE LIQUID. DOT SHIPPING NAME & NUMBER: ETHYL ACETATE, UN1173. DOT REPORTABLE QUANTITY: 5000 LB. TDG (CANADA) CLASSIFICATION: CLASS 3.2, PACKING GROUP II. TDG SHIPPING NAM E AND NUMBER: ETHYL ACETATE, UN1173. ICAO CLASSIFICATION: CLASS 3, PACKING GROUP II. ICAO SHIPPING NAME AND NUMBER: ETHYL ACETATE, UN1173. IMDG CLASSIFICATION: CLASS 3.2. IMDG SHIPPING NAME AND NUMBER : ETHYL ACETATE, UN 1173.

Regulatory

SARA Title III Information:CHMICALS SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF TITLE III OF THE SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT (SARA) OF 1986 ANF 40 CFR 372 (USA): NONE. SARA (USA) SECTIONS 311/312 HA ZARD CLASSIFICATION: FIRE HAZARD.

Federal Regulatory Information:TSCA: THIS MATERIAL IS LISTED IN THE TSCA (USA) INVENTORY. OSHA (USA) HAZARDOUS CHEMICAL ACCORDING TO 29CFR 1910.1200. ETHYL ACETATE, ETHANOL.

State Regulatory Information:CHEMICAL(S) KNOWN TO THE STATE OF CALIFORNIA (USA) TO CAUSE CANCER: NONE. CHEMICAL(S) KNOWN TO THE STATE OF CALIFORNIA (USA) TO CAUSE ADVERSE REPRODUCTIVE EFFECTS: NONE.